



REVISED TRAFFIC IMPACT ANALYSIS REPORT
EAST LAKE SPECIFIC PLAN AMENDMENT No. 11
 Lake Elsinore, California
 March 22, 2017
 (Revision of the February 1, 2017 Report)

Prepared for:

City of Lake Elsinore
 130 South Main Street
 Lake Elsinore, CA 92530

LLG Ref. 2-14-3544-1



Prepared by:
 Justin Tucker
 Transportation Engineer I
 &
 Zawwar Saiyed, P.E.
 Senior Transportation Engineer

Under the Supervision of:
 Keil D. Maberry, P.E.
 Principal

Linscott, Law & Greenspan, Engineers
 2 Executive Circle
 Suite 250
 Irvine, CA 92614
949.825.6175 T
 949.825.6173 F
www.llgengineers.com

TABLE OF CONTENTS

| SECTION | PAGE |
|--|-----------|
| Executive Summary | xv |
| 1.0 Introduction..... | 1 |
| 1.1 Study Area | 2 |
| 1.1.1 Intersections | 2 |
| 1.1.2 Roadway Segments | 3 |
| 1.2 Traffic Impact Analysis Components..... | 4 |
| 1.3 Traffic Impact Analysis Scenarios | 5 |
| 2.0 Project Description and Location..... | 6 |
| 2.1 East Lake Specific Plan Circulation | 6 |
| 3.0 Analysis Conditions and Methodology | 8 |
| 3.1 Existing Street Network | 8 |
| 3.2 Existing Street Network | 8 |
| 3.3 Existing Transit Services..... | 9 |
| 3.4 Existing Traffic Volumes | 10 |
| 3.5 Level Of Service (LOS) Analysis Methodologies | 10 |
| 3.5.1 Highway Capacity Manual (HCM) Method of Analysis (Signalized Intersections)..... | 10 |
| 3.5.2 Highway Capacity Manual (HCM) Method of Analysis (Unsignalized Intersections)..... | 10 |
| 3.5.2.1 Two-Way Stop-Controlled Intersections | 11 |
| 3.5.2.2 All-Way Stop-Controlled Intersections | 11 |
| 3.5.3 Volume to Capacity (V/C) Ratio Method of Analysis (Roadway Segments) .. | 11 |
| 3.5.4 Basic Freeway Segments | 11 |
| 3.5.5 Freeway Merge And Diverge Segments | 12 |
| 3.6 Impact Criteria and Thresholds | 12 |
| 4.0 Project Traffic Characteristics | 21 |
| 4.1 Project Trip Generation Forecast and Assignment..... | 21 |
| 4.1.1 Year 2022 East Lake Specific Plan Project Phase I Assignment..... | 21 |
| 4.1.2 Year 2040 East Lake Specific Plan Project Buildout Assignment | 21 |
| 4.2 Vehicle Miles Travelled (VMT)..... | 21 |
| 5.0 Future Traffic Conditions | 22 |
| 5.1 Travel Demand Model Methodology | 22 |
| 5.1.1 Volume Adjustment | 22 |
| 5.1.2 B-turn Methodology..... | 22 |
| 5.2 Existing With East Lake Specific Plan Project Buildout Traffic Volumes | 23 |

TABLE OF CONTENTS (CONTINUED)

| SECTION | PAGE |
|---|-----------|
| 5.3 Year 2022 Cumulative Traffic Conditions | 23 |
| 5.3.1 Cumulative Projects Traffic | 23 |
| 5.4 Year 2022 Without East Lake Specific Plan Project Phase I Traffic Volumes..... | 24 |
| 5.5 Year 2022 With East Lake Specific Plan Project Phase I Traffic Volumes..... | 24 |
| 5.6 Year 2040 With Adopted Specific Plan Traffic Volumes..... | 24 |
| 5.7 Year 2040 With East Lake Specific Plan Project Buildout Traffic Volumes | 25 |
| 6.0 Existing Conditions Traffic Impact Analysis | 27 |
| 6.1 Existing Conditions Intersection Capacity Analysis | 27 |
| 6.1.1 Existing Traffic Conditions..... | 27 |
| 6.1.2 Existing With East Lake Specific Plan Project Buildout Traffic Conditions | 27 |
| 6.2 Existing Conditions Roadway Segment Analysis | 34 |
| 6.2.1 Existing Traffic Conditions..... | 34 |
| 6.2.2 Existing With East Lake Specific Plan Project Buildout Traffic Conditions | 34 |
| 7.0 Year 2022 Conditions Traffic Impact Analysis..... | 43 |
| 7.1 Year 2022 Conditions Intersection Capacity Analysis..... | 43 |
| 7.1.1 Year 2022 Without East Lake Specific Plan Project Phase I Traffic Conditions | 44 |
| 7.1.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions ... | 44 |
| 7.2 Year 2022 Conditions Roadway Segment Analysis..... | 51 |
| 7.2.1 Year 2022 Without East Lake Specific Plan Project Phase I Traffic Conditions | 51 |
| 7.2.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions ... | 52 |
| 8.0 Year 2040 Conditions Traffic Impact Analysis..... | 63 |
| 8.1 Year 2040 Conditions Intersection Capacity Analysis..... | 63 |
| 8.1.1 Year 2040 With Adopted Specific Plan Traffic Conditions | 64 |
| 8.1.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions | 65 |
| 8.2 Year 2040 Conditions Roadway Segment Analysis..... | 71 |
| 8.2.1 Year 2040 With Adopted Specific Plan Traffic Conditions | 72 |
| 8.2.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions | 72 |
| 9.0 Planned and Recommended Improvements..... | 82 |
| 9.1 Internal Network Planned Improvements..... | 82 |
| 9.1.1 Project Phase I Planned Improvements..... | 82 |
| 9.1.1.1 Intersections | 82 |

TABLE OF CONTENTS (CONTINUED)

| SECTION | PAGE |
|---|------------|
| 9.1.1.2 Roadway Segments | 83 |
| 9.1.2 Project Buildout Planned Improvements | 83 |
| 9.1.2.1 Intersections | 83 |
| 9.1.2.2 Roadway Segments | 84 |
| 9.2 External Network Planned Improvements | 84 |
| 9.2.1 Existing With East Lake Specific Plan Project Buildout | |
| Planned Improvements..... | 84 |
| 9.2.1.1 Intersections | 84 |
| 9.2.1.2 Roadway Segments | 85 |
| 9.2.2 Year 2022 Planned Improvements..... | 85 |
| 9.2.2.1 Intersections | 85 |
| 9.2.2.2 Roadway Segments | 86 |
| 9.2.3 Year 2040 Planned Improvements..... | 87 |
| 9.2.3.1 Intersections | 87 |
| 9.2.3.2 Roadway Segments | 90 |
| 9.3 Recommended Improvements | 91 |
| 9.3.1 Existing With East Lake Specific Plan Project Buildout Traffic Conditions ... | 91 |
| 9.3.1.1 Intersections | 91 |
| 9.3.1.2 Roadway Segments | 92 |
| 9.3.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions ... | 92 |
| 9.3.2.1 Intersections | 92 |
| 9.3.2.2 Roadway Segments | 94 |
| 9.3.3 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions. | 94 |
| 9.3.3.1 Intersections | 94 |
| 9.3.3.2 Roadway Segments | 95 |
| 10.0 Traffic Signal Warrant Analysis | 96 |
| 10.1 Existing With East Lake Specific Plan Project Buildout Traffic Conditions..... | 96 |
| 10.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions | 97 |
| 10.3 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions | 97 |
| 11.0 Project Fair Share Analysis | 100 |
| 11.1 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions | 100 |
| 11.1.1 Intersections | 100 |
| 11.1.2 Roadway Segments | 101 |
| 11.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions | 101 |
| 11.2.1 Intersections | 101 |
| 11.2.2 Roadway Segments | 101 |

TABLE OF CONTENTS (CONTINUED)

| SECTION | PAGE |
|--|------------|
| 12.0 Existing Conditions Caltrans Facilities Analysis | 105 |
| 12.1 Existing Conditions Basic Freeway Segment Capacity Analysis | 106 |
| 12.1.1 Existing Traffic Conditions..... | 106 |
| 12.1.2 Existing With East Lake Specific Plan Project Buildout Traffic Conditions .. | 106 |
| 12.2 Existing Conditions Freeway Merge And Diverge Segments Capacity Analysis | 108 |
| 12.2.1 Existing Traffic Conditions..... | 108 |
| 12.2.2 Existing With East Lake Specific Plan Project Buildout Traffic Conditions .. | 108 |
| 13.0 Year 2022 Conditions Caltrans Facilities Analysis..... | 110 |
| 13.1 Year 2022 Conditions Basic Freeway Segment Capacity Analysis | 111 |
| 13.1.1 Year 2022 Without East Lake Specific Plan Phase I Traffic Conditions | 111 |
| 13.1.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions .. | 111 |
| 13.2 Year 2022 Conditions Freeway Merge And Diverge Segments Capacity Analysis | 114 |
| 13.2.1 Year 2022 Without East Lake Specific Plan Project Phase I Traffic Conditions .. | 114 |
| 13.2.2 Year 2022 With East lake Specific Plan Phase I Traffic Conditions..... | 114 |
| 14.0 Year 2040 Conditions Caltrans Facilities Analysis..... | 116 |
| 14.1 Year 2040 Conditions Basic Freeway Segment Capacity Analysis | 117 |
| 14.1.1 Year 2040 With Adopted Specific Plan Traffic Conditions | 117 |
| 14.1.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions .. | 117 |
| 14.2 Year 2040 Conditions Freeway Merge And Diverge Segments Capacity Analysis | 120 |
| 14.2.1 Year 2040 With Adopted Specific Plan Traffic Conditions | 120 |
| 14.2.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions .. | 120 |
| 15.0 Caltrans Facilities Planned And Recommended Improvements..... | 123 |
| 15.1 Railroad Canyon Road Interchange Project Planned Improvements | 123 |
| 15.1.1 Basic Freeway Segments | 123 |
| 15.1.1.1 Year 2022 Without ELSP Project Phase I, Year 2022 With ELSP Project Phase I, Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout Traffic Conditions | 123 |
| 15.1.2 Freeway Merge And Diverge Segments | 123 |
| 15.1.2.1 Year 2022 Without ELSP Project Phase I, Year 2022 With ELSP Project Phase I, Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout Traffic Conditions | 123 |
| 15.2 Recommended Improvements | 124 |
| 15.2.1 Basic Freeway Segments | 124 |

TABLE OF CONTENTS (CONTINUED)

| SECTION | PAGE |
|--|------|
| 15.2.1.1 Existing With East Lake Specific Plan Project Buildout Traffic Conditions | 124 |
| 15.2.1.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions | 124 |
| 15.2.1.3 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions | 124 |
| 15.2.2 Freeway Merge And Diverge Segments | 125 |
| 15.2.2.1 Existing With East Lake Specific Plan Project Buildout Traffic Conditions | 125 |
| 15.2.2.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions | 125 |
| 15.2.2.3 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions | 125 |

APPENDICES

APPENDIX

A. Approved Traffic Impact Study Scope of Work

B. Existing Traffic Count Data

- B-I Intersection Counts
- B-II Roadway Segment Counts

C. Traffic Model Post-Processing Worksheets

- C-I Existing With ELSP Project Buildout Intersection Volumes
- C-II Existing With ELSP Project Buildout Roadway Segment Volumes
- C-III Year 2022 Without ELSP Project Phase I Intersection Volumes
- C-IV Year 2022 Without ELSP Project Phase I Roadway Segment Volumes
- C-VI Year 2022 With ELSP Project Phase I Intersection Volumes
- C-VII Year 2022 With ELSP Project Phase I Roadway Segment Volumes
- C-VIII Year 2040 With Adopted Specific Plan Intersection Volumes
- C-IX Year 2040 With Adopted Specific Plan Roadway Segment Volumes
- C-X Year 2040 With ELSP Project Buildout Intersection Volumes
- C-XI Year 2040 With ELSP Project Buildout Roadway Segment Volumes

D. Existing Traffic Conditions Intersection Level of Service Calculation Worksheets

- D-I Existing Traffic Conditions
- D-II Existing With ELSP Project Buildout Traffic Conditions
- D-III Existing With ELSP Project Buildout With Mitigation Traffic Conditions

E. Year 2022 Traffic Conditions Intersection Level of Service Calculation Worksheets

- E-I Year 2022 Without ELSP Project Phase I Traffic Conditions
- E-II Year 2022 With ELSP Project Phase I Traffic Conditions
- E-III Year 2022 With ELSP Project Phase I With Mitigation Traffic Conditions

F. Year 2040 Traffic Conditions Intersection Level of Service Calculation Worksheets

- F-I Year 2040 With Adopted Specific Plan Traffic Conditions
- F-II Year 2040 With ELSP Project Buildout Traffic Conditions
- F-III Year 2040 With ELSP Project Buildout With Mitigation Traffic Conditions

G. Intersection Traffic Signal Warrant Analysis Worksheets

- G-I Existing With ELSP Project Buildout Traffic Conditions
- G-II Year 2022 With ELSP Project Phase I Traffic Conditions
- G-III Year 2040 With ELSP Project Buildout Traffic Conditions

APPENDICES (CONTINUED)

APPENDIX

- H. Existing Traffic Conditions Basic Freeway Segments Level of Service Calculation Worksheets**
 - H-I Existing Traffic Conditions
 - H-II Existing With ELSP Project Buildout Traffic Conditions
 - H-III Existing With ELSP Project Buildout With Mitigation Traffic Conditions
- I. Existing Traffic Conditions Freeway Merge And Diverge Segments Level of Service Calculation Worksheets**
 - I-I Existing Traffic Conditions
 - I-II Existing With ELSP Project Buildout Traffic Conditions
 - I-III Existing With ELSP Project Buildout With Mitigation Traffic Conditions
- J. Year 2022 Traffic Conditions Basic Freeway Segments Level of Service Calculation Worksheets**
 - J-I Year 2022 Without ELSP Project Phase I Traffic Conditions
 - J-II Year 2022 With ELSP Project Phase I Traffic Conditions
 - J-III Year 2022 With ELSP Project Phase I With Mitigation Traffic Conditions
- K. Year 2022 Traffic Conditions Freeway Merge And Diverge Segments Level of Service Calculation Worksheets**
 - K-I Year 2022 Without ELSP Project Phase I Traffic Conditions
 - K-II Year 2022 With ELSP Project Phase I Traffic Conditions
 - K-III Year 2022 With ELSP Project Phase I With Mitigation Traffic Conditions
- L. Year 2040 Traffic Conditions Basic Freeway Segments Level of Service Calculation Worksheets**
 - L-I Year 2040 With Adopted Specific Plan Traffic Conditions
 - L-II Year 2040 With ELSP Project Buildout Traffic Conditions
 - L-III Year 2040 With ELSP Project Buildout With Mitigation Traffic Conditions
- M. Year 2040 Traffic Conditions Freeway Merge And Diverge Segments Level of Service Calculation Worksheets**
 - M-I Year 2040 With Adopted Specific Plan Traffic Conditions
 - M-II Year 2040 With ELSP Project Buildout Traffic Conditions
 - M-III Year 2040 With ELSP Project Buildout With Mitigation Traffic Conditions

LIST OF FIGURES

| SECTION – FIGURE # | FOLLOWING PAGE |
|--|----------------|
| 1-1 Vicinity Map | 5 |
| 2-1 Existing Aerial Site Plan | 7 |
| 2-2 Proposed East Lake Specific Plan Land Use Map | 7 |
| 2-3 Proposed East Lake Specific Plan Circulation Map..... | 7 |
| 2-4 Adopted Specific Plan Land Use Map | 7 |
| 2-5 City of Lake Elsinore Circulation Element | 7 |
| 3-1 Existing Roadway Conditions and Intersection Controls | 20 |
| 3-2 Existing Weekday AM Peak Hour Traffic Volumes..... | 20 |
| 3-3 Existing Weekday PM Peak Hour Traffic Volumes..... | 20 |
| 3-4 Existing Saturday Midday Peak Hour Traffic Volumes..... | 20 |
| 3-5 Existing Weekday Daily Traffic Volumes | 20 |
| 3-6 Existing Saturday Daily Traffic Volumes | 20 |
| 4-1 ELSP Project Phase I Weekday Daily Traffic Volumes | 21 |
| 4-2 ELSP Project Phase I Saturday Daily Traffic Volumes | 21 |
| 4-3 ELSP Project Buildout Weekday Daily Traffic Volumes | 21 |
| 4-4 ELSP Project Buildout Saturday Daily Traffic Volumes | 21 |
| 5-1 Existing With ELSP Project Buildout Weekday AM Peak Hour Traffic Volumes | 26 |
| 5-2 Existing With ELSP Project Buildout Weekday PM Peak Hour Traffic Volumes | 26 |
| 5-3 Existing With ELSP Project Buildout Saturday Midday Peak Hour Traffic Volumes | 26 |
| 5-4 Existing With ELSP Project Buildout Weekday Daily Traffic Volumes | 26 |
| 5-5 Existing With ELSP Project Buildout Saturday Daily Traffic Volumes | 26 |
| 5-6 Location of Cumulative Projects | 26 |
| 5-7 Year 2022 Without ELSP Project Phase I Weekday AM Peak Hour Traffic Volumes | 26 |
| 5-8 Year 2022 Without ELSP Project Phase I Weekday PM Peak Hour Traffic Volumes..... | 26 |
| 5-9 Year 2022 Without ELSP Project Phase I Saturday Midday Peak Hour Traffic Volumes ... | 26 |
| 5-10 Year 2022 Without ELSP Project Phase I Weekday Daily Traffic Volumes | 26 |
| 5-11 Year 2022 Without ELSP Project Phase I Saturday Daily Traffic Volumes | 26 |
| 5-12 Year 2022 With ELSP Project Phase I Weekday AM Peak Hour Traffic Volumes..... | 26 |

LIST OF FIGURES (CONTINUED)

| SECTION – FIGURE # | FOLLOWING PAGE |
|---|----------------|
| 5–13 Year 2022 With ELSP Project Phase I Weekday PM Peak Hour Traffic Volumes | 26 |
| 5–14 Year 2022 With ELSP Project Phase I Saturday Midday Peak Hour Traffic Volumes | 26 |
| 5–15 Year 2022 With ELSP Project Phase I Weekday Daily Traffic Volumes | 26 |
| 5–16 Year 2022 With ELSP Project Phase I Saturday Daily Traffic Volumes | 26 |
| 5–17 Year 2040 With Adopted Specific Plan Weekday AM Peak Hour Traffic Volumes | 26 |
| 5–18 Year 2040 With Adopted Specific Plan Weekday PM Peak Hour Traffic Volumes | 26 |
| 5–19 Year 2040 With Adopted Specific Plan Saturday Midday Peak Hour Traffic Volumes | 26 |
| 5–20 Year 2040 With Adopted Specific Plan Weekday Daily Traffic Volumes | 26 |
| 5–21 Year 2040 With Adopted Specific Plan Saturday Daily Traffic Volumes | 26 |
| 5–22 Year 2040 With ELSP Project Buildout Weekday AM Peak Hour Traffic Volumes | 26 |
| 5–23 Year 2040 With ELSP Project Buildout Weekday PM Peak Hour Traffic Volumes | 26 |
| 5–24 Year 2040 With ELSP Project Buildout Saturday Midday Peak Hour Traffic Volumes | 26 |
| 5–25 Year 2040 With ELSP Project Buildout Weekday Daily Traffic Volumes | 26 |
| 5–26 Year 2040 With ELSP Project Buildout Saturday Daily Traffic Volumes | 26 |
| 9–1 Existing With Project Planned and Recommended Improvements | 95 |
| 9–2 Year 2022 With ELSP Project Phase I Planned and Recommended Improvements | 95 |
| 9–3 Year 2040 With ELSP Project Buildout Planned and Recommended Improvements | 95 |

LIST OF TABLES

| SECTION-TABLE# | | PAGE |
|----------------|--|-------|
| 2-1 | East Lake Specific Plan Land Use Phasing Summary..... | 7 |
| 3-1 | Level of Service Criteria For Signalized Intersections (HCM Methodology)..... | 15 |
| 3-2 | Level of Service Criteria For Unsignalized Intersections (HCM Methodology) | 16 |
| 3-3 | Level of Service Criteria For Roadway Segments (V/C Methodology)..... | 17 |
| 3-4 | Daily Roadway Segment Capacities | 18 |
| 3-5 | Basic Freeway Segments Level of Service Criteria (HCM Methodology) | 19 |
| 3-6 | Freeway Merge and Diverge Segments Level of Service Criteria (HCM Methodology) | 20 |
| 5-1 | Location and Description of Cumulative Projects – Phase I and Buildout Development Totals | 26 |
| 6-1 | Existing With ELSP Project Buildout Conditions Peak Hour Intersection Capacity Analysis Summary | 29-33 |
| 6-2 | Existing With ELSP Project Buildout Conditions Daily Roadway Segment Capacity Analysis Summary..... | 35-41 |
| 6-3 | Existing With ELSP Project Buildout Conditions Peak Hour Roadway Segment Capacity Analysis Summary | 42 |
| 7-1 | Year 2022 With ELSP Project Phase I Conditions Peak Hour Intersection Capacity Analysis Summary | 46-50 |
| 7-2 | Year 2022 With ELSP Project Phase I Conditions Daily Roadway Segment Capacity Analysis Summary..... | 53-59 |
| 7-3 | Year 2022 With ELSP Project Phase I Conditions Peak Hour Roadway Segment Capacity Analysis Summary | 60-62 |
| 8-1 | Year 2040 With ELSP Project Buildout Conditions Peak Hour Intersection Capacity Analysis Summary | 66-70 |
| 8-2 | Year 2040 With ELSP Project Buildout Conditions Daily Roadway Segment Capacity Analysis Summary..... | 73-79 |
| 8-3 | Year 2040 With ELSP Project Buildout Conditions Peak Hour Roadway Segment Capacity Analysis Summary | 80-81 |

LIST OF TABLES (CONTINUED)

| SECTION-TABLE# | | PAGE |
|----------------|---|------|
| 10-1 | Intersection Traffic Signal Warrant Analysis Summary | 99 |
| 11-1 | Year 2022 With ELSP Project Phase I Conditions Traffic Conditions | |
| | Fair Share Contribution | 103 |
| 11-2 | Year 2040 With ELSP Project Buildout Conditions Traffic Conditions Intersection | |
| | Fair Share Contribution | 104 |
| 12-1 | Existing With ELSP Project Buildout Conditions | |
| | Peak Hour Basic Freeway Segments Capacity Analysis Summary..... | 107 |
| 12-2 | Existing With ELSP Project Buildout Conditions | |
| | Peak Hour Freeway Merge and Diverge Segments Capacity Analysis Summary | 109 |
| 13-1 | Year 2022 With ELSP Project Phase I Conditions | |
| | Peak Hour Basic Freeway Segments Capacity Analysis Summary..... | 113 |
| 13-2 | Year 2022 With ELSP Project Phase I Conditions | |
| | Peak Hour Freeway Merge and Diverge Segments Capacity Analysis Summary | 115 |
| 14-1 | Year 2040 With ELSP Project Buildout Conditions | |
| | Peak Hour Basic Freeway Segments Capacity Analysis Summary..... | 119 |
| 14-2 | Year 2040 With ELSP Project Buildout Conditions | |
| | Peak Hour Freeway Merge and Diverge Segments Capacity Analysis Summary | 122 |

EXECUTIVE SUMMARY

Project Description

- The proposed East Lake Specific Plan Amendment No. 11 (hereinafter referred to as Project). This Specific Plan Amendment is anticipated to replace the currently Adopted Specific Plan. The East Lake Specific Plan was originally prepared in 1993 and has since been subject to ten amendments as the land use designations within continued to evolve, the most recent of which has been adopted by the City of Lake Elsinore as previously mentioned. The City of Lake Elsinore is striving to promote “Dream Extreme” character to the Project by supporting uses including unique sporting and recreational venues as well as commercial, restaurant, hotel, open space, and residential uses. More specifically, the “Dream Extreme” character of the Project, as described by the City of Lake Elsinore, will consist of active sports-related facilities such as skydiving, hang-gliding, motor cross, and a golf course. East Lake Specific Plan consists of eight planning areas (PA-1, 2, 3, 4, 5, 6, 7, and 8) over nearly 3,000 acres. The Project is anticipated to be completed in two phases. Phase 1 is expected to be complete by the Year 2022 and buildout of the Specific Plan is expected to be complete by the Year 2040.
- The East Lake Specific Plan is generally located east of Lake Elsinore, south of Lakeshore Drive, west of Mission Trail/Corydon Road and North of Grand Avenue. The East Lake Specific Plan will consist of major mixed-use development including land uses such as residential, commercial, action sports, tourism, golf course/parks, preservation/mitigation areas, an airport and other uses.

Study Area

- Twenty-three (23) existing key study intersections and seven (7) future internal intersections were designated for evaluation based on discussions with City staff. The key intersections selected for evaluation in this report provide local and regional access to the study area and are listed as follows, along with their respective jurisdictions:
 1. Railroad Canyon Road at Summerhill Lane/Grape Street (Lake Elsinore)
 2. Railroad Canyon Road at I-15 NB Ramps (Lake Elsinore)
 3. Diamond Drive at I-15 SB Ramps (Lake Elsinore)
 4. Diamond Drive at Casino Drive/Auto Center Drive (Lake Elsinore)
 5. Lucerne Street at Lakeshore Drive (Lake Elsinore)
 6. Diamond Drive at Lakeshore Drive/Mission Trail (Lake Elsinore)
 7. Diamond Drive at Campbell Street (Lake Elsinore)

8. Mission Trail at Campbell Street (Lake Elsinore)
9. Diamond Drive at Malaga Road (Lake Elsinore)
10. Mission Trail at Malaga Road (Lake Elsinore/Wildomar)
11. Mission Trail at Olive Street (Lake Elsinore/Wildomar)
12. Mission Trail at Victorian Lane (Lake Elsinore/Wildomar)
13. Mission Trail at Lemon Street (Lake Elsinore/Wildomar)
14. Mission Trail at Corydon Road (Lake Elsinore/Wildomar)
15. Corydon Road at Cereal Street (Lake Elsinore/Wildomar)
16. Mission Trail at Bundy Canyon Road (Wildomar)
17. Orange Street at Bundy Canyon Road (Wildomar)
18. I-15 SB Ramps at Bundy Canyon Road (Wildomar)
19. I-15 NB Ramps at Bundy Canyon Road (Wildomar)
20. Corydon Road at Palomar Street (Lake Elsinore/Wildomar)
21. Mission Trail at Palomar Street (Wildomar)
22. Stoneman Street at Grand Avenue (Lake Elsinore)
23. Corydon Road at Grand Avenue (Lake Elsinore/Wildomar)
24. Grape Street at I-15 NB Ramps (Lake Elsinore) *[Future-Phase I]*
25. Diamond Drive at Olive Street (Lake Elsinore) *[Future-Phase I]*
26. “A” Street at Olive Street (Lake Elsinore) *[Future-Phase I]*
27. “A” Street at Victorian Lane (Lake Elsinore) *[Future-Phase I]*
28. “A” Street at Cereal Street (Lake Elsinore) *[Future-Phase I]*
29. Lucerne Street at Sylvester Street (Lake Elsinore) *[Future-Buildout]*
30. Stoneman Street at Cereal Street (Lake Elsinore) *[Future-Buildout]*

- The study roadway segments listed below, along with their respective jurisdictions, are locations that could potentially be impacted by the Project. The twenty-six (26) existing roadway segments and six (6) future roadway segments listed below were selected based on the arterial network within the study area and discussions with City of Lake Elsinore staff:

1. Grape Street, east of Railroad Canyon Road (Lake Elsinore)
2. Railroad Canyon Rd, between Summerhill Dr/Grape St and Lakeshore Dr/Mission Trail (Lake Elsinore)
3. Lucerne Street, south of Lakeshore Drive (Lake Elsinore)
4. Casino Drive, east of Diamond Drive (Lake Elsinore)

5. Diamond Drive, between Lakeshore Drive/Mission Trail and Campbell Street (Lake Elsinore)
6. Diamond Drive, between Campbell Street and Malaga Road (Lake Elsinore)
7. Mission Trail, between Diamond Drive and Campbell Street (Lake Elsinore)
8. Mission Trail, between Campbell Street and Malaga Road (Lake Elsinore)
9. Malaga Road, between Diamond Drive and Mission Trail (Lake Elsinore)
10. Malaga Road, east of Mission Trail (Lake Elsinore/Wildomar)
11. Diamond Drive, north of Summerly Place (Lake Elsinore)
12. Mission Trail, between Malaga Road and Olive Street (Lake Elsinore/Wildomar)
13. Olive Street, between Mission Trail and Grape Street (Wildomar)
14. Mission Trail, between Olive Street and Victorian Lane (Lake Elsinore/Wildomar)
15. Mission Trail, between Victorian Lane and Lemon Street (Lake Elsinore/Wildomar)
16. Lemon Street, between Mission Trail and Grape Street (Wildomar)
17. Corydon Road, between Mission Trail and Cereal Street (Lake Elsinore/Wildomar)
18. Cereal Street, west of Corydon Road (Lake Elsinore)
19. Mission Trail, between Corydon Road and Bundy Canyon Road (Wildomar)
20. Bundy Canyon Road, between Mission Trail and I-15 SB Ramps (Wildomar)
21. Corydon Road, between Cereal Street and Palomar Street (Lake Elsinore/Wildomar)
22. Mission Trail, between Bundy Canyon Road and Palomar Street (Wildomar)
23. Palomar Street, between Corydon Road and Mission Trail (Wildomar)
24. Stoneman Street, north of Grand Avenue (Lake Elsinore)
25. Skylark Drive, north of Grand Avenue (Lake Elsinore)
26. Corydon Road, between Palomar Street and Grand Avenue (Lake Elsinore/Wildomar)
27. Sylvester Street, between Lucerne Street and Diamond Drive (Lake Elsinore)
[Future-Phase I]
28. Lucerne Street, between Sylvester Street and Cereal Street (Lake Elsinore)
[Future-Phase I]
29. Cereal Street, between Lucerne Street and Stoneman Street (Lake Elsinore)
[Future-Phase I]
30. Cereal Street, between Stoneman Street and Diamond Drive (Lake Elsinore)
[Future-Phase I]
31. Diamond Drive, between Olive Street and Cereal Street (Lake Elsinore)
[Future-Phase I]

32. Bundy Canyon Road, between Corydon Road and Mission Trail (Lake Elsinore)
[Future-Phase I]

Cumulative Projects Traffic

- The City of Lake Elsinore and the City of Wildomar identified eight (8) large cumulative projects within the Project study area that were included in the model runs prior to developing traffic volumes. Furthermore, due to its proximity to the East Lake Specific Plan and the large amount of volume it attracts during the Saturday peak hour, the Diamond Sports Center project was manually assigned to the Year 2022 traffic volumes and Year 2040 traffic volumes after these volumes were post-processed from the model runs.

Traffic Impact Analysis

Existing Traffic Conditions

- For the Existing traffic conditions, two (2) of the key study intersections (although intersection 24 does not exist in Existing traffic conditions) currently operate at unacceptable levels of service during the AM, PM, and/or Saturday Midday peak hour when compared to the LOS standards defined in this report. The remaining key study intersections currently operate at acceptable levels of service during the AM, PM, and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|--|----------------------------|-------------------|----------------------------|-------------------|---|-------------------|
| | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> |
| 17. Orange Street at Bundy Canyon Road | 294.4 | F | 112.5 | F | 150.7 | F |
| 22. Stoneman Street at Grand Avenue | 41.7 | E | 38.3 | E | -- | -- |

- For the Existing traffic conditions, one (1) of the key study roadway segments currently operates at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway segments currently operate at acceptable levels of service on daily basis. The roadway segment operating at an adverse level of service is:

| <u>Key Roadway Segment</u> | <u>Weekday Daily</u> | | | <u>Saturday Daily</u> | | |
|--|-----------------------------|-------------------------|-------------------|------------------------------|-------------------------|-------------------|
| | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> |
| 17. Corydon Road, <i>between</i> Mission Trail and Cereal Street | 16,978 | 0.943 | E | -- | -- | -- |

Existing With East Lake Specific Plan Project Buildout Traffic Conditions

- For the Existing With ELSP Project Buildout traffic conditions, six (6) key study intersections are forecast to operate at unacceptable levels of service during the AM PM, and/or Saturday Midday peak hours when compared to the LOS standards defined in this report. The remaining key study intersections are forecast to operate at acceptable levels of service during the AM, PM, and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|---|------------------------------|------------|------------------------------|------------|----------------------------------|------------|
| | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> |
| 5. Lucerne Street at Lakeshore Drive | 374.0 | F | 373.4 | F | 725.3 | F |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | -- | -- | -- | -- | 105.4 | F |
| 12. Mission Trail at Victorian Lane | -- | -- | 45.5 | E | 39.4 | E |
| 17. Orange Street at Bundy Canyon Road | 279.9 | F | 130.6 | F | 116.4 | F |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | 55.3 | E | -- | -- | -- | -- |
| 22. Stoneman Street at Grand Avenue | 66.2 | F | 56.9 | F | -- | -- |

Six (6) key study intersections will have a significant impact under the Existing With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report. However, recommended improvements outlined in this report will offset the impact of the Existing With ELSP Project Buildout traffic and bring the significantly impacted intersections to below Existing and/or acceptable conditions at five (5) of the six (6) impacted locations. It should be noted that key study intersection #6, Diamond Drive at Lakeshore Drive/Mission Trail, was mitigated to a feasible extent but does not lower the level of service enough in order to bring below Existing and/or acceptable conditions.

- For the Existing With ELSP Project Buildout traffic conditions, two (2) key study roadway segments are forecast to operate at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway segments are forecast to operate at acceptable levels of service on a daily basis. The roadway segments operating at adverse levels of service are:

| <u>Key Roadway Segment</u> | <u>Weekday Daily</u> | | | <u>Saturday Daily</u> | | |
|---|----------------------|------------------|------------|-----------------------|------------------|------------|
| | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> |
| 17. Corydon Road, <i>between</i> Mission Trail and Cereal Street | 19,795 | 1.100 | F | 19,227 | 1.068 | F |
| 20. Bundy Canyon Road, <i>between</i> Mission Trail and I-15 SB Ramps | 11,968 | 0.921 | E | -- | -- | -- |

To determine if the ELSP Project Buildout creates a significant impact, these adverse roadway segments are further analyzed under peak hour conditions to determine if there are any peak hour deficiencies. These study roadway segments are forecast to operate at LOS A

during the AM, PM, and Saturday Midday peak hours. As a result, the key study roadway segments are not significantly impacted by Existing With ELSP Project Buildout traffic and therefore no improvements are required.

Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

- For the Year 2022 With ELSP Project Phase I traffic conditions, eleven (11) key study intersections are forecast to operate at unacceptable levels of service during the AM, PM, and/or Saturday Midday peak hours when compared to the LOS standards defined in this report. The remaining key study intersections are forecast to operate at acceptable levels of service during the AM, PM, and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|---|---------------------|------------|---------------------|------------|----------------------------------|------------|
| | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | 80.5 | F | 174.7 | F | 335.0 | F |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | -- | -- | -- | -- | 84.0 | F |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | -- | -- | 84.8 | F | 197.0 | F |
| 7. Diamond Drive at Campbell Street | -- | -- | -- | -- | 626.1 | F |
| 8. Mission Trail at Campbell Street | -- | -- | -- | -- | 76.5 | F |
| 9. Diamond Drive at Malaga Road | -- | -- | -- | -- | 322.6 | F |
| 15. Corydon Road at Cereal Street | 55.7 | E | -- | -- | -- | -- |
| 17. Orange Street at Bundy Canyon Road | 288.1 | F | 168.8 | F | 331.3 | F |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | 65.8 | E | -- | -- | 77.7 | E |
| 22. Stoneman Street at Grand Avenue | 442.0 | F | 664.7 | F | -- | -- |
| 24. Grape Street at I-15 Northbound Ramps | -- | -- | -- | -- | 257.1 | F |

Eleven (11) key study intersections will have a significant impact under the Year 2022 With ELSP Project Phase I traffic conditions when compared to the LOS criteria defined in this report. However, the implementation of recommended improvements outlined in this report will offset the impact of the ELSP Project Phase I traffic and bring the significantly impacted intersections to pre-Project and/or acceptable conditions at nine (9) of the eleven (11) impacted locations. It should be noted that key study intersections #1, Railroad Canyon Road at Summerhill Lane/Grape Street, and #6, Diamond Drive at Lakeshore Drive/Mission Trail, were mitigated to a feasible extent but do not lower the level of service enough to acceptable conditions. It should also be noted that the mitigation for key study intersection #4, Diamond Drive at Casino Drive/Auto Center Drive, is infeasible due to the surrounding parcels preventing the additional needed right-of-way.

- For the Year 2022 With ELSP Project Phase I traffic conditions, six (6) key study roadway segments are forecast to operate at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway

segments are forecast to operate at acceptable levels of service on a daily basis. The roadway segments operating at adverse levels of service are:

| <u>Key Roadway Segment</u> | <u>Weekday Daily</u> | | | <u>Saturday Daily</u> | | |
|---|-----------------------------|-------------------------|-------------------|------------------------------|-------------------------|-------------------|
| | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | 35,311 | 1.036 | F | 41,902 | 1.229 | F |
| 15. Mission Trail, <i>between Victorian Lane and Lemon Street</i> | 23,456 | 0.906 | E | -- | -- | -- |
| 17. Corydon Road, <i>between Mission Trail and Cereal Street</i> | 17,177 | 0.954 | E | -- | -- | -- |
| 20. Bundy Canyon Road, <i>between Mission Trail and I-15 SB Ramps</i> | 19,789 | 1.522 | F | 19,035 | 1.464 | F |
| 21. Corydon Road, <i>between Cereal Street and Palomar Street</i> | 23,915 | 1.329 | F | 22,691 | 1.261 | F |
| 26. Corydon Road, <i>between Palomar Street and Grand Avenue</i> | 17,681 | 0.982 | E | 16,582 | 0.921 | E |

To determine if the ELSP Project Phase I creates a significant impact, these adverse roadway segments are further analyzed under peak hour conditions to determine if there are any peak hour deficiencies. These study roadway segments are forecast to operate at LOS D or better during the AM, PM, and Saturday Midday peak hours. As a result, the key study roadway segments are not significantly impacted by Year 2022 With ELSP Project Phase I traffic and therefore no improvements are required.

Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

- For the Year 2040 With ELSP Project Buildout traffic conditions, eleven (11) key study intersections are forecast to operate at unacceptable levels of service during the AM, PM, and/or Saturday Midday peak hours when compared to the LOS standards defined in this report. The remaining key study intersections are forecast to operate at acceptable levels of service during the AM, PM, and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|---|----------------------------|-------------------|----------------------------|-------------------|---|-------------------|
| | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | 162.0 | F | 271.8 | F | 383.1 | F |
| 3. Diamond Drive at I-15 Southbound Ramps | -- | -- | -- | -- | 87.2 | F |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | 124.8 | F | 209.0 | F | 213.5 | F |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | 237.7 | F | 308.6 | F | 440.0 | F |
| 7. Diamond Drive at Campbell Street | -- | -- | -- | -- | 3,158.4 | F |
| 8. Mission Trail at Campbell Street | -- | -- | 101.2 | F | 183.2 | F |
| 9. Diamond Drive at Malaga Road | -- | -- | -- | -- | 194.2 | F |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | 70.7 | E | -- | -- | 72.9 | E |
| 21. Mission Trail at Palomar Street | 76.6 | E | 108.1 | F | -- | -- |
| 22. Stoneman Street at Grand Avenue | 56.7 | E | -- | -- | -- | -- |
| 24. Grape Street at I-15 Northbound Ramps | 70.6 | E | 73.5 | E | 341.8 | F |

Eleven (11) key study intersections will have a significant impact under the Year 2040 With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report. However, the implementation of recommended improvements outlined in this report will offset the impact of the ELSP Project Buildout traffic and bring the significantly impacted intersections to below Adopted Specific Plan and/or acceptable conditions at ten (10) of the eleven (11) impacted locations. It should be noted that mitigation for key study intersection #4, Diamond Drive at Casino Drive/Auto Center Drive, is infeasible due to the surrounding parcels preventing the additional needed right-of-way.

- For the Year 2040 With ELSP Project Buildout traffic conditions, three (3) key study roadway segments are forecast to operate at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway segments are forecast to operate at acceptable levels of service on a daily basis. The roadway segments operating at adverse levels of service are:

| <u>Key Roadway Segment</u> | <u>Weekday Daily</u> | | | <u>Saturday Daily</u> | | |
|--|----------------------|------------------|------------|-----------------------|------------------|------------|
| | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | 44,090 | 1.293 | F | 52,289 | 1.533 | F |
| 22. Mission Trail, <i>between Bundy Canyon Road and Palomar Street</i> | 15,466 | 1.190 | F | 13,554 | 1.043 | F |
| 23. Palomar Street, <i>between Corydon Road and Mission Trail</i> | 13,572 | 1.044 | F | 11,788 | 0.907 | E |

To determine if the ELSP Project Buildout creates a significant impact, these adverse roadway segments are further analyzed under peak hour conditions to determine if there are any peak hour deficiencies. These study roadway segments are forecast to operate at LOS C or better during the AM, PM, and Saturday Midday peak hours. As a result, the key study roadway segments are not significantly impacted by Year 2040 With ELSP Project Buildout traffic and therefore no improvements are required.

Internal Network Planned Improvements

Project Phase I Planned Improvements

- The planned improvements for the internal network intersections listed below are anticipated to be completed in conjunction with the Project Phase I development and have been assumed in the Year 2022 Without ELSP Project Phase I and Year 2022 With ELSP Project Phase I traffic conditions:
 - Intersection 25. Diamond Drive at Olive Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no west leg. The northbound movement will consist of a through lane and a shared through-right-turn lane. The southbound movement will consist of a shared through-left-turn lane and through lane. The westbound movement will consist of a shared left-right-turn lane.

- Intersection 26. “A” Street at Olive Street: This intersection is proposed to be a roundabout three-legged intersection with no north leg. The roundabout will consist of one lane and each leg will have one entry lane and one exit lane. “A” Street and Olive Street are both proposed to be two lane collector roads.
 - Intersection 27. “A” Street at Victorian Lane: This intersection is proposed to be a roundabout three-legged intersection with no west leg. The roundabout will consist of one lane and each leg will have one entry lane and one exit lane. “A” Street and Victorian Lane are both proposed to be two lane collector roads.
 - Intersection 28. “A” Street at Cereal Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no south leg. The southbound movement will consist of a shared left-right-turn lane. The eastbound movement will consist of a shared through-left-turn lane and through lane. The westbound movement will consist of a through lane and a shared through-right-turn lane.
- The planned improvements for the internal network roadway segments listed below are anticipated to be completed in conjunction with the Project Phase I development and have been assumed in the Year 2022 Without ELSP Project Phase I and Year 2022 With ELSP Project Phase I traffic conditions:
- Roadway Segment 27. Sylvester Street, between Lucerne Street and Diamond Drive: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
 - Roadway Segment 28. Lucerne Street, between Sylvester Street and Cereal Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
 - Roadway Segment 29. Cereal Street, between Lucerne Street and Stoneman Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
 - Roadway Segment 30. Cereal Street between Stoneman Street and Diamond Drive: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
 - Roadway Segment 31. Diamond Drive, between Olive Street and Cereal Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.

Project Buildout Planned Improvements

- The planned improvements listed below for the internal network intersections are anticipated to be completed in conjunction with the Project Buildout development and have been assumed in the Existing With ELSP Project Buildout, Year 2040 With Adopted Specific Plan, and Year 2040 With ELSP Project Buildout traffic conditions:
- Intersection 25. Diamond Drive at Olive Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no west leg. The northbound movement will consist of a through lane and a shared through-right-turn lane. The southbound movement will consist of a shared through-left-turn lane and through lane. The westbound movement will consist of a shared left-right-turn lane.

- Intersection 26. “A” Street at Olive Street: This intersection is proposed to be a roundabout three-legged intersection with no north leg. The roundabout will consist of one lane and each leg will have one entry lane and one exit lane. “A” Street and Olive Street are both proposed to be two lane collector roads.
 - Intersection 27. “A” Street at Victorian Lane: This intersection is proposed to be a roundabout three-legged intersection with no west leg. The roundabout will consist of one lane and each leg will have one entry lane and one exit lane. “A” Street and Victorian Lane are both proposed to be two lane collector roads.
 - Intersection 28. “A” Street at Cereal Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no south leg. The southbound movement will consist of a shared left-right-turn lane. The eastbound movement will consist of a shared through-left-turn lane and through lane. The westbound movement will consist of a through lane and a shared through-right-turn lane.
 - Intersection 29. Lucerne Street at Sylvester Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no west leg. The northbound movement will consist of a through lane and a shared through-right-turn lane. The southbound movement will consist of a shared through-left-turn lane and through lane. The westbound movement will consist of an exclusive left-turn lane and an exclusive right-turn lane.
 - Intersection 30. Stoneman Street at Cereal Street: This intersection is proposed to be a three phase signalized three-legged intersection with no north leg. The northbound movement will consist of an exclusive left-turn lane and an exclusive right-turn lane. The eastbound movement will consist of a through lane and a shared through-right-turn lane. The westbound movement will consist of an exclusive left-turn lane and two (2) through lanes.
- The planned improvements listed below for the internal network roadway segments are anticipated to be completed in conjunction with the Project Buildout development and have been assumed in the Existing With ELSP Project Buildout, Year 2040 With Adopted Specific Plan, and Year 2040 With ELSP Project Buildout traffic conditions:
- Roadway Segment 27. Sylvester Street, between Lucerne Street and Diamond Drive: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
 - Roadway Segment 28. Lucerne Street, between Sylvester Street and Cereal Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
 - Roadway Segment 29. Cereal Street, between Lucerne Street and Stoneman Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
 - Roadway Segment 30. Cereal Street between Stoneman Street and Diamond Drive: This roadway segment is proposed to be a major arterial with four (4) lanes divided.

- Roadway Segment 31. Diamond Drive, between Olive Street and Cereal Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.

External Network Planned Improvements

Existing With East Lake Specific Plan Project Buildout Planned Improvements

- The planned improvements for the external network intersections listed below are anticipated to be completed in conjunction with the Project Buildout and have been assumed in the Existing With ELSP Project Buildout traffic conditions:
 - Intersection 11. Mission Trail at Olive Street: Add a west leg and provide the eastbound approach with an exclusive eastbound left-turn lane, and a shared through-right-turn lane, and provide a lane for the westbound departure. Restripe the west leg to provide a shared through-right-turn lane. Restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane. Restripe the southbound approach to provide a shared through-right-turn lane. Modify the existing traffic signal to provide a five phase signal.
- There are no Existing With ELSP Project Buildout external network planned improvements for roadway segments.

Year 2022 Planned Improvements

- The planned improvements listed below for the external network intersections are anticipated to be completed in Year 2022 and have been assumed in the Year 2022 Without ELSP Project Phase I and Year 2022 With ELSP Project Phase I traffic conditions:
 - Intersection 1. Railroad Canyon Road at Summerhill Road/Grape Street: Remove a northbound left-turn lane and the east leg crosswalk. Widen and/or restripe the westbound approach of Grape Street to provide an exclusive right-turn lane. Modify the existing traffic signal as necessary. These improvements are in conjunction with the Railroad Canyon Road Interchange Project.
 - Intersection 2. Railroad Canyon Road at I-15 NB Ramps: This intersection will not exist upon completion of the Railroad Canyon Road Interchange Project.
 - Intersection 3. Diamond Drive at I-15 SB Ramps: Widen and/or restripe the southbound approach to provide a second exclusive left-turn lane as well as a third exclusive through lane. Widen and/or restripe the southbound departure to include a third lane. Widen and/or restripe the eastbound departure to include two (2) additional on-ramp lanes. Modify the existing traffic signal as necessary. These improvements are in conjunction with the Railroad Canyon Road Interchange Project.
 - Intersection 5. Lucerne Street at Lakeshore Drive: Widen and/or restripe Lucerne Street to provide an exclusive northbound left-turn lane.

- Intersection 11. Mission Trail at Olive Street: Add a west leg and provide the eastbound approach with an exclusive eastbound left-turn lane, and a shared through-right-turn lane, and provide a lane for the westbound departure. Restripe the west leg to provide a shared through-right-turn lane. Restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane. Restripe the southbound approach to provide a shared through-right-turn lane. Stripe crosswalks on the north and east legs. Modify the existing traffic signal to provide a five phase signal with protective left-turn phasing on Mission Trail.
 - Intersection 12. Mission Trail at Victorian Lane: Widen and/or restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive southbound left-turn lane. Stripe crosswalks on all four legs. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.
 - Intersection 15. Corydon Road at Cereal Street: Add an east leg and provide the westbound approach with an exclusive left-turn lane, a through lane, a shared through-right-turn lane, and provide the eastbound departure with two (2) lanes. Widen and/or restripe the eastbound approach with an exclusive left-turn lane, a through lane, and a shared through-right-turn lane. Widen and/or restripe the westbound departure with a second lane. Restripe the northbound approach of Corydon Road to provide a shared through-right-turn lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane. Stripe crosswalks on all four legs. Install an eight phase traffic signal.
 - Intersection 16. Mission Trail at Bundy Canyon Road: Widen and/or restripe the eastbound approach of Bundy Canyon Road to provide an exclusive left-turn lane, a through lane, and a shared through-right-turn lane. Widen and/or restripe the westbound departure with a second lane. Widen and/or restripe the westbound approach to provide two (2) through lanes. Modify the existing traffic signal to provide an eight phase signal.
 - Intersection 24. Grape Street at I-15 NB Ramps: Add a west leg and provide the eastbound approach with two (2) exclusive left-turn lanes, an exclusive right-turn lane, and provide the westbound departure with three (3) on-ramp lanes. Widen and/or restripe the northbound approach on Grape Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive right-turn lane. Install a three phase traffic signal.
- The planned improvements listed below for the external network roadway segments are anticipated to be completed in Year 2022 and have been assumed in the Year 2022 Without ELSP Project Phase I and Year 2022 With ELSP Project Phase I traffic conditions:
- Roadway Segment 3. Lucerne Street, south of Lakeshore Drive: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided.

- Roadway Segment 18. Cereal Street, west of Corydon Road: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided.
- Roadway Segment 32. Bundy Canyon Road, between Corydon Road and Mission Trail: Extend Bundy Canyon Road from Mission Trail to Corydon Road with four (4) lanes divided.

Year 2040 Planned Improvements

- The planned improvements listed below for the external network intersections are anticipated to be completed in Year 2040 and have been assumed in the Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout traffic conditions:
 - Intersection 1. Railroad Canyon Road at Summerhill Road/Grape Street: Remove a northbound left-turn lane and the east leg crosswalk. Widen and/or restripe the westbound approach of Grape Street to provide an exclusive right-turn lane. Modify the existing traffic signal as necessary. These improvements are in conjunction with the Railroad Canyon Road Interchange Project.
 - Intersection 2. Railroad Canyon Road at I-15 NB Ramps: This intersection will not exist upon completion of the Railroad Canyon Road Interchange Project.
 - Intersection 3. Diamond Drive at I-15 SB Ramps: Widen and/or restripe the southbound approach to provide a second exclusive left-turn lane as well as a third exclusive through lane. Widen and/or restripe the southbound departure to include a third lane. Widen and/or restripe the eastbound departure to include two (2) additional on-ramp lanes. Modify the existing traffic signal as necessary. These improvements are in conjunction with the Railroad Canyon Road Interchange Project.
 - Intersection 5. Lucerne Street at Lakeshore Drive: Widen and/or restripe Lucerne Street to provide an exclusive northbound left-turn lane. Widen and/or restripe the eastbound approach on Lakeshore Drive to provide two (2) exclusive through lanes. Widen and/or restripe the westbound departure to provide two (2) additional lanes. Widen and/or restripe the westbound approach to provide two (2) exclusive through lanes. Widen and/or restripe the eastbound departure to provide two (2) additional lanes. Stripe crosswalks on all legs. Install three phase traffic signal.
 - Intersection 6. Diamond Drive at Lakeshore Drive/Mission Trail: Widen and/or restripe the eastbound approach on Lakeshore Drive to provide one (1) additional through lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach on Mission Trail to provide one (1) additional through lane. Widen and/or restripe eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.
 - Intersection 8. Mission Trail at Campbell Street: Widen and/or restripe the northbound approach on Mission Trail to provide one (1) additional through lane. Widen and/or restripe the southbound departure to provide a third lane. Widen and/or

restripe the southbound approach to provide one (1) additional through lane. Widen and/or restripe the northbound departure to provide a third lane.

- Intersection 10. Mission Trail at Malaga Road: Widen and/or restripe the northbound approach on Mission Trail to provide one (1) additional through lane. Widen and/or restripe the southbound departure to provide a third lane. Widen and/or restripe the southbound approach to provide one (1) additional through lane. Widen and/or restripe the northbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 11. Mission Trail at Olive Street: Add a west leg and provide the eastbound approach with an exclusive eastbound left-turn lane, and a shared through-right-turn lane, and provide a lane for the westbound departure. Restripe the west leg to provide a shared through-right-turn lane. Widen and/or restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane and a second through lane. Widen and/or restripe the southbound departure to provide a third lane. Widen and/or restripe the southbound approach to provide a shared through-right-turn lane and a second through lane. Widen and/or restripe the northbound departure with a third lane. Stripe crosswalks on the north and east legs. Modify the existing traffic signal to provide a five phase signal with protective left-turn phasing on Mission Trail.
- Intersection 12. Mission Trail at Victorian Lane: Widen and/or restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane and a second through lane. Widen and/or restripe the southbound departure to provide a third lane. Widen and/or restripe the southbound approach to provide an exclusive southbound left-turn lane and a second through lane. Widen and/or restripe the northbound departure to provide a third lane. Stripe crosswalks on all four legs. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.
- Intersection 13. Mission Trail at Lemon Street: Widen and/or restripe the northbound approach of Mission Trail to provide a third through lane. Widen and/or restripe the southbound departure to provide a third lane. Widen and/or restripe the southbound approach to provide a third through lane. Widen and/or restripe the northbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 15. Corydon Road at Cereal Street: Add an east leg and provide the westbound approach with an exclusive left-turn lane, a through lane, and a shared through-right-turn lane, and provide the eastbound departure with two (2) lanes. Widen and/or restripe the eastbound approach with an exclusive left-turn lane, a through lane, and a shared through-right-turn lane. Widen and/or restripe the westbound departure with a second lane. Widen and/or restripe the northbound approach of Corydon Road to provide a through lane and a shared through-right-turn lane. Widen and/or restripe the southbound departure with a second lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane and a

through lane. Widen and/or restripe the northbound departure with a second lane. Stripe crosswalks on all four legs. Install an eight phase traffic signal.

- Intersection 16. Mission Trail at Bundy Canyon Road: Widen and/or restripe the eastbound approach of Bundy Canyon Road to provide an exclusive left-turn lane, a through lane, and a shared through-right-turn lane. Widen and/or restripe the westbound departure with a second lane. Widen and/or restripe the westbound approach to provide two (2) through lanes. Modify the existing traffic signal to provide an eight phase signal.
- Intersection 17. Orange Street at Bundy Canyon Road: Widen and/or restripe the northbound approach on Orange Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane and a shared through-right-turn lane. Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a second through lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify existing traffic signal to provide an eight phase signal.
- Intersection 18. I-15 SB Ramps at Bundy Canyon Road: Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a second through lane. Widen and/or restripe the westbound departure to provide a third lane. Please note that the addition of a third westbound departure lane would not result in a trap lane at the intersection of Orange Street at Bundy Canyon Road due to an additional westbound through lane included as a planned improvement at that location. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 19. I-15 NB Ramps at Bundy Canyon Road: Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a third through lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 20. Corydon Road at Palomar Street: Widen and/or restripe the northbound approach on Corydon Road to provide a second through lane. Widen and/or restripe the northbound departure to provide a second lane. Modify the existing traffic signal as necessary.
- Intersection 21. Mission Trail at Palomar Street: Stripe crosswalks on all legs. Install a three phase traffic signal.
- Intersection 22. Stoneman Street at Grand Avenue: Widen and/or restripe the eastbound approach on Grand Avenue to provide a through lane. Widen and/or

restripe the eastbound departure to provide a second lane. Stripe crosswalks on all legs. Install a five phase traffic signal with protective left-turn phasing for Grand Avenue.

- Intersection 23. Corydon Road at Grand Avenue: Widen and/or restripe the eastbound approach on Grand Avenue to provide a through lane. Widen and/or restripe the westbound departure to provide a second lane. Widen and/or restripe the westbound approach to provide a through lane. Widen and/or restripe the eastbound departure to provide a second lane. Modify the existing traffic signal as necessary.
 - Intersection 24. Grape Street at I-15 NB Ramps: Add a west leg and provide the eastbound approach with two (2) exclusive left-turn lanes, an exclusive right-turn lane, and provide the westbound departure with three (3) on-ramp lanes. Widen and/or restripe the northbound approach on Grape Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive right-turn lane. Install a three phase traffic signal.
- The planned improvements listed below for the external network roadway segments are anticipated to be completed in Year 2040 and have been assumed in the Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout traffic conditions:
- Roadway Segment 3. Lucerne Street, south of Lakeshore Drive: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided. Extend south to Sylvester Street.
 - Roadway Segment 7. Mission Trail, between Diamond Drive and Campbell Street: Widen from a major arterial with four (4) lanes divided to an urban arterial with six (6) lanes divided.
 - Roadway Segment 8. Mission Trail, between Campbell Street and Malaga Road: Widen from a major arterial with four (4) lanes divided to an urban arterial with six (6) lanes divided.
 - Roadway Segment 12. Mission Trail, between Malaga Road and Olive Street: Widen from a major arterial with four (4) lanes divided to an urban arterial with six (6) lanes divided.
 - Roadway Segment 13. Olive Street, between Mission Trail and Grape Street: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided.
 - Roadway Segment 14. Mission Trail, between Olive Street and Victorian Lane: Widen from a secondary arterial with four (4) lanes undivided to an urban arterial with six (6) lanes divided.
 - Roadway Segment 15. Mission Trail, between Victorian Lane and Lemon Street: Widen from a secondary arterial with four (4) lanes undivided to an urban arterial with six (6) lanes divided.

- Roadway Segment 17. Corydon Road, between Mission Trail and Cereal Street: Widen from a divided collector with two (2) lanes divided to a major arterial with four (4) lanes divided.
- Roadway Segment 18. Cereal Street, west of Corydon Road: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided.
- Roadway Segment 20. Bundy Canyon Road, between Mission Trail and I-15 SB Ramps: Widen from a collector with two (2) lanes undivided to an urban arterial with six (6) lanes divided.
- Roadway Segment 21. Corydon Road, between Cereal Street and Palomar Street: Widen from a divided collector with two (2) lanes divided to a major arterial with four (4) lanes divided.
- Roadway Segment 24. Stoneman Street, north of Grand Avenue: Extend north to Cereal Street.
- Roadway Segment 26. Corydon Road, between Palomar Street and Grand Avenue: Widen from a divided collector with two (2) lanes divided to a major arterial with four (4) lanes divided.
- Roadway Segment 32. Bundy Canyon Road, between Corydon Road and Mission Trail: Extend Bundy Canyon Road from Mission Trail to Corydon Road with four (4) lanes divided.

Recommended Improvements

Existing With East Lake Specific Plan Project Buildout Traffic Conditions

- The results of the Existing With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed Project Buildout will significantly impact six (6) key study intersections. The remaining key study intersections are forecast to operate at acceptable levels of service under the Existing With ELSP Project Buildout traffic conditions. The improvements listed below have been identified to address the traffic impacts at the intersections significantly impacted by the Existing With ELSP Project Buildout traffic:
 - Intersection 5. Lucerne Street at Lakeshore Drive: Widen and/or restripe Lucerne Street to provide an exclusive northbound left-turn lane. Stripe crosswalks on all legs. Install three phase traffic signal.
 - Intersection 6. Diamond Drive at Lakeshore Drive/Mission Trail: Modify the existing traffic signal to provide overlap phasing for the westbound right-turn movement. No additional physical improvements are feasible to achieve an acceptable level of service LOS D or better. Hence the Project's impact at this key intersection is considered unavoidable.

- Intersection 12. Mission Trail at Victorian Lane: Widen and/or restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive southbound left-turn lane. Stripe crosswalks on all four legs. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.
 - Intersection 17. Orange Street at Bundy Canyon Road: Widen and/or restripe the northbound approach on Orange Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane and a shared through-right-turn lane. Modify existing traffic signal to provide an eight phase signal.
 - Intersection 18. I-15 SB Ramps at Bundy Canyon Road: Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a second through lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.
 - Intersection 22. Stoneman Street at Grand Avenue: Stripe crosswalks on all legs. Install a five phase traffic signal with protective left-turn phasing for Grand Avenue.
- The results of the roadway segment analyses for Existing With ELSP Project Buildout traffic conditions indicate that the proposed Project is not forecast to have a significant impact at any of the thirty-one (31) key roadway segments (roadway segment 32 does not exist in Existing With ELSP Project Buildout traffic conditions). As there are no significant impacts, no traffic mitigation measures are required under this traffic scenario.

Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

- The results of the Year 2022 With ELSP Project Phase I traffic conditions level of service analyses indicate that the proposed Project Phase I will significantly impact eleven (11) key study intersections. The remaining key study intersections are forecast to operate at acceptable levels of service under the Year 2022 With ELSP Project Phase I traffic conditions. The improvements listed below have been identified to address the traffic impacts at the intersections significantly impacted by the Year 2022 With ELSP Project Phase I traffic:
- Intersection 1. Railroad Canyon Road at Summerhill Road/Grape Street: Widen and/or restripe the eastbound approach of Summerhill Road to provide a second through lane and convert the shared through-right lane into an exclusive through lane. Widen and/or restripe the southbound approach to provide a second left-turn lane. Widen and/or restripe the northbound departure to provide a third lane. Widen and/or restripe the northbound movement to provide a third through lane and to convert the northbound right-turn lane into a free right-turn movement. Modify the existing

traffic signal to be an eight phase signal and to provide overlap phasing for the westbound right-turn movement.

- Intersection 4. Diamond Drive at Auto Center Drive/Casino Drive: Widen the southbound approach of Diamond Drive to provide a second through lane. However, this mitigation is infeasible due to the surrounding parcels preventing the additional needed right-of-way. Hence the Project's impact at this key intersection is considered unavoidable.
- Intersection 6. Diamond Drive at Lakeshore Drive/Mission Trail: Modify the existing traffic signal to provide overlap phasing for the westbound right-turn movement. No additional physical improvements are feasible to achieve an acceptable level of service LOS D or better. Hence the Project's impact at this key intersection is considered unavoidable.
- Intersection 7. Diamond Drive at Campbell Street: Restrict southbound left-turn movement and westbound left-turn movement. Please note that the recommended improvement is for Saturday Midday peak hour only.
- Intersection 8. Mission Trail at Campbell Street: Stripe crosswalks on the east and west leg. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.
- Intersection 9. Diamond Drive at Malaga Road: Restripe the southbound approach on Diamond Drive to provide a second exclusive left-turn lane. Widen and/or restripe the eastbound approach to provide a second exclusive left-turn lane. Modify the existing traffic signal as necessary.
- Intersection 15. Corydon Road at Cereal Street: Widen and/or restripe the northbound approach on Corydon Road to provide a through lane. Widen and/or restripe the northbound departure to provide a second lane. Modify the existing traffic signal as necessary.
- Intersection 17. Orange Street at Bundy Canyon Road: Widen and/or restripe the northbound approach on Orange Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane and a shared through-right-turn lane. Modify existing traffic signal to provide an eight phase signal.
- Intersection 18. I-15 SB Ramps at Bundy Canyon Road: Widen and/or restripe the southbound approach to provide an exclusive right-turn lane. Widen and/or restripe the southbound departure to provide a second on-ramp lane. Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a second through lane and an exclusive right-turn lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.

- Intersection 22. Stoneman Street at Grand Avenue: Stripe crosswalks on all legs. Install a five phase traffic signal with protective left-turn phasing for Grand Avenue.
- Intersection 24. Grape Street at I-15 NB Ramps: Widen and/or restripe the southbound approach on Grape Street to convert the southbound right-turn lane into a free right-turn movement. Modify the existing traffic signal as necessary.
- The results of the roadway segment analyses for Year 2022 With ELSP Project Phase I traffic conditions indicate that the proposed Project is not forecast to have a significant impact at any of the thirty-two (32) key roadway segments. As there are no significant impacts, no traffic mitigation measures are required under this traffic scenario.

Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

- The results of the Year 2040 With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed Project Buildout will significantly impact eleven (11) key study intersections. The remaining key study intersections are forecast to operate at acceptable levels of service under the Year 2040 With ELSP Project Buildout traffic conditions. The improvements listed below have been identified to address the traffic impacts at the intersections significantly impacted by the Year 2040 With ELSP Project Buildout traffic:
 - Intersection 1. Railroad Canyon Road at Summerhill Road/Grape Street: Widen and/or restripe the eastbound approach of Summerhill Road to provide a second through lane and convert the shared through-right lane into an exclusive through lane. Widen and/or restripe the southbound approach to provide a second left-turn lane. Widen and/or restripe the northbound departure to provide a third lane. Widen and/or restripe the northbound movement to provide a third through lane and to convert the northbound right-turn lane into a free right-turn movement. Modify the existing traffic signal to be an eight phase signal and to provide overlap phasing for the westbound right-turn movement.
 - Intersection 3. Railroad Canyon Road at I-15 SB Ramps: Widen and/or restripe the northbound approach on Railroad Canyon Road to provide an exclusive right-turn lane. Widen and/or restripe the eastbound approach on the off-ramp to provide a second exclusive right-turn lane. Modify the existing traffic signal as necessary.
 - Intersection 4. Diamond Drive at Auto Center Drive/Casino Drive: Widen the northbound approach of Diamond Drive to provide a second exclusive left-turn lane. Widen the southbound approach to provide an exclusive right-turn lane and third through lane. Widen the eastbound approach to provide a second exclusive left-turn lane and right-turn lane. Install a pedestrian refuge on the south leg. Modify the existing traffic signal to provide eight phasing with overlap phases for the southbound and eastbound right-turn. However, this mitigation is infeasible due to the surrounding parcels preventing the additional needed right-of-way. Hence the Project's impact at this key intersection is considered unavoidable.

- Intersection 6. Diamond Drive at Lakeshore Drive/Mission Trail: Modify the existing traffic signal to provide overlap phasing for the westbound right-turn movement. No additional physical improvements are feasible to achieve an acceptable level of service LOS D or better. Hence the Project's impact at this key intersection is considered unavoidable.
 - Intersection 7. Diamond Drive at Campbell Street: Restrict southbound left-turn movement and westbound left-turn movement. Please note that the recommended improvement is for Saturday Midday peak hour only.
 - Intersection 8. Mission Trail at Campbell Street: Stripe crosswalks on the east and west leg. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.
 - Intersection 9. Diamond Drive at Malaga Road: Restripe the southbound approach on Diamond Drive to provide a second exclusive left-turn lane. Widen and/or restripe the eastbound approach to provide a second exclusive left-turn lane. Modify the existing traffic signal as necessary. Please note that the second eastbound left-turn lane is only needed in the Year 2022 With ELSP Project Phase I traffic conditions.
 - Intersection 18. I-15 SB Ramps at Bundy Canyon Road: Widen and/or restripe the southbound approach to provide an exclusive right-turn lane. Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide an exclusive right-turn lane. Widen and/or restripe the southbound departure to provide a second on-ramp lane. Modify the existing traffic signal as necessary.
 - Intersection 21. Mission Trail at Palomar Street: Widen and/or restripe the northbound approach on Mission Trail to provide a second exclusive left-turn lane. Widen and/or restripe the westbound departure to provide a second lane. Modify the traffic signal to provide overlap phasing for the eastbound right-turn movement.
 - Intersection 22. Stoneman Street at Grand Avenue: Widen and/or restripe the northbound approach on Stoneman Street to provide an exclusive left-turn lane. Modify the existing traffic signal as necessary.
 - Intersection 24. Grape Street at I-15 NB Ramps: Widen and/or restripe the southbound approach on Grape Street to convert the southbound right-turn lane into a free right-turn movement. Modify the existing traffic signal as necessary.
- The results of the roadway segment analyses for Year 2040 With ELSP Project Buildout traffic conditions indicate that the proposed Project is not forecast to have a significant impact at any of the thirty-two (32) key roadway segments. As there are no significant impacts, no traffic mitigation measures are required under this traffic scenario.

Traffic Signal Warrant Analysis

Existing With East Lake Specific Plan Project Buildout Traffic Conditions

- The results of the peak-hour traffic signal warrant analysis for the Existing With ELSP Project Buildout traffic conditions indicate that the following key unsignalized impacted intersection has future traffic conditions that would exceed the volume thresholds of Warrant #3, Part A and Part B for the Weekday AM, Weekday PM and Saturday Midday peak hours:
 - 5. Lucerne Street at Lakeshore Drive

The analysis and the recommended improvements show that the above-mentioned intersection in the Existing With ELSP Project Buildout traffic conditions is recommended to be signalized. With signalization of this intersection, which is warranted, this intersection is forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and Saturday Midday peak hours.

The analysis and the recommended improvements show that intersections #12, Mission Trail at Victorian Lane, and #22, Stoneman Street at Grand Avenue, are recommended to be signalized. With signalization of these intersections, which is not warranted under any peak hours, these intersections are forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and Saturday Midday peak hours. Although these intersections do not meet signal warrants, it is recommended these locations be signalized due to right-of-way restrictions and safety concerns.

Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

- The results of the peak-hour traffic signal warrant analysis for the Year 2022 With ELSP Project Phase I traffic conditions indicate that the following key unsignalized impacted intersection has future traffic conditions that would exceed the volume thresholds of Warrant #3, Part A and Part B for the Weekday AM and Weekday PM peak hours:
 - 22. Stoneman Street at Grand Avenue

The analysis and the recommended improvements show that the above-mentioned intersection in the Year 2022 With ELSP Project Phase I traffic conditions is recommended to be signalized. With signalization of this intersection, which is warranted under the Weekday AM and PM peak hours, this intersection is forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and Saturday Midday peak hours.

The analysis and the recommended improvements show that intersection #8, Mission Trail at Campbell Street, is recommended to be signalized. With signalization of this intersection, which is not warranted under any peak hours, these intersections are forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and Saturday Midday peak hours. Although this intersection does not meet signal warrants, it is recommended this location be signalized due to safety concerns.

Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

- The results of the peak-hour traffic signal warrant analysis for the Year 2040 With ELSP Project Buildout traffic conditions indicate that the following key unsignalized impacted intersection has future traffic conditions that will not exceed the volume thresholds of Warrant #3, Part A and Part B for the Weekday AM, Weekday PM, or Saturday Midday peak hours:
- 8. Mission Trail at Campbell Street

The analysis and the recommended improvements show that the above-mentioned intersection in the Year 2040 With ELSP Project Buildout traffic conditions is recommended to be signalized. With signalization of this intersection, which is not warranted under any peak hours, this intersection is forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and Saturday Midday peak hours. Although this intersection does not meet signal warrants, the signalization of this intersection is consistent with the analysis performed in the currently Adopted Specific Plan and it is reasonable to assume that by Year 2040, along with the adjoining planned roadway widening along Mission Trail from 4 lanes to 6 lanes, a traffic signal will be installed at this location.

Project Fair Share Analysis

Year 2022 With East Lake Specific Project Phase I Traffic Conditions

- The ELSP Project Phase I fair share percentages (worse time period impacted) for the eleven (11) impacted intersections for the Year 2022 With ELSP Project Phase I traffic conditions are shown below:
- 1. Railroad Canyon Road at Summerhill Lane/Grape Street 100.00%¹
 - 4. Diamond Drive at Casino Drive/Auto Center Drive 32.01%²
 - 6. Diamond Drive at Lakeshore Drive/Mission Trail 100.00%¹
 - 7. Diamond Drive at Campbell Street 27.41%
 - 8. Mission Trail at Campbell Street 40.42%
 - 9. Diamond Drive at Malaga Road 46.02%
 - 15. Croydon Road at Cereal Street 61.60%
 - 17. Orange Street at Bundy Canyon Road 48.01%
 - 18. I-15 SB Ramps at Bundy Canyon Road 42.16%

¹ The mitigation at this intersection only mitigates up to pre-Project level. As such, the Project would be responsible for 100% of costs.

² The mitigation at this intersection is considered infeasible and is included for informational purposes only.

- 22. Stoneman Street at Grand Avenue 18.62%
 - 24. Grape Street at I-15 Northbound Ramps 5.54%
- The results of the roadway segment analyses indicate that the proposed ELSP Project Phase I is not forecast to have a significant impact at any of the thirty-two (32) key roadway segments for the Year 2022 With ELSP Project Phase I traffic conditions. As there are no significant impacts, no Project fair share calculation is needed.
- Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions*
- The ELSP Project Buildout fair share percentages (worse time period impacted) for the eleven (11) impacted intersections for the Year 2040 With ELSP Project Buildout traffic conditions are shown below:
- | | |
|---|----------------------|
| ▪ 1. Railroad Canyon Road at Summerhill Lane/Grape Street | 100.00% ³ |
| ▪ 3. Diamond Drive at I-15 Northbound Ramps | 18.10% |
| ▪ 4. Diamond Drive at Casino Drive/Auto Center Drive | 21.54% ⁴ |
| ▪ 6. Diamond Drive at Lakeshore Drive/Mission Trail | 100.00% ³ |
| ▪ 7. Diamond Drive at Campbell Street | 4.79% |
| ▪ 8. Mission Trail at Campbell Street | 34.65% |
| ▪ 9. Diamond Drive at Malaga Road | 13.99% |
| ▪ 18. I-15 SB Ramps at Bundy Canyon Road | 17.87% |
| ▪ 21. Mission Trail at Palomar Street | 12.72% |
| ▪ 22. Stoneman Street at Grand Avenue | 6.41% |
| ▪ 24. Grape Street at I-15 Northbound Ramps | 10.00% |
- The results of the roadway segment analyses indicate that the proposed ELSP Project Buildout is not forecast to have a significant impact at any of the thirty-two (32) key roadway segments for the Year 2040 With ELSP Project Buildout traffic conditions. As there are no significant impacts, no Project fair share calculation is needed.

Caltrans Facilities Analysis

Existing Traffic Conditions

- All six (6) basic freeway segments currently operate at acceptable LOS D or better during the AM and PM peak hours under the Existing traffic conditions based on the LOS standards defined in this report.

³ The mitigation at this intersection only mitigates up to pre-Project level. As such, the Project would be responsible for 100% of costs.

⁴ The mitigation at this intersection is considered infeasible and is included for informational purposes only.

- All four (4) freeway merge and diverge segments currently operate at acceptable levels of service LOS D or better under the Existing traffic conditions based on the LOS standards defined in this report.

Existing With East Lake Specific Plan Project Buildout Traffic Conditions

- All six (6) basic freeway segments are forecast to operate at acceptable levels of service during the AM and PM peak hours under the Existing With ELSP Project Buildout traffic conditions based on the LOS standards defined in this report. None of the six (6) basic freeway segments will have a significant impact under the Existing With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report.
- All four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service LOS D or better under the Existing With ELSP Project Buildout traffic conditions based on the LOS standards defined in this report. None of the four (4) freeway merge and diverge segments will have a significant impact under the Existing With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report.

Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

- One (1) basic freeway segment is forecast to operate at an adverse level of service under the Year 2022 With ELSP Project Phase I traffic conditions based on the LOS standards defined in this report. The remaining five (5) basic freeway segments are forecast to operate at an acceptable LOS D or better during the AM and PM peak hours under the Year 2022 With ELSP Project Phase I traffic conditions. The location operating at an adverse level of service is listed below:

| <u>Key Basic Freeway Segment</u> | <u>AM Peak Hour</u> | | | <u>PM Peak Hour</u> | | |
|--|---------------------|----------------|---------------|---------------------|----------------|------------|
| | <u>Pk Hr</u> | <u>Density</u> | <u>LOS</u> | <u>Pk Hr</u> | <u>Density</u> | <u>LOS</u> |
| <u>Volume</u> | <u>(pc/mi/ln)</u> | | <u>Volume</u> | <u>(pc/mi/ln)</u> | | |
| 6. I-15 Southbound from Bundy Canyon Road to Baxter Road | 6,120 | 38.3 | E | -- | -- | -- |

One (1) of the six (6) basic freeway segments will have a significant impact under the Year 2022 With ELSP Project Phase I traffic conditions when compared to the LOS criteria defined in this report. However, the implementation of recommended mitigation measures at the impacted basic freeway segments, mitigates the impacts of the proposed ELSP Project Phase I. After implementation of the recommended mitigation measures, the impacted basic freeway segment is forecast to operate at an acceptable LOS based on the LOS standards outlined in this report.

- All four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service LOS D or better under the Year 2022 With ELSP Project Phase I traffic conditions based on the LOS standards defined in this report. None of the four (4) freeway merge and diverge segments will have a significant impact under the Year 2022 With ELSP Project Phase I traffic conditions when compared to the LOS criteria defined in this report.

Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

- Four (4) basic freeway segments are forecast to operate at adverse levels of service under the Year 2040 With ELSP Project Buildout traffic conditions based on the LOS standards defined in this report. The remaining two (2) basic freeway segments are forecast to operate at an acceptable LOS D or better during the AM and PM peak hours under the Year 2040 With ELSP Project Buildout traffic conditions. The locations operating at adverse levels of service are listed below:

| <u>Key Basic Freeway Segment</u> | <u>AM Peak Hour</u> | | | <u>PM Peak Hour</u> | | |
|---|---------------------|---------------------------|------------|---------------------|---------------------------|------------|
| | <u>Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> | <u>Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> |
| 1. I-15 Northbound <i>from</i> Baxter Road <i>to</i> Bundy Canyon Road | -- | -- | -- | 7,232 | 55.9 | F |
| 2. I-15 Northbound <i>from</i> Bundy Canyon Rd <i>to</i> Railroad Canyon Rd | -- | -- | -- | 6,594 | 44.5 | E |
| 5. I-15 Southbound <i>from</i> Railroad Canyon Rd <i>to</i> Bundy Canyon Rd | 6,746 | 46.8 | F | -- | -- | -- |
| 6. I-15 Southbound <i>from</i> Bundy Canyon Road <i>to</i> Baxter Road | 7,528 | 63.2 | F | -- | -- | -- |

Four (4) of the six (6) basic freeway segments will have a significant impact under the Year 2040 With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report. However, the implementation of recommended mitigation measures at the impacted basic freeway segments, mitigates the impacts of the proposed ELSP Project Buildout. After implementation of the recommended mitigation measures, the impacted basic freeway segments are forecast to operate at an acceptable LOS based on the LOS standards outlined in this report.

- One (1) freeway merge segment is forecast to operate at an adverse level of service under the Year 2040 With ELSP Project Buildout traffic conditions based on the LOS standards defined in this report. The remaining three (3) freeway merge and diverge segments are forecast to operate at an acceptable LOS C or better during the AM and PM peak hours under the Year 2040 With ELSP Project Buildout traffic conditions. The location operating at an adverse level of service is listed below:

| <u>Key Basic Freeway Segment</u> | <u>AM Peak Hour</u> | | | | <u>PM Peak Hour</u> | | | |
|---|-----------------------------|--------------------------|---------------------------|------------|-----------------------------|--------------------------|---------------------------|------------|
| | <u>Freeway Pk Hr Volume</u> | <u>Ramp Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> | <u>Freeway Pk Hr Volume</u> | <u>Ramp Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> |
| | | | | | | | | |
| 1. I-15 Southbound On-Ramp <i>from</i> Railroad Canyon Road | 5,512 | 1,234 | 34.0 | F | -- | -- | -- | -- |

One (1) of the four (4) freeway merge and diverge segments will have a significant impact under the Year 2040 With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report. However, the implementation of recommended mitigation

measures at the impacted freeway merge segment, mitigates the impacts of the proposed East Lake Specific Plan (Buildout). After implementation of the recommended mitigation measures, the impacted freeway merge segment is forecast to operate at an acceptable LOS based on the LOS standards outlined in this report.

Railroad Canyon Road Interchange Project Planned Improvements (Caltrans Facilities)

Year 2022 Without ELSP Project Phase I, Year 2022 With ELSP Project Phase I, Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout Traffic Conditions

- The planned improvements listed below for the basic freeway segments are anticipated to be completed in conjunction with the I-15 and Railroad Canyon Road Interchange Project and have been assumed in the Year 2022 Without ELSP Project Phase I, Year 2022 With ELSP Project Phase I, Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout traffic conditions:
 - 3. I-15 Northbound from Railroad Canyon Road to Franklin Street: Add one (1) auxiliary lane connecting the Railroad Canyon Road On-Ramp to the Franklin Street Off-Ramp.
 - 4. I-15 Southbound from Franklin Street to Railroad Canyon Road: Add one (1) auxiliary lane connecting the Franklin Street On-Ramp to the Railroad Canyon Road Off-Ramp.
- The planned improvements listed below for the freeway merge and diverge segments are anticipated to be completed in conjunction with the I-15 and Railroad Canyon Road Interchange Project and have been assumed in the Year 2022 Without ELSP Project Phase I, Year 2022 With ELSP Project Phase I, Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout traffic conditions:
 - 1. I-15 Northbound Off-Ramp to Grape Street: Replace the existing off-ramp onto Railroad Canyon Road with a one-lane hook ramp onto Grape Street. Extend the deceleration lane to approximately 1,530 feet.
 - 2. I-15 Northbound On-Ramp from Grape Street: Replace the existing on-ramp from Railroad Canyon Road with a one-lane hook ramp from Grape Street. The acceleration lane will tie in with the future auxiliary lane connecting to the Franklin Street off-ramp, approximately 2,400 feet downstream.
 - 3. I-15 Southbound Off-Ramp to Railroad Canyon Road: Add a second off-ramp lane with an approximately 170 foot long deceleration lane. Configure the existing off-ramp lane to the proposed auxiliary lane connecting to the Franklin Street on-ramp approximately 1,950 feet upstream.
 - 4. I-15 Southbound On-Ramp from Railroad Canyon Road: Extend the acceleration lane to approximately 1,500 feet.

Recommended Improvements (Caltrans Facilities)

Existing With East Lake Specific Plan Project Buildout Traffic Conditions

- The results of the Existing With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed ELSP Project Buildout will not have a significant impact at any of the six (6) basic freeway segments. All six (6) basic freeway segments are forecast to operate at acceptable levels of service under the Existing With ELSP Project Buildout traffic conditions.
- The results of the Existing With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed ELSP Project Buildout will not have a significant impact at any of the four (4) freeway merge and diverge segments. All four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service under the Existing With ELSP Project Buildout traffic conditions.

Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

- The results of the Year 2022 With ELSP Project Phase I traffic conditions level of service analyses indicate that the proposed ELSP Project Phase I will significantly impact one (1) of the six (6) basic freeway segments. The remaining five (5) basic freeway segments are forecast to operate at acceptable levels of service under the Year 2022 With ELSP Project Phase I traffic conditions. It should be noted that the planned improvements from the Railroad Canyon Road Interchange Project have been included in the background traffic conditions for Year 2022. The improvements listed below have been identified to address the traffic impacts at the basic freeway segments significantly impacted by the Year 2022 With ELSP Project Phase I traffic:
 - 6. I-15 Southbound from Bundy Canyon Road to Baxter Road: Add one (1) general purpose lane in the southbound direction.
- The results of the Year 2022 With ELSP Project Phase I traffic conditions level of service analyses indicate that the proposed ELSP Project Phase I will not have a significant impact at any of the four (4) freeway merge and diverge segments. All four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service under the Year 2022 With ELSP Project Phase I traffic conditions. It should be noted that the planned improvements from the Railroad Canyon Road Interchange Project have been included in the background traffic conditions for Year 2022.

Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

- The results of the Year 2040 With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed ELSP Project Buildout will significantly impact four (4) of the six (6) basic freeway segments. The remaining two (2) basic freeway segments are forecast to operate at acceptable levels of service under the Year 2040 With ELSP Project Buildout traffic conditions. It should be noted that the planned improvements from the

Railroad Canyon Road Interchange Project have been included in the background traffic conditions for Year 2040. The improvements listed below have been identified to address the traffic impacts at the basic freeway segments significantly impacted by the Year 2040 With ELSP Project Buildout traffic:

- 1. I-15 Northbound *from* Baxter Road *to* Bundy Canyon Road: Add one (1) general purpose lane in the northbound direction.
 - 2. I-15 Northbound *from* Bundy Canyon Road *to* Railroad Canyon Road: Add one (1) general purpose lane in the northbound direction.
 - 5. I-15 Southbound *from* Railroad Canyon Road *to* Bundy Canyon Road: Add one (1) general purpose lane in the southbound direction.
 - 6. I-15 Southbound *from* Bundy Canyon Road *to* Baxter Road: Add one (1) general purpose lane in the southbound direction.
- The results of the Year 2040 With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed ELSP Project Buildout will significantly impact one (1) of the of four (4) freeway merge and diverge segments. The remaining three (3) freeway merge and diverge segments are forecast to operate at acceptable levels of service under the Year 2040 With ELSP Project Buildout traffic conditions. It should be noted that the planned improvements from the Railroad Canyon Road Interchange Project have been included in the background traffic conditions for Year 2040. The improvements listed below have been identified to address the traffic impacts at the freeway merge segment significantly impacted by the Year 2040 With ELSP Project Buildout traffic:
- 4. I-15 Southbound On-Ramp *from* Railroad Canyon Road: The addition of the fourth southbound general purpose lane previously mentioned to mitigate basic freeway segment No. 5 (I-15 Southbound *from* Railroad Canyon Road *to* Bundy Canyon Road) under Year 2040 With ELSP Project Buildout traffic conditions will sufficiently offset the adverse level of service for this merge segment. No additional mitigation is needed.

REVISED TRAFFIC IMPACT ANALYSIS REPORT
EAST LAKE SPECIFIC PLAN AMENDMENT NO. 11

Lake Elsinore, California

March 22, 2017
(Revision of the February 1, 2017 Report)

1.0 INTRODUCTION

This Traffic Impact Analysis report addresses the potential traffic impacts and circulation needs associated with the proposed East Lake Specific Plan Amendment No. 11 (hereinafter referred to as Project). This Specific Plan Amendment is anticipated to replace the currently Adopted Specific Plan. The East Lake Specific Plan was originally prepared in 1993 and has since been subject to ten amendments as the land use designations within continued to evolve, the most recent of which has been adopted by the City of Lake Elsinore as previously mentioned. The City of Lake Elsinore is striving to promote “Dream Extreme” character to the Project by supporting uses including unique sporting and recreational venues as well as commercial, restaurant, hotel, open space, and residential uses. More specifically, the “Dream Extreme” character of the Project, as described by the City of Lake Elsinore, will consist of active sports-related facilities such as skydiving, hang-gliding, motor cross, and a golf course. East Lake Specific Plan consists of eight planning areas (PA-1, 2, 3, 4, 5, 6, 7, and 8) over nearly 3,000 acres. The Project is anticipated to be completed in two phases. Phase 1 is expected to be complete by the Year 2022 and buildout of the Specific Plan is expected to be complete by the Year 2040.

This report documents the findings and recommendations of a traffic impact analysis conducted by Linscott, Law & Greenspan, Engineers (LLG) to determine the potential traffic impacts that the Project may have on the local and/or regional transportation network in the vicinity of the Project site. The traffic impact analysis evaluates the operating conditions at twenty-three (23) existing and seven (7) future key study intersections, as well as twenty-six (26) existing and six (6) future key roadway segments within the Project vicinity, models the trip generation potential of the Project and forecasts existing and future (near-term Year 2022 and long-term Year 2040) operating conditions without and with the Project.

The Project site has been visited and an inventory of adjacent area roadways and intersections was performed. Existing (i.e. baseline) peak hours and daily traffic information has been collected at key existing study intersections and key existing roadway segments, respectively, on a “typical” weekday for use in the preparation of intersection and roadway segment level of service calculations. This traffic report analyzes existing (i.e. baseline) and future (near-term and long-term) weekday Daily, AM and PM peak hour traffic conditions as well as Saturday Daily and Midday peak hour traffic conditions for Existing (i.e. baseline), Year 2022, and Year 2040 traffic conditions without and with the proposed Project. Weekday AM/PM and Saturday Midday peak hour and Weekday/Saturday daily traffic forecasts for the Buildout (Year 2040) traffic conditions have been

projected based on the City of Lake Elsinore Transportation and Analysis Model, administered by LSA Associates, Inc. (LSA).

The work program for this traffic study was developed in conjunction with the City of Lake Elsinore Planning Department staff. **Appendix A** contains a copy of the approved City of Lake Elsinore Traffic Impact Study Scoping Agreement.

1.1 Study Area

1.1.1 *Intersections*

Twenty-three (23) existing key study intersections and seven (7) future internal intersections were designated for evaluation based on discussions with City staff. The key intersections selected for evaluation in this report provide local and regional access to the study area and are listed as follows, along with their respective jurisdictions:

1. Railroad Canyon Road at Summerhill Lane/Grape Street (Lake Elsinore)
2. Railroad Canyon Road at I-15 NB Ramps (Lake Elsinore)
3. Diamond Drive at I-15 SB Ramps (Lake Elsinore)
4. Diamond Drive at Casino Drive/Auto Center Drive (Lake Elsinore)
5. Lucerne Street at Lakeshore Drive (Lake Elsinore)
6. Diamond Drive at Lakeshore Drive/Mission Trail (Lake Elsinore)
7. Diamond Drive at Campbell Street (Lake Elsinore)
8. Mission Trail at Campbell Street (Lake Elsinore)
9. Diamond Drive at Malaga Road (Lake Elsinore)
10. Mission Trail at Malaga Road (Lake Elsinore/Wildomar)
11. Mission Trail at Olive Street (Lake Elsinore/Wildomar)
12. Mission Trail at Victorian Lane (Lake Elsinore/Wildomar)
13. Mission Trail at Lemon Street (Lake Elsinore/Wildomar)
14. Mission Trail at Corydon Road (Lake Elsinore/Wildomar)
15. Corydon Road at Cereal Street (Lake Elsinore/Wildomar)
16. Mission Trail at Bundy Canyon Road (Wildomar)
17. Orange Street at Bundy Canyon Road (Wildomar)
18. I-15 SB Ramps at Bundy Canyon Road (Wildomar)
19. I-15 NB Ramps at Bundy Canyon Road (Wildomar)
20. Corydon Road at Palomar Street (Lake Elsinore/Wildomar)
21. Mission Trail at Palomar Street (Wildomar)
22. Stoneman Street at Grand Avenue (Lake Elsinore)

23. Corydon Road at Grand Avenue (Lake Elsinore/Wildomar)
24. Grape Street at I-15 NB Ramps (Lake Elsinore) *[Future-Phase I]*
25. Diamond Drive at Olive Street (Lake Elsinore) *[Future-Phase I]*
26. "A" Street at Olive Street (Lake Elsinore) *[Future-Phase I]*
27. "A" Street at Victorian Lane (Lake Elsinore) *[Future-Phase I]*
28. "A" Street at Cereal Street (Lake Elsinore) *[Future-Phase I]*
29. Lucerne Street at Sylvester Street (Lake Elsinore) *[Future-Buildout]*
30. Stoneman Street at Cereal Street (Lake Elsinore) *[Future-Buildout]*

1.1.2 Roadway Segments

The study roadway segments listed below, along with their respective jurisdictions, are locations that could potentially be impacted by the Project. The twenty-six (26) existing roadway segments and six (6) future internal roadway segments listed below were selected based on the arterial network within the study area and discussions with City of Lake Elsinore staff:

1. Grape Street, east of Railroad Canyon Road (Lake Elsinore)
2. Railroad Canyon Rd, between Summerhill Dr/Grape St and Lakeshore Dr/Mission Trail (Lake Elsinore)
3. Lucerne Street, south of Lakeshore Drive (Lake Elsinore)
4. Casino Drive, east of Diamond Drive (Lake Elsinore)
5. Diamond Drive, between Lakeshore Drive/Mission Trail and Campbell Street (Lake Elsinore)
6. Diamond Drive, between Campbell Street and Malaga Road (Lake Elsinore)
7. Mission Trail, between Diamond Drive and Campbell Street (Lake Elsinore)
8. Mission Trail, between Campbell Street and Malaga Road (Lake Elsinore)
9. Malaga Road, between Diamond Drive and Mission Trail (Lake Elsinore)
10. Malaga Road, east of Mission Trail (Lake Elsinore/Wildomar)
11. Diamond Drive, north of Summerly Place (Lake Elsinore)
12. Mission Trail, between Malaga Road and Olive Street (Lake Elsinore/Wildomar)
13. Olive Street, between Mission Trail and Grape Street (Wildomar)
14. Mission Trail, between Olive Street and Victorian Lane (Lake Elsinore/Wildomar)
15. Mission Trail, between Victorian Lane and Lemon Street (Lake Elsinore/Wildomar)
16. Lemon Street, between Mission Trail and Grape Street (Wildomar)
17. Corydon Road, between Mission Trail and Cereal Street (Lake Elsinore/Wildomar)
18. Cereal Street, west of Corydon Road (Lake Elsinore)

19. Mission Trail, between Corydon Road and Bundy Canyon Road (Wildomar)
20. Bundy Canyon Road, between Mission Trail and I-15 SB Ramps (Wildomar)
21. Corydon Road, between Cereal Street and Palomar Street (Lake Elsinore/Wildomar)
22. Mission Trail, between Bundy Canyon Road and Palomar Street (Wildomar)
23. Palomar Street, between Corydon Road and Mission Trail (Wildomar)
24. Stoneman Street, north of Grand Avenue (Lake Elsinore)
25. Skylark Drive, north of Grand Avenue (Lake Elsinore)
26. Corydon Road, between Palomar Street and Grand Avenue (Lake Elsinore/Wildomar)
27. Sylvester Street, between Lucerne Street and Diamond Drive (Lake Elsinore)

[Future-Phase I]
28. Lucerne Street, between Sylvester Street and Cereal Street (Lake Elsinore)

[Future-Phase I]
29. Cereal Street, between Lucerne Street and Stoneman Street (Lake Elsinore)

[Future-Phase I]
30. Cereal Street, between Stoneman Street and Diamond Drive (Lake Elsinore)

[Future-Phase I]
31. Diamond Drive, between Olive Street and Cereal Street (Lake Elsinore)

[Future-Phase I]
32. Bundy Canyon Road, between Corydon Road and Mission Trail (Lake Elsinore)

[Future-Phase I]

1.2 Traffic Impact Analysis Components

The Highway Capacity Manual 2010 (HCM 2010) Delay, Volume to Capacity (V/C) ratio and corresponding Level of Service (LOS) calculations at the key study locations were used to evaluate the potential traffic-related impacts associated with area growth, cumulative projects and the Project. When necessary, this report recommends intersection/roadway segment improvements that may be required to accommodate future traffic volumes and restore/maintain an acceptable Level of Service and/or addresses the impact of the Project.

Included in this Traffic Impact Analysis are:

- Existing Traffic Counts,
- Modeled Project trip generation/distribution/assignment,
- Modeled Cumulative Projects trip generation/distribution/assignment,
- Weekday Daily, Saturday Daily, Weekday AM, Weekday PM, and Saturday Midday peak hour LOS analyses for Existing (i.e. Baseline) Conditions,
- Weekday Daily, Saturday Daily, Weekday AM, Weekday PM, and Saturday Midday peak hour LOS analyses for Existing (i.e. Baseline) Conditions with Project traffic,


- Weekday Daily, Saturday Daily, Weekday AM, Weekday PM, and Saturday Midday peak hour LOS analyses for Near-Term (Year 2022) Conditions without and with Project traffic,
- Weekday Daily, Saturday Daily, Weekday AM, Weekday PM, and Saturday Midday peak hour LOS analyses for Long-Term (Year 2040) Conditions without and with Project traffic,
- Planned and Recommended Improvements,
- Traffic Signal Warrant Analysis,
- Project Fair Share Analysis, and
- Caltrans Facilities Analysis.

Figure 1-1 presents a Vicinity Map, which illustrates the general location of the East Lake Specific Plan Area and depicts the existing and future (Phase I and Buildout) study locations and surrounding street system.

1.3 Traffic Impact Analysis Scenarios

The following scenarios are those for which Weekday AM, Weekday PM and Saturday Midday peak hour Delay calculations as well as Weekday Daily and Saturday Daily V/C calculations have been performed at the key intersections and roadway segments for existing, near-term, and long-term traffic conditions:

1. Existing Traffic Conditions,
2. Existing with East Lake Specific Plan (ELSP) Project Buildout Traffic Conditions,
3. Scenario (2) with Mitigation, if any,
4. Year 2022 without ELSP Project Phase I Traffic Conditions,
5. Year 2022 with ELSP Project Phase I Traffic Conditions,
6. Scenario (5) with Mitigation, if any,
7. Year 2040 with Adopted Specific Plan Traffic Conditions,
8. Year 2040 with ELSP Project Buildout Traffic Conditions, and
9. Scenario (8) with Mitigation, if any.



SOURCE: GOOGLE
KEY

- = EXISTING STUDY INTERSECTION
- = FUTURE STUDY INTERSECTION (PHASE I)
- = FUTURE STUDY INTERSECTION (BUILDOUT)
- = EXISTING STUDY ROADWAY SEGMENT
- = FUTURE STUDY ROADWAY SEGMENT (PHASE I)
- = FUTURE ROADWAY (PHASE I)
- = FUTURE ROADWAY (BUILDOUT)

LINSCOTT
LAW &
GREENSPAN
e n g i n e e r s



NO SCALE

FIGURE 1-1

VICINITY MAP

EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE

2.0 PROJECT DESCRIPTION AND LOCATION

The East Lake Specific Plan is generally located east of Lake Elsinore, south of Lakeshore Drive, west of Mission Trail/Corydon Road and North of Grand Avenue. The East Lake Specific Plan will consist of major mixed-use development including land uses such as residential, commercial, action sports, tourism, golf course/parks, preservation/mitigation areas, an airport and other uses. **Table 2-1** presents the land use breakdown for the East Lake Specific Plan broken down by Phase I and Buildout conditions, as well as by Planning Area. *Table 2-1* also details the land use breakdown specifically for the Adopted Specific Plan. **Figure 2-1** presents the existing aerial site for the East Lake Specific Plan area.

Phase I for the East Lake Specific Plan is expected to be completed by Year 2022 and this horizon year will be utilized to assess the Project's potential traffic impacts at Phase I occupancy within a near-term cumulative traffic setting.

Buildout for the East Lake Specific Plan is expected to be completed by Year 2040 and this buildout year will be utilized to assess the Project's potential traffic impacts at full occupancy under Year 2040 traffic conditions.

Figure 2-3 presents the East Lake Specific Plan Land Use Map, prepared by the City of Lake Elsinore, which corresponds with *Table 2-1* previously mentioned. **Figure 2-4** presents the East Lake Specific Plan Circulation Map which is basis for the assumed roadway network under Year 2040 traffic conditions.

Year 2040 With ELSP Project Buildout will be compared to Year 2040 With Adopted Specific Plan (Specific Plan No. 10) traffic conditions. **Figure 2-5** presents the Adopted Specific Plan Land Use Map, prepared by the City of Lake Elsinore, which corresponds with *Table 2-1* previously mentioned. **Figure 2-6** presents the Adopted Specific Plan Circulation Map which is basis for the assumed roadway network under Year 2040 traffic conditions.

2.1 East Lake Specific Plan Circulation

As shown in *Figure 2-4*, the East Lake Specific Plan area is comprised of several roadways, proposed and existing, that will provide access to the various planning areas. Lakeshore Drive and Mission Trail borders ELSP to the north and east, respectively. Corydon Road also borders ELSP to the east. Grand Avenue runs parallel to the southern border. Diamond Drive, Malaga Road, Olive Street, Victorian Lane and Cereal Street will extend through the ELSP area and provide access to the eight planning areas. Additionally under buildout conditions, Stoneman Street and Lucerne Street will be extended to Cereal Street and Sylvester Street, respectively, to provide additional access to within the East Lake Specific Plan area. Key study intersections #24 through #30 are proposed intersections within East Lake Specific Plan and will form with in conjunction with these future roadways. Further discussion on these future East Lake Specific Plan intersections and roadway segments is provided in *Section 9.0*.

TABLE 2-1
EAST LAKE SPECIFIC PLAN LAND USE PHASING SUMMARY⁵

| Planning Area | Land Use Type | Existing/Baseline Development | Proposed Phase I (Year 2022) Development | | Proposed Buildout (Year 2040) Development (SPN #11) | | Adopted Specific Plan Amendment #10 Development Totals | | Proposed 2040 Buildout Totals vs. Adopted SPA #10 Totals Difference |
|----------------------------------|---|-------------------------------|--|---------------------|---|----------------------|--|-----------|---|
| | | | Phase I Additional | Total After Phase I | Phase II Additional | Total After Buildout | | | |
| | | | | | | | Total | Units | |
| Planning Area 1 (707.5 Acres) | Golf Course (18 Hole) | 169 AC | -- | 169 AC | -- | 169 AC | 169 AC | -- | -- |
| | Hotel | -- | 90 RM | 90 RM | -- | 90 RM | -- | 90 RM | -- |
| | Single-Family Residential | 600 DU | 1,379 DU | 1,979 DU | -- | 1,979 DU | -- | 1,979 DU | -- |
| | Preservation/Mitigation | 100.43 AC | -- | 100.43 AC | -- | 100.43 AC | -- | 100.43 AC | -- |
| Planning Area 2 (310.6 Acres) | Active Recreation 2 (e.g. Ski/Water/Hockey) | -- | 60-100 AC | 60-100 AC | -- | 60-100 AC | -- | -- | 60-100 AC |
| | Action Sport 1 (e.g. Motocross) | 93 AC | -- | -- | -- | -- | 0 | -- | (93 AC) |
| | Commercial | -- | 43,500 SF | 43,500 SF | 246,500 SF | 290,000 SF | 392,040 SF (30 AC) | -- | (102,040 SF) |
| | Hotel | -- | -- | -- | 150 RM | 150 RM | -- | -- | 150 RM |
| | Multi-Family Residential | -- | 300 DU | 300 DU | 300 DU | 600 DU | -- | 1,301 DU | (701) |
| | Single-Family Residential | -- | -- | -- | -- | -- | -- | 930 DU | (930 DU) |
| | Restaurant | -- | 4,500 SF | 4,500 SF | 25,500 SF | 30,000 SF | -- | -- | 30,000 SF |
| | Park | -- | N/A | N/A | N/A | N/A | 7.5 AC | -- | N/A |
| Planning Area 3 (603.7 Acres) | Active Recreation 1 or 2 | -- | 100 AC | 100 AC | -- | 100 AC | -- | -- | 100 AC |
| | Active Recreation 2 (e.g. Ski/Water/Hockey) | -- | -- | -- | 60-100 AC | 60-100 AC | -- | -- | 60-100 AC |
| | Commercial | -- | 30,000 SF | 30,000 SF | 70,000 SF | 100,000 SF | -- | -- | 100,000 SF |
| | Hotel | -- | -- | -- | 150 RM | 150 RM | -- | -- | 150 RM |
| | Restaurant | -- | 4,500 SF | 4,500 SF | 25,500 SF | 30,000 SF | -- | -- | 30,000 SF |
| | Skydive Airport | 150 AC | -- | 150 AC | -- | 150 AC | 150 AC | -- | -- |
| | Multi-Family Residential | -- | -- | -- | -- | -- | -- | 48 DU | (48 DU) |
| | Single-Family Residential | -- | -- | -- | -- | -- | -- | 215 DU | (215 DU) |
| | Active Open Space | -- | -- | -- | -- | -- | 186.6 | -- | (186.6) |
| | Limited Industrial | -- | -- | -- | -- | -- | -- | -- | -- |
| | Preservation/Mitigation | -- | 20.46 AC | 20.46 AC | -- | 20.46 AC | -- | -- | 20.46 AC |
| Planning Area 4 (98.2 Acres) | Residential | 311 DU | -- | 311 DU | -- | 311 DU | -- | 311 DU | -- |
| | Park | 5.5 | -- | 5.5 | -- | 5.5 | 5.5 | -- | -- |
| | Preservation/Mitigation | 11.73 | -- | 11.73 | -- | 11.73 | 11.73 | -- | -- |
| Planning Area 5 (422.6 Acres) | Preservation/Mitigation | 422.6 AC | -- | 422.6 AC | -- | 422.6 AC | 422.6 AC | -- | -- |
| Planning Area 6 (425.2 Acres) | Active Recreation 1 (Baseball/Concert) | -- | 100 AC | 100 AC | -- | 100 AC | -- | -- | 100 AC |
| | Action Sport 1 (Motocross) | -- | 93 AC | 93 AC | -- | 93 AC | -- | -- | 93 AC |
| | Action Sport 2 (Hard Track) | -- | 80 AC | 80 AC | -- | 80 AC | -- | -- | 80 AC |
| | Commercial | -- | -- | -- | 10,000 SF | 10,000 SF | 818,928 SF | -- | (808,928 SF) |
| | Hotel | -- | -- | -- | 150 RM | 150 RM | -- | -- | 150 RM |
| | Multi-Family Residential | -- | -- | -- | -- | -- | -- | 0 DU | (0 DU) |
| | Single-Family Residential | -- | -- | -- | -- | -- | -- | 1,189 DU | (1,189 DU) |
| | Restaurant | -- | -- | -- | 7,500 SF | 7,500 SF | 7,500 SF | -- | 7,500 SF |
| | Preservation/Mitigation | -- | 70.18 AC | 70.18 AC | -- | 70.18 AC | 70.18 AC | -- | -- |
| Planning Area 7 (187.7 Acres) | Action Sports Uses | -- | -- | -- | 8.5 AC | 8.5 AC | 0 AC | -- | 7.5 AC |
| | Preservation/Mitigation | -- | 174.4 AC | 174.4 AC | -- | 174.4 AC | -- | -- | 174.4 AC |
| Planning Area 8 (196.7 Acres) | Commercial/Overlay | -- | -- | -- | 58,000 SF | 58,000 SF | 352,836 SF | -- | (294,836 SF) |
| | Multi-Family Residential | 195 DU | -- | 195 DU | 255 DU | 450 DU | -- | 535 DU | (85 DU) |
| | Single-Family Residential | 130 DU | -- | 130 DU | 170 DU | 300 DU | -- | 613 DU | (313 DU) |

KEY:

- [a] SF = Square-Feet
- [b] AC = Acres
- [c] RM = Rooms
- [d] DU = Dwelling Units

Notes:

1. Preservation/Mitigation area and passive open space area totals subject to change. Total preservation/mitigation area in Back Basin required for MSHCP compliance is 770 acres.

⁵ Source: City of Lake Elsinore.



LINSCOTT
LAW &
GREENSPAN
e ngineers



NO SCALE

SOURCE: GOOGLE


KEY


[Yellow dotted pattern] = PROJECT SITE

FIGURE 2-1

EXISTING AERIAL SITE PLAN
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE

n:\3500\2143544 - east lake specific plan eir, lake elsinore\6 - dwg\3544f2-1.dwg LDP 09:48:49 12-21-2016 aguilar






SOURCE: CITY OF LAKE ELSINORE

FIGURE 2-3

**PROPOSED EAST LAKE SPECIFIC PLAN
CIRCULATION MAP**
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE



- CITY BOUNDARY
- FLOODWAY
- RECREATION
- AIRPORT USE AREA
- LIMITED INDUSTRIAL
- GENERAL COMMERCIAL
- TOURIST COMMERCIAL
- COMMERCIAL MIXED USE
- RESIDENTIAL MIXED USE
- LOW DENSITY RESIDENTIAL
- LOW-MEDIUM RESIDENTIAL
- MEDIUM DENSITY RESIDENTIAL
- HIGH DENSITY RESIDENTIAL
- OPEN SPACE

n:\3500\2143544 - east lake specific plan eir, lake elsinore\6 - dwg\354412-4.dwg LDP 13:44:17 03-20-2017 besa

SOURCE: CITY OF LAKE ELSINORE

FIGURE 2-4

ADOPTED SPECIFIC PLAN
LAND USE MAP

EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE

LINSCOTT
LAW &
GREENSPAN
engineers



NO SCALE




FIGURE 2-5

**CITY OF LAKE ELSINORE
CIRCULATION ELEMENT**

EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE

3.0 ANALYSIS CONDITIONS AND METHODOLOGY

3.1 Existing Street Network

The I-15 Freeway provides regional access to the Project site. The I-15 Freeway runs in the north-south direction, east of the Project site. The principal local network of streets serving the site consists of Diamond Drive/Railroad Canyon Road, Lakeshore Drive/Mission Trail, Corydon Road, Orange Street, Malaga Road, Olive Street, Lemon Street, Bundy Canyon Road, Palomar Street and Grand Avenue. The following discussion provides a brief synopsis of the key area streets.

3.2 Existing Street Network

Diamond Drive/Railroad Canyon Road is a north-south roadway within the vicinity of the Project site. South of I-15 Southbound Ramps the roadway is Diamond Drive and turns into Railroad Canyon Road north of I-15 Southbound Ramps. On-street parking is not permitted on either side of the roadway in the vicinity of the Project. Diamond Drive/Railroad Canyon Road is a four-lane divided roadway with a posted speed limit of 35 miles per hour (mph) south of the I-15 freeway and decreases to 30 mph north of the I-15 freeway. Traffic signals control the key study intersections of Diamond Drive and Summerhill Drive/Grape Street, I-15 Northbound Ramps, I-15 Southbound Ramps, Auto Center Drive/Casino Drive, Campbell Street and Malaga Road.

Lakeshore Drive/Mission Trail is an east-west roadway west of Diamond Drive and a north-south roadway east of Diamond Drive. West of Diamond Drive the roadway is Lakeshore Drive and turns into Mission Trail east of Diamond Drive. On-street parking is not permitted on either side of the roadway within the Project vicinity. Lakeshore Drive/Mission Trail is a four-lane divided roadway with a posted speed limit of 45 mph. Traffic signals control the key study intersections of Lakeshore Drive/Mission Trail and Diamond Drive, Malaga Road, Olive Street, Lemon Street, Corydon Road and Bundy Canyon Road. The intersections of Lakeshore Drive/Mission Trail and Campbell Street, Victorian Lane and Palomar Street are stop-controlled.

Corydon Road is a north-south roadway within the vicinity of the Project site. On-street parking is generally not permitted on either side of the roadway. Corydon Road is a two-lane undivided roadway with a posted speed limit of 45 mph. Traffic signals control the key study intersections of Corydon Road and Mission Trail, Palomar Street and Grand Avenue. The intersection of Corydon Road and Cereal Street is controlled by a one-way stop.

Orange Street is a north-south roadway within the vicinity of the Project site. On-street parking is not permitted on either side of the roadway. Orange Street is a two-lane undivided roadway with a posted speed limit of 40 mph.

Malaga Road is an east-west roadway located within the vicinity of the Project site. On-street parking is not permitted on either side of the roadway. Malaga Road is a four-lane, divided roadway west of Mission Trail and a two-lane, undivided roadway east of Mission trail. The posted speed limit along Malaga Road is 35 mph.

Olive Street is an east-west, two-lane undivided roadway located within the vicinity of the Project site. On-street parking is permitted on both sides of the roadway within the vicinity of the Project. The posted speed limit along Olive Street is 25 mph.

Lemon Street is an east-west, two-lane undivided roadway located within the vicinity of the Project site. On-street parking is not permitted on both sides of the roadway within the vicinity of the Project. The posted speed limit along Lemon Street is 25 mph.

Bundy Canyon Road is an east-west roadway located within the vicinity of the Project site. Bundy Canyon Road is a two-lane undivided roadway between Mission Trail and Orchard Street, three-lane undivided roadway between Orchard Street and Orange Street, four-lane divided roadway between Orange Street and I-15 Northbound Ramps and a two-lane undivided roadway east of the I-15 Northbound Ramps. Parking is not permitted on either side of the roadway within the vicinity of the Project. The posted speed limit on Bundy Canyon Road is 45 mph. The intersections of Bundy Canyon Road at Mission Trail, Orange Street, I-15 Southbound Ramps and I-15 Northbound Ramps are controlled by traffic signals.

Palomar Street is an east-west, two-lane undivided roadway located within the vicinity of the Project site. Parking is permitted on the south side of the roadway and the posted speed limit on Palomar Street is 35 mph.

Grand Avenue is an east-west, two-lane divided roadway located within the vicinity of the Project site. On-street parking is not permitted on either side of the roadway and the posted speed limit on Grand Avenue is 50 mph.

Figure 3-1 presents an inventory of the existing roadway conditions within the study area evaluated in this report. The number of travel lanes and intersection controls for the key area study intersections and roadway segments are identified.

3.3 Existing Transit Services

The study area is served by the Riverside Transit Agency (RTA). A description of the transit services is as follows:

Riverside Transit Agency (RTA)

Route 8: Lake Elsinore, Wildomar Loop Route

- The route extends from the Lake Elsinore Outlet Center in Lake Elsinore to the Wildomar Independent and Assisted Living in Wildomar. The route then travels northwest along Grand Avenue past the lake and heads northeast up Riverside Drive back towards the Outlet Center.
- The route mainly travels along Lakeshore Drive/Mission Trail, Grand Avenue and Palomar Street within the vicinity of the Project.
- There are several bus stops located within the vicinity of the study area. They are located:
 - Twenty-three bus stops located along Lakeshore Drive/Mission Trail
 - Sixteen bus stops located along Grand Avenue

- Five bus stops located along Palomar Street

3.4 Existing Traffic Volumes

Existing AM, PM and Saturday Midday peak hour traffic volumes for the twenty-three (23) key existing study intersections and daily two-way traffic volumes for the twenty-six (26) key existing roadway segments evaluated in this report, were collected by *Counts Unlimited, Inc.* in May and December 2016. **Appendix B** contains the existing intersection turning movement and roadway segment traffic count data.

Figures 3-2, 3-3 and 3-4 present the existing Weekday AM, Weekday PM and Saturday Midday peak hour traffic volumes, respectively, for the twenty-three (23) key existing study intersections. **Figures 3-5 and 3-6** present the existing Weekday and Saturday daily traffic volumes, respectively, for the twenty-six (26) key existing study roadway segments.

3.5 Level Of Service (LOS) Analysis Methodologies

AM, PM and Saturday Midday peak hour operating conditions for the key study intersections were evaluated using the methodology outlined in *Chapter 18 of the Highway Capacity Manual 2010 (HCM 2010)* for signalized intersections, the methodology outlined in *Chapter 19 of the HCM 2010* for two-way stop-controlled intersections, and the methodology outlined in *Chapter 20 of the HCM 2010* for all-way stop-controlled intersections. Daily operating conditions for the key study roadway segments were analyzed using the *Volume to Capacity (V/C) Ratio*. Freeway mainline segments and ramp merge/diverge segments were analyzed using *HCM 2010 Chapters 11 and 13, respectively*. Daily operating conditions for the key study roadway segments were analyzed using the *Volume to Capacity (V/C) ratio*.

3.5.1 *Highway Capacity Manual (HCM) Method of Analysis (Signalized Intersections)*

Based on the HCM operations method of analysis, level of service for signalized intersections and approaches is defined in terms of control delay, which is a measure of the increase in travel time due to traffic signal control, driver discomfort, and fuel consumption. Control delay includes the delay associated with vehicles slowing in advance of an intersection, the time spent stopped on an intersection approach, the time spent as vehicles move up in the queue, and the time needed for vehicles to accelerate to their desired speed. LOS criteria for traffic signals are stated in terms of the control delay in seconds per vehicle. The LOS thresholds established for the automobile mode at a signalized intersection are shown in **Table 3-1**.

3.5.2 *Highway Capacity Manual (HCM) Method of Analysis (Unsignalized Intersections)*

The HCM unsignalized methodology for stop-controlled intersections was utilized for the analysis of the unsignalized intersections. LOS criteria for unsignalized intersections differ from LOS criteria for signalized intersections as signalized intersections are designed for heavier traffic and therefore a greater delay. Unsignalized intersections are also associated with more uncertainty for users, as delays are less predictable, which can reduce users' delay tolerance.

3.5.2.1 Two-Way Stop-Controlled Intersections

Two-way stop-controlled intersections are comprised of a major street, which is uncontrolled, and a minor street, which is controlled by stop signs. Level of service for a two-way stop-controlled intersection is determined by the computed or measured control delay. The control delay by movement, by approach, and for the intersection as a whole is estimated by the computed capacity for each movement. LOS is determined for each minor-street movement (or shared movement) as well as major-street left turns. The worst side street approach delay is reported. LOS is not defined for the intersection as a whole or for major-street approaches, as it is assumed that major-street through vehicles experience zero delay. The HCM control delay value range for two-way stop-controlled intersections are shown in *Table 3-2*.

3.5.2.2 All-Way Stop-Controlled Intersections

All-way stop-controlled intersections require every vehicle to stop at the intersection before proceeding. Because each driver must stop, the decision to proceed into the intersection is a function of traffic conditions on the other approaches. The time between subsequent vehicle departures depends on the degree of conflict that results between the vehicles and vehicles on the other approaches. This methodology determines the control delay for each lane on the approach, computes a weighted average for the whole approach, and computes a weighted average for the intersection as a whole. Level of service (LOS) at the approach and intersection levels is based solely on control delay. The HCM control delay value range for all-way stop-controlled intersections are shown in *Table 3-2*.

3.5.3 Volume to Capacity (V/C) Ratio Method of Analysis (Roadway Segments)

In conformance with the City of Lake Elsinore requirements, daily operating conditions for the key study roadway segments have been investigated according to the Volume to Capacity (V/C) Ratio of each roadway segment. The V/C relationship is used to estimate the LOS of the roadway segment with the volume based on the 24-hour traffic volumes and the capacity based on the City's classification of each roadway. The six qualitative categories of Level of Service have been defined along with the corresponding Volume to Capacity (V/C) value range and are shown in *Table 3-3*.

The roadway segment daily capacity of each street classification according to the *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)* is presented in *Table 3-4*.

3.5.4 Basic Freeway Segments

The basic freeway segment criteria is based on peak hour *HCM 2010* density analysis. The capacities are based on information contained in the *HCM 2010*. Existing traffic count data for the analyzed freeway segments was obtained from the Caltrans website.

Basic freeway segment levels of service are determined from segment density. *Table 3-5* presents the correlation between LOS and density in terms of passenger cars per mile per lane (pc/mi/ln) for freeway basic freeway segments.

3.5.5 Freeway Merge And Diverge Segments

Freeway merge and diverge segment analysis is based on peak hour *HCM 2010* density analysis for freeway-to-arterial interchanges. According to *HCM 2010* methodology, the ramp merge and diverge segments focus on an influential area of 1,500 feet, including the acceleration or deceleration lane(s) and adjacent freeway ramps. The methodology incorporates three fundamental steps:

- Determination of the traffic entering the freeway lanes upstream of the merge or at the beginning of the deceleration lane at diverge;
- Determination of the capacity for the segment; and
- Determination of the density of traffic flow within the ramp influence area and its level of service.

The level of service (LOS) for freeway ramps is determined by traffic density based on criteria outlined in the *HCM 2010*. *Table 3-6* presents the correlation between LOS and density in terms of passenger cars per mile per lane (pc/mi/ln) for freeway merge and diverge segments.

3.6 Impact Criteria and Thresholds

City of Lake Elsinore

According to City of Lake Elsinore criteria, LOS D is the minimum acceptable condition that should be maintained during the weekday AM/PM and Saturday Midday peak commute hours. Therefore, any City intersection operating at LOS “E” or “F” will be considered adverse. However, as noted by the *City of Lake Elsinore General Plan Update Draft Program EIR* on page 3.4-58, the City considers LOS “E” as acceptable for City intersections located within either the Main Street Overlay District or the Ballpark District in an effort to increase activity and revitalize these areas. The roadway segments that are located within the City of Lake Elsinore must also maintain a LOS “D” or better. An impact is considered significant if the ELSP causes an intersection to drop below the target LOS as described above.

City of Wildomar

The definition for minimum LOS for intersections and roadway segments within the City of Wildomar is based on the County of Riverside General Plan Circulation Element. *Riverside County General Plan Policy C 2.1* states that LOS “D” shall apply to all development proposals located within the Community Development Areas of the Elsinore Area Plan, where the Project is located. In regards to this traffic analysis, LOS “D” will be considered the minimum acceptable LOS at all intersections and roadway segments within the City of Wildomar. Consistent with County of Riverside guidelines, an impact is considered significant if the proposed project causes an intersection to drop below the target LOS as described above.

Caltrans

Caltrans “endeavors to maintain a target LOS at the transition between LOS “C” and LOS “D” on State highway facilities”; it does not require that LOS “D” (shall) be maintained. However, Caltrans acknowledges that this may not always be feasible and recommends that the lead agency consult with Caltrans to determine the appropriate target LOS. For this analysis, LOS D is the target level of

service standard and will be utilized to assess the project impacts at the state-controlled study intersections, consistent with City of Lake Elsinore requirements.

Based on the above, the following summarizes the minimum LOS required for each key study intersection and roadway segment:

| <u>LOS "D" Requirements – Key Study Intersections</u> | |
|--|--|
| 1. Railroad Canyon Rd at Summerhill Lane/Grape St | 19. I-15 NB Ramps at Bundy Canyon Road |
| 2. Railroad Canyon Road at I-15 NB Ramps | 20. Corydon Road at Palomar Street |
| 3. Diamond Drive at I-15 SB Ramps | 21. Mission Trail at Palomar Street |
| 4. Diamond Dr at Casino Drive/Auto Center Dr | 22. Stoneman Street at Grand Avenue |
| 5. Lucerne Street at Lakeshore Drive | 23. Corydon Road at Grand Avenue |
| 11. Mission Trail at Olive Street | 24. I-15 NB Ramps at Grape Street |
| 12. Mission Trail at Victorian Lane | 25. Diamond Drive at Olive Street |
| 13. Mission Trail at Lemon Street | 26. "A" Street at Olive Street |
| 14. Mission Trail at Corydon Road | 27. "A" Street at Victorian Lane |
| 15. Corydon Road at Cereal Street | 28. "A" Street at Cereal Street |
| 16. Mission Trail at Bundy Canyon Road | 29. Lucerne Street at Sylvester Street |
| 17. Orange Street at Bundy Canyon Road | 30. Stoneman Street at Cereal Street |
| 18. I-15 SB Ramps at Bundy Canyon Road | |
| <u>LOS "E" Requirements – Key Study Intersections</u> | |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | 9. Diamond Drive at Malaga Road |
| 7. Diamond Drive at Campbell Street | 10. Mission Trail at Malaga Road |
| 8. Mission Trail at Campbell Street | |
| <u>LOS "D" Requirements – Key Study Roadway Segments</u> | |
| 1. Grape Street, east of Railroad Canyon Road | |
| 2. Railroad Canyon Rd, between Summerhill Dr/Grape St and Lakeshore Dr/Mission Trail | |
| 3. Lucerne Street, south of Lakeshore Drive | |
| 4. Casino Drive, east of Diamond Drive | |
| 5. Diamond Drive, between Lakeshore Drive/Mission Trail and Campbell Street | |
| 6. Diamond Drive, between Campbell Street and Malaga Road | |
| 7. Mission Trail, between Diamond Drive and Campbell Street | |
| 8. Mission Trail, between Campbell Street and Malaga Road | |

9. Malaga Road, between Diamond Drive and Mission Trail
10. Malaga Road, east of Mission Trail
11. Diamond Drive, north of Summerly Place
12. Mission Trail, between Malaga Road and Olive Street
13. Olive Street, between Mission Trail and Grape Street
14. Mission Trail, between Olive Street and Victorian Lane
15. Mission Trail, between Victorian Lane and Lemon Street
16. Lemon Street, between Mission Trail and Grape Street
17. Corydon Road, between Mission Trail and Cereal Street
18. Cereal Street, west of Corydon Road
19. Mission Trail, between Corydon Road and Bundy Canyon Road
20. Bundy Canyon Road, between Mission Trail and I-15 SB Ramps
21. Corydon Road, between Cereal Street and Palomar Street
22. Mission Trail, between Bundy Canyon Road and Palomar Street
23. Palomar Street, between Corydon Road and Mission Trail
24. Stoneman Street, north of Grand Avenue
25. Skylark Drive, north of Grand Avenue
26. Corydon Road, between Palomar Street and Grand Avenue
27. Sylvester Street, between Lucerne Street and Diamond Drive
28. Lucerne Street, between Sylvester Street and Cereal Street
29. Cereal Street, between Lucerne Street and Stoneman Street
30. Cereal Street, between Stoneman Street and Diamond Drive
31. Diamond Drive, between Olive Street and Cereal Street
32. Bundy Canyon Road, between Corydon Road and Mission Trail

TABLE 3-1
LEVEL OF SERVICE CRITERIA FOR SIGNALIZED INTERSECTIONS (HCM METHODOLOGY)⁶

| Level of Service (LOS) | Control Delay Per Vehicle (seconds/vehicle) | Level of Service Description |
|------------------------|---|--|
| A | ≤ 10.0 | This level of service occurs when progression is extremely favorable and most vehicles arrive during the green phase. Most vehicles do not stop at all. Short cycle lengths may also contribute to low delay. |
| B | > 10.0 and ≤ 20.0 | This level generally occurs with good progression, short cycle lengths, or both. More vehicles stop than with LOS A, causing higher levels of average delay. |
| C | > 20.0 and ≤ 35.0 | Average traffic delays. These higher delays may result from fair progression, longer cycle lengths, or both. Individual cycle failures may begin to appear at this level. The number of vehicles stopping is significant at this level, though many still pass through the intersection without stopping. |
| D | > 35.0 and ≤ 55.0 | Long traffic delays At level D, the influence of congestion becomes more noticeable. Longer delays may result from some combination of unfavorable progression, long cycle lengths, or high v/c ratios. Many vehicles stop and the proportion of vehicles not stopping declines. Individual cycle failures are noticeable. |
| E | > 55.0 and ≤ 80.0 | Very long traffic delays This level is considered by many agencies to be the limit of acceptable delay. These high delay values generally indicate poor progression, long cycle lengths and high v/c ratios. Individual cycle failures are frequent occurrences. |
| F | ≥ 80.0 | Severe congestion This level, considered to be unacceptable to most drivers, often occurs with over saturation, that is, when arrival flow rates exceed the capacity of the intersection. It may also occur at high v/c ratios below 1.0 with many individual cycle failures. Poor progression and long cycle lengths may also be major contributing factors to such delay levels. |

⁶ Source: *Highway Capacity Manual 2000*, Chapter 16 (Signalized Intersections).

TABLE 3-2
LEVEL OF SERVICE CRITERIA FOR UNSIGNALIZED INTERSECTIONS (HCM METHODOLOGY)⁷

| Level of Service (LOS) | Highway Capacity Manual (HCM) Delay Per Vehicle (seconds/vehicle) | Level of Service Description |
|-----------------------------------|--|-------------------------------------|
| A | ≤ 10.0 | Little or no delay |
| B | > 10.0 and ≤ 15.0 | Short traffic delays |
| C | > 15.0 and ≤ 25.0 | Average traffic delays |
| D | > 25.0 and ≤ 35.0 | Long traffic delays |
| E | > 35.0 and ≤ 50.0 | Very long traffic delays |
| F | > 50.0 | Severe congestion |

⁷ Source: *Highway Capacity Manual 2000*, Chapter 17 (Unsignalized Intersections).

TABLE 3-3
LEVEL OF SERVICE CRITERIA FOR ROADWAY SEGMENTS (V/C METHODOLOGY)⁸

| Level of Service (LOS) | Volume to Capacity Ratio (V/C) | Level of Service Description |
|-------------------------------|---------------------------------------|--|
| A | ≤ 0.600 | EXCELLENT. Describes primarily free flow operations at average travel speeds, usually about 90% of the free flow speed for the arterial class. Vehicles are completely unimpeded in their ability to maneuver within the traffic stream. Stopped delay at signalized intersections is minimal. |
| B | 0.601 – 0.700 | VERY GOOD. Represents reasonably unimpeded operations at average travel speeds, usually about 70% of the free flow speed for the arterial class. The ability to maneuver within the traffic stream is only slightly restricted and stopped delays are not bothersome. Drivers are not generally subjected to appreciable tension. |
| C | 0.701 – 0.800 | GOOD. Represents stable conditions; however, ability to maneuver and change lanes in mid-block location may be more restricted than in LOS B, and longer queues and/or adverse signal coordination may contribute to lower average travel speeds of about 50% of the average free flow speed for the arterial class. Motorists will experience appreciable tension while driving. |
| D | 0.801 – 0.900 | FAIR. Borders on a range in which small increases in flow may cause substantial increases in approach delay and, hence, decreases in arterial speed. This may be due to adverse signal progression, inappropriate signal timing, high volumes, or some combination of these. Average travel speeds are about 40% of free flow speed. |
| E | 0.901 – 1.000 | POOR. Characterized by significant approach delays and average travel speeds of one-third the free flow speed or lower. Such operations are caused by some combination of adverse progression, high signal density, extensive queuing at critical intersections, and inappropriate signal timing. |
| F | > 1.000 | FAILURE. Characterizes arterial flow at extremely low speeds below one-third to one-quarter of the free flow speed. Intersection congestion is likely at critical signalized locations, with resultant high approach delays. Adverse progression is frequently a contributor to this condition. |

Note:

- LOS F applies whenever the flow rate exceeds the segment capacity.

⁸ Source: *Transportation Research Board 2000*.

TABLE 3-4
DAILY ROADWAY SEGMENT CAPACITIES⁹

| Type of Arterial | Lane Configuration | LOS E Capacity (VPD) |
|-------------------|--------------------|----------------------|
| Urban Arterial | 8-Lanes | 71,800 |
| Urban Arterial | 6-Lanes | 53,900 |
| Major | 4-Lanes | 34,100 |
| Secondary | 4-Lanes | 25,900 |
| Divided Collector | 4-Lanes | 18,000 |
| Collector | 2-Lanes | 13,000 |

Notes:

- VPD = Vehicles per Day

⁹ Source: *City of Lake Elsinore General Plan Update Draft Program EIR – Section 3.4: Transportation and Circulation*, August 2011.

TABLE 3-5
BASIC FREEWAY SEGMENTS LEVEL OF SERVICE CRITERIA (HCM METHODOLOGY)¹⁰

| LOS | Basic Freeway Segment Density (pc/mi/ln) |
|------------|---|
| A | ≤ 11.0 |
| B | $> 11.0 - 18.0$ |
| C | $> 18.0 - 26.0$ |
| D | $> 26.0 - 35.0$ |
| E | $> 35.0 - 45.0$ |
| F | > 45.0 |

¹⁰ Source: *HCM 2010, Chapter 11 – Basic Freeway Segments, Exhibit 11-5.*

TABLE 3-6
FREEWAY MERGE AND DIVERGE SEGMENTS LEVEL OF SERVICE CRITERIA (HCM METHODOLOGY)¹¹

| LOS | Freeway Ramp Density (pc/mi/ln) | Level of Service Description |
|------------|--|---|
| A | ≤ 10.0 | Unrestricted operations |
| B | $> 10.0 - 20.0$ | Merging and diverging maneuvers noticeable to drivers |
| C | $> 20.0 - 28.0$ | Influence area speeds begin to decline |
| D | $> 28.0 - 35.0$ | Influence area turbulence becomes intrusive |
| E | > 35.0 | Turbulence felt by virtually all drivers |
| F | Demand Exceeds Capacity | Ramp and freeway queues form |

¹¹ Source: HCM 2010, Chapter 13 – Freeway Merge and Diverge Segments, Exhibit 13-2.





FIGURE 3-1

EXISTING LANE GEOMETRIES
AND INTERSECTION CONTROLS
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE




LINSCOTT
LAW &
GREENSPAN
engineers

N
NO SCALE

KEY
= STUDY INTERSECTION

FIGURE 3-2
EXISTING WEEKDAY AM PEAK HOUR TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE



KEY


EXISTING WEEKDAY PM PEAK HOUR TRAFFIC VOLUMES EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE

LINSCOTT
LAW &
GREENSPAN



O SCALE

FIGURE 3-3







FIGURE 3-5

 EXISTING WEEKDAY DAILY TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE



LINSCOTT
LAW &
GREENSPAN
engineering



NO SCALE

KEY
= STUDY ROADWAY SEGMENT

FIGURE 3-6

EXISTING SATURDAY DAILY TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE

4.0 PROJECT TRAFFIC CHARACTERISTICS

4.1 Project Trip Generation Forecast and Assignment

Trip generation is expressed in vehicle trip ends, defined as one-way vehicular movements, either entering or exiting the generating land use. The East Lake Specific Plan traffic has been modeled by LSA Associates, Inc. using the City of Lake Elsinore Transportation and Analysis Model (LETAM). Appropriate socio-economic data (SED) data was allocated to the ELSP Traffic Analysis Zones (TAZs) based on the project description information provided by the City of Lake Elsinore regarding ELSP land uses, which is also reflected in *Table 2-1*. This was done for both the Adopted Specific Plan as well as the Specific Plan Amendment scenarios. Riverside County FAR conversion factors that are allocated for the region have been utilized to develop SED data for the Project. Furthermore, county rates have also been used for converting square feet to employment for updating the SED data within the specific plan TAZs. Appropriate land uses were removed from the Buildout traffic conditions in order to derive Phase I Project traffic only.

4.1.1 Year 2022 East Lake Specific Plan Project Phase I Assignment


Figures 4-1 and *4-2* present the daily Phase I Project traffic volumes for the Weekday and Saturday traffic conditions, respectively. The traffic volume assignments presented reflect the modeled traffic from the LETAM.

4.1.2 Year 2040 East Lake Specific Plan Project Buildout Assignment

Figures 4-3 and *4-4* present the daily Project Buildout traffic volumes for the Weekday and Saturday traffic conditions, respectively. The traffic volume assignments presented reflect the modeled traffic from the LETAM.

4.2 Vehicle Miles Travelled (VMT)

The Vehicle Miles Travelled (VMT) analysis utilizes the Lake Elsinore Transportation and Analysis Model (LETAM), which was the model used to forecast future traffic levels in this traffic study. A select zone run was conducted for TAZs that are included within the East Lake Specific Plan Project Buildout. Daily Project Buildout trips from each of these TAZs on the model roadway network were obtained using the select zone assignment output from the model run. These trips were multiplied with the individual length of each respective roadway link in the model to develop the Project's daily VMT. Based on these calculations, the Project Buildout's daily VMT is forecasted to be 473,696 miles.



LINSCOTT
LAW &
GREENSPAN
engineering





NO SCALE


KEY
= STUDY ROADWAY SEGMENT

FIGURE 4-1

ELSP PROJECT PHASE I
WEEKDAY DAILY TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE







5.0 FUTURE TRAFFIC CONDITIONS

5.1 Travel Demand Model Methodology

Traffic volume forecasts for all scenarios, excluding Existing traffic conditions which come directly from the traffic count data, were obtained by LSA Associates, Inc. through utilization of the City of Lake Elsinore Transportation and Analysis Model (LETAM). Model runs have been conducted for the Base (Year 2007) and Future (Year 2035) scenarios. To incorporate the proposed ELSP, some roadway network and socio-economic data (SED) modifications were made in LETAM to appropriately incorporate the proposed project. These changes were made in both the base and future model scenarios. Additionally, both the base and future year model networks do not include some of the major roadway segments within and in the near vicinity of the project area. These roadways have been added into the model network to reflect appropriate assignment of traffic on to the study area roadway system. The internal and external roadway networks change between Existing, Year 2022 and Year 2040 traffic conditions, resulting in noticeable volume differences between the different horizon years.

5.1.1 *Volume Adjustment*

Using the City of Lake Elsinore General Plan Circulation Element with selected CIP projects added as well as the Railroad Canyon Road Interchange Project (implemented only under scenarios in which the respective project is anticipated to be complete), projected traffic volumes were obtained for each intersection and roadway segment. The model produces peak period and off-peak period volumes (6 AM – 9 AM, 9 AM – 3 PM, 3 PM – 7 PM and 7 PM – 6 AM). Before converting the model peak period link volumes to future turning movement volumes for analysis, the model volumes must be reviewed and adjusted.

The first step is to obtain the approach and departure volumes from the model for each leg of the analyzed intersections. The next step converts the model approach and departure volumes from AM and PM peak period volumes to peak hour volumes. The AM peak hour volumes are calculated by multiplying the AM peak period volumes by 38%. Similarly, the PM peak hour volumes are calculated by multiplying the PM period volumes by 28%. These are the percentages of vehicles that are assumed to occur in the peak hour of the peak period. These factors are derived from SCAG research. It should be noted that the LETAM does not include any model data for Saturday Midday peak hour volumes or Saturday Daily volumes. Engineering judgement was used in order to convert the Weekday Midday and Weekday Daily model runs into Saturday Midday and Saturday Daily volumes, respectively. The next step is to determine the difference between the base year (2007) peak hour model volumes and the Buildout (Year 2035) peak hour model volumes. This “difference” represents the projected growth in traffic on each approach to the Buildout of the General Plan using the SCAG 2035 CTP model. This approach was slightly adjusted for each study scenario in order to develop accurate volumes.

5.1.2 *B-turn Methodology*

The base year turning movement counts (Year 2016) for each intersection must be converted to approach and departure volumes for each leg of the intersection. Once the base counts are in this

format, the difference between the Buildout model and base model are then added to the base year counts for each corresponding approach and departure volume. This step provides the adjusted volumes that will be used to determine the Buildout turning movement volumes. The next process in the forecasting of future turning volumes applies the B-turn methodology. The B-turn methodology is generally described in the “*National Cooperative Highway Research Program Report (NCHRP) 255: Highway Traffic Data for Urbanized Area Project Planning and Design*”, Chapter 8. The B-turn method uses the base year turning percentages (from traffic counts) and proceeds through an iterative computational technique to produce a final set of future year turning volumes. The computations involve alternatively balancing the rows (approaches) and the columns (departures) of a turning movement matrix until an acceptable convergence is obtained. Future year link volumes are fixed using this method and the turning movements are adjusted to match. The results must be checked for reasonableness, and manual adjustments are sometimes necessary.

Finally, it should be noted that all provided volumes are from a Citywide General Plan level model that was not specifically developed for analysis of individual intersection turning movements. Therefore each projected volume was reviewed carefully and adjustments were applied as warranted based on local conditions and professional judgment.

5.2 Existing With East Lake Specific Plan Project Buildout Traffic Volumes

The first step is to determine the growth or decline for each approach and departure for every study intersection and roadway segment between the “2007 Base Model” and the “2007 Base Model with the ELSP Buildout Network (No Project).” This difference is then grown by 2% per year (20% total) and applied to the 2017 existing counts and post-processed in order to determine the shift in existing volumes if the ELSP Buildout Network is included. The “ELSP Project Buildout Select Zone Model” was then added on top of the shifted existing volumes and post-processed to derive the Existing With ELSP Project Buildout traffic volumes. This process was conducted for Weekday AM, Weekday PM and Saturday Midday peak hours as well as Weekday Daily and Saturday Daily.

Figures 5-1, 5-2 and 5-3 present the anticipated Weekday AM/PM and Saturday Midday peak hour Existing With ELSP Project Buildout traffic volumes, respectively, at the thirty (30) key study intersections. **Figures 5-4 and 5-5** present the Weekday and Saturday daily Existing With ELSP Project Buildout daily traffic volumes, respectively, for the thirty-one (31) key study roadway segments (roadway segment 32 does not exist under Existing With ELSP Project Buildout traffic conditions).

5.3 Year 2022 Cumulative Traffic Conditions

5.3.1 Cumulative Projects Traffic

The City of Lake Elsinore and the City of Wildomar identified eight (8) large cumulative projects within the Project study area that needed to be confirmed were included in the model runs prior to developing traffic volumes. **Table 5-1** presents the jurisdiction, description and development totals of these eight (8) cumulative projects and **Figure 5-6** presents their respective locations on a map. Furthermore, due to its proximity to the East Lake Specific Plan and the large amount of volume it

attracts during the Midday peak hour on a Saturday, the Diamond Sports Center project was manually assigned to the Year 2022 traffic volumes and Year 2040 traffic volumes after these volumes were post-processed from the model runs.

5.4 Year 2022 Without East Lake Specific Plan Project Phase I Traffic Volumes

The first step is to determine the growth or decline for each approach and departure for every study intersection and roadway segment between the “2007 Base Model” and the “2007 Base Model with the ELSP Project Phase I Network and Year 2022 External Network (No Project).” This difference is then grown by 2% per year (20% total) and applied to the 2017 existing counts and post-processed in order to determine the shift in existing volumes if the ELSP Project Phase I Network as well as the Year 2022 external network changes are included. The growth between the “2007 Base Model” and the “2035 Base Model with the ELSP Project Phase I Network and Year 2022 External Network (No Project)” was then added on top of the shifted existing volumes in order to determine the Year 2022 Without ELSP Project Phase I traffic volumes. It should be noted that the growth was interpolated between 2007 and 2035 in order to derive Year 2022 volumes. This process was conducted for Weekday AM, Weekday PM and Saturday Midday peak hours as well as Weekday Daily and Saturday Daily.

Figures 5-7, 5-8 and 5-9 present the anticipated Weekday AM/PM and Saturday Midday peak hour Year 2022 Without ELSP Project Phase I traffic volumes, respectively, at the twenty-eight (28) key study intersections (intersections 29 and 30 do not exist under Year 2022 traffic conditions). *Figures 5-10 and 5-11* present the Weekday and Saturday daily Year 2022 Without ELSP Project Phase I daily traffic volumes, respectively, for the thirty-two (32) key study roadway segments.

5.5 Year 2022 With East Lake Specific Plan Project Phase I Traffic Volumes

The “ELSP Project Phase I” trips were then added on top of the Year 2022 Without ELSP Project Phase I traffic volumes and post-processed to derive the Year 2022 With ELSP Project Phase I traffic volumes. This process was conducted for Weekday AM, Weekday PM and Saturday Midday peak hours as well as Weekday Daily and Saturday Daily.

Figures 5-12, 5-13 and 5-14 present the anticipated Weekday AM/PM and Saturday Midday peak hour Year 2022 With ELSP Project Phase I traffic volumes, respectively, at the twenty-eight (28) key study intersections (intersections 29 and 30 do not exist under Year 2022 traffic conditions). *Figures 5-15 and 5-16* present the Weekday and Saturday daily Year 2022 With ELSP Project Phase I daily traffic volumes, respectively, for the thirty-two (32) key study roadway segments.

5.6 Year 2040 With Adopted Specific Plan Traffic Volumes

The first step is to determine the growth or decline for each approach and departure for every study intersection and roadway segment between the “2007 Base Model” and the “2007 Base Model with the Adopted Specific Plan Network and Year 2040 External Network (No Project).” This difference is then grown by 2% per year (20% total) and applied to the 2017 existing counts and post-processed in order to determine the shift in existing volumes if the Adopted Specific Plan Network as well as the Year 2040 external network changes are included. The growth between the “2007 Base Model”

and the “2035 Base Model with the Adopted Specific Plan Network and Year 2040 External Network (No Project)” was then added on top of the shifted existing volumes in order to determine the Year 2040 Without Adopted Specific Plan traffic volumes. It should be noted that the growth was increased further in order to derive Year 2040 volumes. The “Adopted Specific Plan Select Zone Model” was then added on top of the Year 2040 Without Adopted Specific Plan traffic volumes and post-processed to derive the Year 2040 With Adopted Specific Plan traffic volumes. This process was conducted for Weekday AM, Weekday PM and Saturday Midday peak hours as well as Weekday Daily and Saturday Daily.

Figures 5-17, 5-18 and 5-19 present the anticipated Weekday AM/PM and Saturday Midday peak hour Year 2040 With Adopted Specific Plan traffic volumes, respectively, at the thirty (30) key study intersections. **Figures 5-20 and 5-21** present the Weekday and Saturday daily Year 2040 With Adopted Specific Plan daily traffic volumes, respectively, for the thirty-two (32) key study roadway segments.

5.7 Year 2040 With East Lake Specific Plan Project Buildout Traffic Volumes

The first step is to determine the growth or decline for each approach and departure for every study intersection and roadway segment between the “2007 Base Model” and the “2007 Base Model with the ELSP Project Buildout Network and Year 2040 External Network (No Project).” This difference is then grown by 2% per year (20% total) and applied to the 2017 existing counts and post-processed in order to determine the shift in existing volumes if the ELSP Project Buildout Network as well as the Year 2040 external network changes are included. The growth between the “2007 Base Model” and the “2035 Base Model with the ELSP Project Buildout Network and Year 2040 External Network (No Project)” was then added on top of the shifted existing volumes in order to determine the Year 2040 Without ELSP Project Buildout traffic volumes. It should be noted that the growth was increased further in order to derive Year 2040 volumes. The “ELSP Project Buildout Select Zone Model” was then added on top of the Year 2040 Without ELSP Project Buildout traffic volumes and post-processed to derive the Year 2040 With ELSP Project Buildout traffic volumes. This process was conducted for Weekday AM, Weekday PM and Saturday Midday peak hours as well as Weekday Daily and Saturday Daily.

Figures 5-22, 5-23 and 5-24 present the anticipated Weekday AM/PM and Saturday Midday peak hour Year 2040 With ELSP Project Buildout traffic volumes, respectively, at the thirty (30) key study intersections. **Figures 5-25 and 5-26** present the Weekday and Saturday daily Year 2040 With ELSP Project Buildout daily traffic volumes, respectively, for the thirty-two (32) key study roadway segments.

Copies of the traffic model post-processing worksheets and a detailed description of the traffic volume derivation are contained in **Appendix C**. Please note that the post-processing methodology utilized in this report is consistent with SCAG requirements.


TABLE 5-1
LOCATION AND DESCRIPTION OF CUMULATIVE PROJECTS – PHASE I AND BUILDOUT DEVELOPMENT TOTALS¹²

| No. | Cumulative Project | Location | Year 2022 (Phase I) | Year 2040 (Buildout) | Development Total |
|-----|--|--|--|--|--|
| 1. | Diamond Sports Center Project | NWC of Pete Lehr Drive and Diamond Drive | 600,000 SF Indoor Sports Center | No Additional Development between Year 2022 and 2040 | 600,000 SF Indoor Sports Center |
| 2. | South Shore Phase I & II, Spyglass Ranch | North of Camino Del Norte and Main Street | No Development Anticipated to be Complete by Year 2022 | 1,600 Single-Family DU | 1,600 Single-Family DU |
| 3. | Canyon Hills | Along Railroad Canyon Road, between I-15 and I-215 | 456 DU Condominiums | No Additional Development between Year 2022 and 2040 | 456 Condominium DU |
| 4. | Alberhill Villages | South of the I-15 freeway and west of Lake Street | No Development Anticipated to be Complete by Year 2022 | 50% Assumed to be Complete | 8,024 Residential DU, 1,335,800 SF Retail/Medical/Office, 974,500 SF Retail/Service Uses, 6,000 Student University, 850 Student Elementary School, 39.6 Acre Park, 45.9 Acre Sports Park |
| 5. | North Tuscany | North of Summerhill Drive and Ponte Russo | No Development Anticipated to be Complete by Year 2022 | 807 Single-Family DU | 807 Single-Family DU |
| 6. | Terracina Residential | South of Collier Avenue and east of Terra Cotta Road | 452 Single-Family Residential | No Additional Development between Year 2022 and 2040 | 452 Single-Family Residential |
| 7. | Artisan Alley | NEC of Diamond Drive and Malaga Road | 95,000 SF Commercial, 1 live-work DU, 130-Room Hotel | No Additional Development between Year 2022 and 2040 | 95,000 SF Commercial, 1 live-work DU, 130-Room Hotel |
| 8. | Spring Meadow Ranch | SEC of Sunset Avenue and Keller Road | No Development Anticipated to be Complete by Year 2022 | 1,192 Single-Family DU | 1,192 Single-Family DU |

Notes:

- SF = Square-Feet
- DU = Dwelling Units


¹² Source: *City of Lake Elsinore*.



KEY

EXISTING WITH ELSP PROJECT BUILDOUT
WEEKDAY AM PEAK HOUR TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE

LINSCOTT
LAW &
GREENSPAN
engineers



LINSCOTT
LAW &
GREENSPAN
engineers

N
NO SCALE

KEY
= STUDY INTERSECTION

FIGURE 5-2

EXISTING WITH ELSPI PROJECT BUILDOUT
WEEKDAY PM PEAK HOUR TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE




FIGURE 5-3

EXISTING WITH ELSPI PROJECT BUILDOUT
SATURDAY MIDDAY PEAK HOUR TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE






FIGURE 5-4

EXISTING WITH ELSP PROJECT BUILDOUT
WEEKDAY DAILY TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE





n:\3500\2143544 - east lake specific plan eir, lake elsinore\6 - dwg\3544f5-6.dwg LDP 11:48:59 02-01-2017 mempin

FIGURE 5-6


**LOCATION OF CUMULATIVE PROJECTS
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE**


**LINGCOTT
LAW &
GREENSPAN**
engineers




NO SCALE

KEY
= CUMULATIVE PROJECT LOCATION










FIGURE 5-10


YEAR 2022 WITHOUT ELSP PROJECT PHASE I
WEEKDAY DAILY TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE


LINSCHOTT
LAW &
GREENSPAN

NO SCALE

KEY
= STUDY ROADWAY SEGMENT

n:\3500\2143544 - east lake specific plan eir, lake elsinore\6 - dwg\3544f5-10.dwg LDP 08:50:02 02-01-2017 mempin









FIGURE 5-13

YEAR 2022 WITH ELSP PROJECT PHASE I
WEEKDAY PM PEAK HOUR TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE






FIGURE 5-15

YEAR 2022 WITH ELSP PROJECT PHASE I
WEEKDAY DAILY TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE






FIGURE 5-16

YEAR 2022 WITH ELSP PROJECT PHASE I
SATURDAY DAILY TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE












FIGURE 5-19

YEAR 2040 WITH ADOPTED SPECIFIC PLAN
SATURDAY MIDDAY PEAK HOUR TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE







LINSCOTT
LAW &
GREENSPAN
engineering



NO SCALE

KEY
= STUDY INTERSECTION

FIGURE 5-22

YEAR 2040 WITH ELSPI PROJECT BUILDOUT
WEEKDAY AM PEAK HOUR TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE





FIGURE 5-23

YEAR 2040 WITH ELS Project Buildout
WEEKDAY PM PEAK HOUR TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE





KEY


FIGURE 5-24

YEAR 2040 WITH ELSP PROJECT BUILDOUT
SATURDAY MIDDAY PEAK HOUR TRAFFIC VOLUMES
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE

LINSCOTT
LAW &
GREENSPAN
→
en gIn eers







6.0 EXISTING CONDITIONS TRAFFIC IMPACT ANALYSIS

The existing conditions traffic analysis establishes the basis for the future forecasts for the Project. This analysis was based on existing intersection and roadway segment counts collected in May and December 2016. The existing conditions analysis reflects these counts as well as existing lane configurations for all analyzed intersections and roadway segments.

6.1 Existing Conditions Intersection Capacity Analysis

Table 6-1 summarizes the peak hour Level of Service results at the key study intersections for existing traffic conditions, without and with ELSP Project Buildout. The first column (1) of Delay/LOS values in *Table 6-1* presents a summary of Existing AM, PM and Saturday Midday peak hour traffic conditions. The second column (2) in *Table 6-1* presents forecast Existing With ELSP Project Buildout traffic conditions. The third column (3) of *Table 6-1* shows whether the traffic associated with the ELSP Project Buildout will have a significant impact based on the LOS standards and the significance impact criteria defined in this report. The fourth column (4) of *Table 6-1* presents the Level of Service with the implementation of traffic mitigation improvements, if necessary.

Planned improvements, which are discussed in more detail in *Section 9.0* of this report, have been assumed for the “With ELSP Project Buildout” scenario for the intersection listed below:

- 11. Mission Trail at Olive Street

6.1.1 Existing Traffic Conditions

Review of column (1) of *Table 6-1* indicates that for the Existing traffic conditions, two (2) of the key study intersections currently operate at unacceptable levels of service during the AM, PM and/or Saturday Midday peak hour when compared to the LOS standards defined in this report. The remaining key study intersections currently operate at acceptable levels of service during the AM, PM and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|--|------------------------------|------------|------------------------------|------------|----------------------------------|------------|
| | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> |
| 17. Orange Street at Bundy Canyon Road | 294.4 | F | 112.5 | F | 150.7 | F |
| 22. Stoneman Street at Grand Avenue | 41.7 | E | 38.3 | E | -- | -- |

6.1.2 Existing With East Lake Specific Plan Project Buildout Traffic Conditions

Review of column (2) of *Table 6-1* indicates that for the Existing With ELSP Project Buildout traffic conditions, six (6) key study intersections are forecast to operate at unacceptable levels of service during the AM, PM and/or Saturday Midday peak hours when compared to the LOS standards defined in this report. The remaining key study intersections are forecast to operate at acceptable levels of service during the AM, PM and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|---|---------------------|------------|---------------------|------------|----------------------------------|------------|
| | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> |
| 5. Lucerne Street at Lakeshore Drive | 374.0 | F | 373.4 | F | 725.3 | F |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | -- | -- | -- | -- | 105.4 | F |
| 12. Mission Trail at Victorian Lane | -- | -- | 45.5 | E | 39.4 | E |
| 17. Orange Street at Bundy Canyon Road | 279.9 | F | 130.6 | F | 116.4 | F |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | 55.3 | E | -- | -- | -- | -- |
| 22. Stoneman Street at Grand Avenue | 66.2 | F | 56.9 | F | -- | -- |

Review of column (3) of *Table 6-1* indicates that six (6) key study intersections will have a significant impact under the Existing With ELS Project Buildout traffic conditions when compared to the LOS criteria defined in this report. However, as shown in column (4) of *Table 6-1*, the recommended improvements outlined in this report will offset the impact of the Existing With ELS Project Buildout traffic and bring the significantly impacted intersections to below Existing and/or acceptable conditions at five (5) of the six (6) impacted locations. It should be noted that key study intersection #6, Diamond Drive at Lakeshore Drive/Mission Trail, was mitigated to a feasible extent but does not lower the level of service enough in order to bring below Existing and/or acceptable conditions.

Appendix D contains the Delay/LOS calculation worksheets for the Existing Traffic Conditions.

TABLE 6-1
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY¹³

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Existing With ELSP Project Buildout Traffic Conditions | | (3) Significant Impact | (4) Existing With ELSP Project Buildout With Mitigation | |
|---|------------------------|-----------------|------------------------------------|-----|---|-----|---------------------------|--|-------------|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | | Yes/No | Delay (s/v) |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | D | Weekday AM | 37.1 | D | 37.5 | D | No | -- | -- |
| | | Weekday PM | 46.4 | D | 47.9 | D | No | -- | -- |
| | | Saturday Midday | 39.8 | D | 40.6 | D | No | -- | -- |
| 2. Railroad Canyon Road at I-15 Northbound Ramps | D | Weekday AM | 21.3 | C | 20.5 | C | No | -- | -- |
| | | Weekday PM | 19.8 | B | 20.0 | B | No | -- | -- |
| | | Saturday Midday | 24.1 | C | 23.9 | C | No | -- | -- |
| 3. Diamond Drive at I-15 Southbound Ramps | D | Weekday AM | 36.8 | D | 41.8 | D | No | -- | -- |
| | | Weekday PM | 27.0 | C | 25.0 | C | No | -- | -- |
| | | Saturday Midday | 28.2 | C | 27.5 | C | No | -- | -- |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | D | Weekday AM | 21.7 | C | 24.7 | C | No | -- | -- |
| | | Weekday PM | 20.6 | C | 22.3 | C | No | -- | -- |
| | | Saturday Midday | 21.4 | C | 26.6 | C | No | -- | -- |
| 5. Lucerne Street at Lakeshore Drive | D | Weekday AM | 12.3 | B | 374.0 | F | Yes | 23.3 | C |
| | | Weekday PM | 15.1 | C | 373.4 | F | Yes | 21.8 | C |
| | | Saturday Midday | 12.0 | B | 725.3 | F | Yes | 20.5 | C |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | E | Weekday AM | 36.5 | D | 46.7 | D | No | 46.8 | D |
| | | Weekday PM | 38.2 | D | 68.7 | E | No | 67.7 | E |
| | | Saturday Midday | 45.9 | D | 105.4 | F | Yes | 103.0 | F |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1* and *3-2* for the LOS definitions

¹³ Appendix D contains the Delay/LOS calculation worksheets for all study intersections.

TABLE 6-1 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY¹⁴

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Existing With ELSP Project Buildout Traffic Conditions | | (3) Significant Impact | (4) Existing With ELSP Project Buildout With Mitigation | |
|-------------------------------------|------------------------|-----------------|------------------------------------|-----|---|-----|---------------------------|--|-------------|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | | Yes/No | Delay (s/v) |
| 7. Diamond Drive at Campbell Street | E | Weekday AM | 8.9 | A | 9.1 | A | No | -- | -- |
| | | Weekday PM | 9.2 | A | 9.7 | A | No | -- | -- |
| | | Saturday Midday | 10.1 | B | 11.3 | B | No | -- | -- |
| 8. Mission Trail at Campbell Street | E | Weekday AM | 17.5 | C | 17.7 | C | No | -- | -- |
| | | Weekday PM | 22.0 | C | 22.3 | C | No | -- | -- |
| | | Saturday Midday | 28.6 | D | 29.5 | D | No | -- | -- |
| 9. Diamond Drive at Malaga Road | E | Weekday AM | 9.9 | A | 15.1 | B | No | -- | -- |
| | | Weekday PM | 13.2 | B | 16.3 | B | No | -- | -- |
| | | Saturday Midday | 16.1 | B | 21.8 | C | No | -- | -- |
| 10. Mission Trail at Malaga Road | E | Weekday AM | 9.2 | A | 11.2 | B | No | -- | -- |
| | | Weekday PM | 14.1 | B | 30.6 | C | No | -- | -- |
| | | Saturday Midday | 15.7 | B | 17.9 | B | No | -- | -- |
| 11. Mission Trail at Olive Street | D | Weekday AM | 5.6 | A | 8.1 | A | No | -- | -- |
| | | Weekday PM | 6.8 | A | 10.8 | B | No | -- | -- |
| | | Saturday Midday | 7.2 | A | 11.5 | B | No | -- | -- |
| 12. Mission Trail at Victorian Lane | D | Weekday AM | 25.3 | D | 25.2 | D | No | 3.6 | A |
| | | Weekday PM | 27.9 | D | 45.5 | E | Yes | 5.2 | A |
| | | Saturday Midday | 26.4 | D | 39.4 | E | Yes | 4.5 | A |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1* and *3-2* for the LOS definitions

¹⁴ Appendix D contains the Delay/LOS calculation worksheets for all study intersections.

TABLE 6-1 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY¹⁵

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Existing With ELSP Project Buildout Traffic Conditions | | (3) Significant Impact | (4) Existing With ELSP Project Buildout With Mitigation | |
|--|------------------------|-----------------|------------------------------------|----------|---|----------|---------------------------|--|-------------|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | | Yes/No | Delay (s/v) |
| 13. Mission Trail at Lemon Street | D | Weekday AM | 8.0 | A | 8.4 | A | No | -- | -- |
| | | Weekday PM | 8.0 | A | 8.7 | A | No | -- | -- |
| | | Saturday Midday | 7.7 | A | 8.3 | A | No | -- | -- |
| 14. Mission Trail at Corydon Road | D | Weekday AM | 19.9 | B | 22.5 | C | No | -- | -- |
| | | Weekday PM | 18.7 | B | 23.3 | C | No | -- | -- |
| | | Saturday Midday | 18.4 | B | 20.0 | C | No | -- | -- |
| 15. Corydon Road at Cereal Street | D | Weekday AM | 13.5 | B | 22.7 | C | No | -- | -- |
| | | Weekday PM | 15.2 | C | 24.4 | C | No | -- | -- |
| | | Saturday Midday | 13.9 | B | 21.0 | C | No | -- | -- |
| 16. Mission Trail at Bundy Canyon Road | D | Weekday AM | 18.9 | B | 21.5 | C | No | -- | -- |
| | | Weekday PM | 24.4 | C | 24.3 | C | No | -- | -- |
| | | Saturday Midday | 20.5 | C | 21.3 | C | No | -- | -- |
| 17. Orange Street at Bundy Canyon Road | D | Weekday AM | 294.4 | F | 279.9 | F | Yes | 52.1 | D |
| | | Weekday PM | 112.5 | F | 130.6 | F | Yes | 25.5 | C |
| | | Saturday Midday | 150.7 | F | 116.4 | F | Yes | 26.4 | C |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | D | Weekday AM | 36.7 | D | 55.3 | E | Yes | 53.4 | D |
| | | Weekday PM | 23.0 | C | 23.4 | C | No | 22.1 | C |
| | | Saturday Midday | 19.8 | B | 19.5 | B | No | 19.0 | B |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1* and *3-2* for the LOS definitions

¹⁵ Appendix D contains the Delay/LOS calculation worksheets for all study intersections.

TABLE 6-1 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY¹⁶

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Existing With ELSP Project Buildout Traffic Conditions | | (3) Significant Impact | (4) Existing With ELSP Project Buildout With Mitigation | |
|--|------------------------|-----------------|---|----------|---|----------|---------------------------|--|-------------|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | | Yes/No | Delay (s/v) |
| 19. I-15 Northbound Ramps at Bundy Canyon Road | D | Weekday AM | 23.8 | C | 25.0 | C | No | -- | -- |
| | | Weekday PM | 24.4 | C | 25.3 | C | No | -- | -- |
| | | Saturday Midday | 20.8 | C | 22.1 | C | No | -- | -- |
| 20. Corydon Road at Palomar Street | D | Weekday AM | 16.4 | B | 17.4 | B | No | -- | -- |
| | | Weekday PM | 13.5 | B | 15.5 | B | No | -- | -- |
| | | Saturday Midday | 14.1 | B | 15.3 | B | No | -- | -- |
| 21. Mission Trail at Palomar Street | D | Weekday AM | 13.7 | B | 14.3 | B | No | -- | -- |
| | | Weekday PM | 12.6 | B | 13.4 | B | No | -- | -- |
| | | Saturday Midday | 11.0 | B | 11.1 | B | No | -- | -- |
| 22. Stoneman Street at Grand Avenue | D | Weekday AM | 41.7 | E | 66.2 | F | Yes | 6.9 | A |
| | | Weekday PM | 38.3 | E | 56.9 | F | Yes | 6.2 | A |
| | | Saturday Midday | 20.0 | C | 23.5 | C | No | 6.2 | A |
| 23. Corydon Road at Grand Avenue | D | Weekday AM | 13.8 | B | 13.1 | B | No | -- | -- |
| | | Weekday PM | 12.7 | B | 11.1 | B | No | -- | -- |
| | | Saturday Midday | 11.6 | B | 10.8 | B | No | -- | -- |
| 24. Grape Street at I-15 Northbound Ramps | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | | | | No | -- | -- |
| | | Weekday PM | Intersection Does Not Exist Under Existing Traffic Conditions | | | | No | -- | -- |
| | | Saturday Midday | Intersection Does Not Exist Under Existing Traffic Conditions | | | | No | -- | -- |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1* and *3-2* for the LOS definitions

¹⁶ Appendix D contains the Delay/LOS calculation worksheets for all study intersections.

TABLE 6-1 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY¹⁷

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Existing With ELSP Project Buildout Traffic Conditions | | (3) Significant Impact | (4) Existing With ELSP Project Buildout With Mitigation | |
|--|------------------------|-----------------|---|------|---|-----|---------------------------|--|-------------|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | | Yes/No | Delay (s/v) |
| 25. Diamond Drive at Olive Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 9.0 | A | No | No | -- | -- |
| | | Weekday PM | | 9.2 | A | No | | -- | -- |
| | | Saturday Midday | | 9.1 | A | No | | -- | -- |
| 26. "A" Street at Olive Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 3.5 | A | No | No | -- | -- |
| | | Weekday PM | | 3.7 | A | No | | -- | -- |
| | | Saturday Midday | | 3.8 | A | No | | -- | -- |
| 27. "A" Street at Victorian Lane | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 3.5 | A | No | No | -- | -- |
| | | Weekday PM | | 3.6 | A | No | | -- | -- |
| | | Saturday Midday | | 3.7 | A | No | | -- | -- |
| 28. "A" Street at Cereal Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 9.0 | A | No | No | -- | -- |
| | | Weekday PM | | 9.4 | A | No | | -- | -- |
| | | Saturday Midday | | 9.3 | A | No | | -- | -- |
| 29. Lucerne Street at Sylvester Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 12.5 | B | No | No | -- | -- |
| | | Weekday PM | | 15.1 | C | No | | -- | -- |
| | | Saturday Midday | | 14.0 | B | No | | -- | -- |
| 30. Stoneman Street at Cereal Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 23.0 | C | No | No | -- | -- |
| | | Weekday PM | | 9.2 | A | No | | -- | -- |
| | | Saturday Midday | | 24.1 | C | No | | -- | -- |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1* and *3-2* for the LOS definitions

¹⁷ Appendix D contains the Delay/LOS calculation worksheets for all study intersections.

6.2 Existing Conditions Roadway Segment Analysis

Table 6-2 summarizes the daily level of service results at the key study roadway segments during a “typical” Weekday and Saturday for the existing traffic conditions without and with the ELSP Project Buildout. The first column (1) of LOS E Capacity values in *Table 6-2* presents the daily roadway segment capacities from the *City of Lake Elsinore General Plan Update Draft Program EIR, dated August 2011*. The second column (2) lists the number of travel lanes and the third column (3) indicates the Existing daily traffic volumes, Volume to Capacity (V/C) ratio and Level of Service (LOS). The fourth column (4) in *Table 6-2* forecasts the Existing With ELSP Project Buildout traffic conditions. The fifth column (5) of *Table 6-2* presents the increase in the V/C ratio and indicates whether the roadway segment operates at an adverse level of service based on the LOS standards and the impact criteria defined in this report.

6.2.1 Existing Traffic Conditions

Review of column (3) of *Table 6-2* indicates that for the Existing traffic conditions, one (1) of the key study roadway segments currently operate at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway segments currently operate at acceptable levels of service on daily basis. The roadway segments operating at adverse levels of service are:

| <u>Key Roadway Segment</u> | <u>Weekday Daily</u> | | | <u>Saturday Daily</u> | | |
|--|----------------------|------------------|------------|-----------------------|------------------|------------|
| | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> |
| 17. Corydon Road, <i>between</i> Mission Trail and Cereal Street | 16,978 | 0.943 | E | -- | -- | -- |

6.2.2 Existing With East Lake Specific Plan Project Buildout Traffic Conditions

Review of column (4) of *Table 6-2* indicates that for the Existing With ELSP Project Buildout traffic conditions, two (2) key study roadway segments are forecast to operate at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway segments are forecast to operate at acceptable levels of service on a daily basis. The roadway segments operating at adverse levels of service are:

| <u>Key Roadway Segment</u> | <u>Weekday Daily</u> | | | <u>Saturday Daily</u> | | |
|---|----------------------|------------------|------------|-----------------------|------------------|------------|
| | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> |
| 17. Corydon Road, <i>between</i> Mission Trail and Cereal Street | 19,795 | 1.100 | F | 19,227 | 1.068 | F |
| 20. Bundy Canyon Road, <i>between</i> Mission Trail and I-15 SB Ramps | 11,968 | 0.921 | E | -- | -- | -- |

To determine if the ELSP Project Buildout creates a significant impact, these adverse roadway segments are further analyzed under peak hour conditions to determine if there are any peak hour deficiencies. As presented in **Table 6-3**, these study roadway segments are forecast to operate at LOS A during the AM, PM and Saturday Midday peak hours. As a result, the key study roadway segments are not significantly impacted by Existing With ELSP Project Buildout traffic and therefore no improvements are required.

TABLE 6-2
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Type of Arterial | LOS E Capacity ¹⁸ (VPD) | Lanes | Existing Traffic Conditions | | | Existing With ELSP Project Buildout Traffic Conditions | | | (5) Adverse Condition | |
|--|-------------|------------------|------------------------------------|-------|-----------------------------|-----------|-----|--|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | Weekday | Major | 34,100 | 4D | 20,281 | 0.595 | A | 20,406 | 0.598 | A | 0.003 | No |
| | Saturday | | | | 24,102 | 0.707 | C | 24,173 | 0.709 | C | 0.002 | No |
| 2. Railroad Canyon Road, <i>between Summerhill Drive/Grape Street and Lakeshore Drive/Mission Trail</i> | Weekday | Urban Arterial | 62,850 | 7D | 26,367 | 0.420 | A | 32,190 | 0.512 | A | 0.092 | No |
| | Saturday | | | | 26,682 | 0.425 | A | 33,186 | 0.528 | A | 0.103 | No |
| 3. Lucerne Street, <i>south of Lakeshore Drive</i> | Weekday | Collector | 13,000 | 2U | 71 | 0.005 | A | 8,967 | 0.690 | B | 0.685 | No |
| | Saturday | | | | 63 | 0.005 | A | 9,571 | 0.736 | C | 0.731 | No |
| 4. Casino Drive, <i>east of Diamond Drive</i> | Weekday | Major | 34,100 | 4D | 5,861 | 0.172 | A | 5,814 | 0.170 | A | -0.002 | No |
| | Saturday | | | | 5,468 | 0.160 | A | 5,423 | 0.159 | A | -0.001 | No |
| 5. Diamond Drive, <i>between Lakeshore Drive/Mission Trail and Campbell Street</i> | Weekday | Major | 34,100 | 4D | 4,924 | 0.144 | A | 6,716 | 0.197 | A | 0.053 | No |
| | Saturday | | | | 4,703 | 0.138 | A | 6,519 | 0.191 | A | 0.053 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

¹⁸ Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 6-2 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Type of Arterial | LOS E Capacity ¹⁹ (VPD) | Lanes | (3) Existing Traffic Conditions | | | (4) Existing With ELSP Project Buildout Traffic Conditions | | | (5) Adverse Condition | |
|---|-------------|------------------|------------------------------------|-------|---------------------------------|-----------|-----|--|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 6. Diamond Drive, between Campbell Street and Malaga Road | Weekday | Major | 34,100 | 4D | 3,671 | 0.108 | A | 5,131 | 0.150 | A | 0.042 | No |
| | Saturday | | | | 3,750 | 0.110 | A | 5,293 | 0.155 | A | 0.045 | No |
| 7. Mission Trail, between Diamond Drive and Campbell Street | Weekday | Major | 34,100 | 4D | 19,238 | 0.564 | A | 19,240 | 0.564 | A | 0.000 | No |
| | Saturday | | | | 16,742 | 0.491 | A | 17,775 | 0.521 | A | 0.030 | No |
| 8. Mission Trail, between Campbell Street and Malaga Road | Weekday | Major | 34,100 | 4D | 16,132 | 0.473 | A | 16,743 | 0.491 | A | 0.018 | No |
| | Saturday | | | | 16,713 | 0.490 | A | 17,550 | 0.515 | A | 0.025 | No |
| 9. Malaga Road, between Diamond Drive and Mission Trail | Weekday | Major | 34,100 | 4D | 1,216 | 0.036 | A | 2,003 | 0.059 | A | 0.023 | No |
| | Saturday | | | | 1,238 | 0.036 | A | 2,089 | 0.061 | A | 0.025 | No |
| 10. Malaga Road, east of Mission Trail | Weekday | Collector | 13,000 | 2U | 2,740 | 0.211 | A | 2,740 | 0.211 | A | 0.000 | No |
| | Saturday | | | | 2,934 | 0.226 | A | 2,934 | 0.226 | A | 0.000 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold "V/C"/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

¹⁹ Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 6-2 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Type of Arterial | LOS E Capacity ²⁰ (VPD) | Lanes | (3) Existing Traffic Conditions | | | (4) Existing With ELSP Project Buildout Traffic Conditions | | | (5) Adverse Condition | |
|--|-------------|------------------|------------------------------------|-------|---------------------------------|-----------|-----|--|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 11. Diamond Drive, <i>north of Summerly Place</i> | Weekday | Major | 34,100 | 4D | 703 | 0.021 | A | 2,007 | 0.059 | A | 0.038 | No |
| | Saturday | | | | 636 | 0.019 | A | 1,848 | 0.054 | A | 0.035 | No |
| 12. Mission Trail, <i>between Malaga Road and Olive Street</i> | Weekday | Major | 34,100 | 4D | 16,593 | 0.487 | A | 17,201 | 0.504 | A | 0.017 | No |
| | Saturday | | | | 16,042 | 0.470 | A | 17,184 | 0.504 | A | 0.034 | No |
| 13. Olive Street, <i>between Mission Trail and Grape Street</i> | Weekday | Collector | 13,000 | 2U | 2,393 | 0.184 | A | 2,248 | 0.173 | A | -0.011 | No |
| | Saturday | | | | 2,312 | 0.178 | A | 2,191 | 0.169 | A | -0.009 | No |
| 14. Mission Trail, <i>between Olive Street and Victorian Lane</i> | Weekday | Secondary | 25,900 | 4U | 17,898 | 0.691 | B | 17,068 | 0.659 | B | -0.032 | No |
| | Saturday | | | | 16,952 | 0.655 | B | 16,616 | 0.642 | B | -0.013 | No |
| 15. Mission Trail, <i>between Victorian Lane and Lemon Street</i> | Weekday | Secondary | 25,900 | 4U | 18,146 | 0.701 | C | 17,891 | 0.691 | B | -0.010 | No |
| | Saturday | | | | 17,176 | 0.663 | B | 17,467 | 0.674 | B | 0.011 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

²⁰ Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 6-2 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Type of Arterial | LOS E Capacity ²¹ (VPD) | Lanes | (3) Existing Traffic Conditions | | | (4) Existing With ELSP Project Buildout Traffic Conditions | | | (5) Adverse Condition | |
|--|-------------|-------------------|------------------------------------|-------|---------------------------------|--------------|-----|--|--------------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 16. Lemon Street, between Mission Trail and Grape Street | Weekday | Collector | 13,000 | 2U | 3,253 | 0.250 | A | 3,497 | 0.269 | A | 0.019 | No |
| | Saturday | | | | 3,007 | 0.231 | A | 3,293 | 0.253 | A | 0.022 | No |
| 17. Corydon Road, between Mission Trail and Cereal Street | Weekday | Divided Collector | 18,000 | 2D | 16,978 | 0.943 | E | 19,795 | 1.100 | F | 0.157 | Yes |
| | Saturday | | | | 15,639 | 0.869 | D | 19,227 | 1.068 | F | 0.199 | Yes |
| 18. Cereal Street, west of Corydon Road | Weekday | Collector | 13,000 | 2U | 445 | 0.034 | A | 3,389 | 0.261 | A | 0.227 | No |
| | Saturday | | | | 711 | 0.055 | A | 3,890 | 0.299 | A | 0.244 | No |
| 19. Mission Trail, between Corydon Road and Bundy Canyon Road | Weekday | Major | 34,100 | 4D | 13,919 | 0.408 | A | 17,102 | 0.502 | A | 0.094 | No |
| | Saturday | | | | 12,283 | 0.360 | A | 15,932 | 0.467 | A | 0.107 | No |
| 20. Bundy Canyon Road, between Mission Trail and I-15 Southbound Ramps | Weekday | Collector | 13,000 | 2U | 9,781 | 0.752 | C | 11,968 | 0.921 | E | 0.169 | Yes |
| | Saturday | | | | 9,107 | 0.701 | C | 11,584 | 0.891 | D | 0.190 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

²¹ Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 6-2 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Type of Arterial | LOS E Capacity ²² (VPD) | Lanes | (3) Existing Traffic Conditions | | | (4) Existing With ELSP Project Buildout Traffic Conditions | | | (5) Adverse Condition | |
|--|-------------|-------------------|------------------------------------|-------|---------------------------------|-----------|-----|--|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 21. Corydon Road, <i>between Cereal Street and Palomar Street</i> | Weekday | Divided Collector | 18,000 | 2D | 15,630 | 0.868 | D | 16,075 | 0.893 | D | 0.025 | No |
| | Saturday | | | | 14,481 | 0.805 | D | 15,571 | 0.865 | D | 0.060 | No |
| 22. Mission Trail, <i>between Bundy Canyon Road and Palomar Street</i> | Weekday | Collector | 13,000 | 2U | 8,034 | 0.618 | B | 8,749 | 0.673 | B | 0.055 | No |
| | Saturday | | | | 6,887 | 0.530 | A | 7,747 | 0.596 | A | 0.066 | No |
| 23. Palomar Street, <i>between Corydon Road and Mission Trail</i> | Weekday | Collector | 13,000 | 2U | 3,221 | 0.248 | A | 3,220 | 0.248 | A | 0.000 | No |
| | Saturday | | | | 2,744 | 0.211 | A | 2,954 | 0.227 | A | 0.016 | No |
| 24. Stoneman Street, <i>north of Grand Avenue</i> | Weekday | Collector | 13,000 | 2U | 760 | 0.058 | A | 2,536 | 0.195 | A | 0.137 | No |
| | Saturday | | | | 724 | 0.056 | A | 2,556 | 0.197 | A | 0.141 | No |
| 25. Skylark Drive, <i>north of Grand Avenue</i> | Weekday | Collector | 13,000 | 2U | 220 | 0.017 | A | 474 | 0.036 | A | 0.019 | No |
| | Saturday | | | | 237 | 0.018 | A | 511 | 0.039 | A | 0.021 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

²² Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 6-2 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Type of Arterial | LOS E Capacity ²³ (VPD) | Lanes | (3) Existing Traffic Conditions | | | (4) Existing With ELSP Project Buildout Traffic Conditions | | | (5) Adverse Condition | |
|--|-------------|-------------------|------------------------------------|-------|--|-----------|-----|--|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 26. Corydon Road, between Palomar Street and Grand Avenue | Weekday | Divided Collector | 18,000 | 2D | 11,849 | 0.658 | B | 9,559 | 0.531 | A | -0.127 | No |
| | Saturday | | | | 10,999 | 0.611 | B | 8,940 | 0.497 | A | -0.114 | No |
| 27. Sylvester Street, between Lucerne Street and Diamond Drive | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 1,635 | 0.048 | A | 0.048 | No |
| | Saturday | | | | Segment Does Not Exist Under Existing Traffic Conditions | | | 1,759 | 0.052 | A | 0.052 | No |
| 28. Lucerne Street, between Sylvester Street and Cereal Street | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 9,814 | 0.288 | A | 0.288 | No |
| | Saturday | | | | Segment Does Not Exist Under Existing Traffic Conditions | | | 10,506 | 0.308 | A | 0.308 | No |
| 29. Cereal Street, between Lucerne Street and Stoneman Street | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 4,399 | 0.129 | A | 0.129 | No |
| | Saturday | | | | Segment Does Not Exist Under Existing Traffic Conditions | | | 4,670 | 0.137 | A | 0.137 | No |
| 30. Cereal Street, between Stoneman Street and Diamond Drive | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 5,316 | 0.156 | A | 0.156 | No |
| | Saturday | | | | Segment Does Not Exist Under Existing Traffic Conditions | | | 5,426 | 0.159 | A | 0.159 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

²³ Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 6-2 (CONTINUED)
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Type of Arterial | LOS E Capacity ²⁴ (VPD) | Lanes | (3) Existing Traffic Conditions | | | (4) Existing With ELSP Project Buildout Traffic Conditions | | | (5) Adverse Condition | |
|---|-------------|------------------|------------------------------------|-------|--|-----------|-----|--|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 31. Diamond Drive, between Olive Street and Cereal Street | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 1,662 | 0.049 | A | 0.049 | No |
| | Saturday | | | | | | | 1,574 | 0.046 | A | 0.046 | No |
| 32. Bundy Canyon Road, between Corydon Road and Mission Trail | Weekday | | | | Segment Does Not Exist Under Existing and Existing With ELSP Project Buildout Traffic Conditions | | | | | | -- | -- |
| | Saturday | | | | | | | | | | -- | |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

²⁴ Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 6-3
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Type of Arterial | Approach | Time Period | Link Capacity (VPHPL) | Lanes | Total Link Capacity (VPH) | (4) Existing With ELSP Project Buildout Traffic Conditions | | |
|---|------------------|------------|-----------------|-----------------------|-------|---------------------------|--|-----------|-----|
| | | | | | | | Peak Hour Volume | V/C Ratio | LOS |
| 17. Corydon Road, <i>between Mission Trail and Cereal Street</i> | Divided Arterial | Northbound | Weekday AM | 1,600 | 1 | 1600 | 848 | 0.530 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 734 | 0.459 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 746 | 0.466 | A |
| | Southbound | | Weekday AM | 1,600 | 1 | 1600 | 507 | 0.317 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 853 | 0.533 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 653 | 0.408 | A |
| 20. Bundy Canyon Road, <i>between Mission Trail and I-15 Southbound Ramps</i> | Collector | Eastbound | Weekday AM | 1,600 | 1 | 1600 | 570 | 0.356 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 553 | 0.346 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 481 | 0.301 | A |
| | Westbound | | Weekday AM | 1,600 | 1 | 1600 | 363 | 0.227 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 559 | 0.349 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 421 | 0.263 | A |

Notes:

- VPHPL = Vehicles Per Hour Per Lane
- VPH = Vehicles Per Hour
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions

7.0 YEAR 2022 CONDITIONS TRAFFIC IMPACT ANALYSIS

The relative impacts of the added ELSP Project Phase I traffic volumes generated by proposed ELSP Project Phase I during the AM peak hour, PM peak hour, Saturday Midday and Daily conditions was evaluated based on analysis of future Year 2022 operating conditions at twenty-seven (27) key study intersections (three (3) intersections do not exist under Year 2022 traffic conditions) and thirty-two (32) key roadway segments, without and with the proposed ELSP Project Phase I. The previously discussed capacity analysis procedures were utilized to investigate the future Delay/V/C relationships and service level characteristics at each study intersection and roadway segment. The significance of the potential impacts of the ELSP Project Phase I at each key intersection and roadway segment was then evaluated using the traffic impact criteria mentioned in this report.

7.1 Year 2022 Conditions Intersection Capacity Analysis

Table 7-1 summarizes the AM, PM and Saturday Midday peak hour Level of Service results at the key study intersections for the Year 2022 traffic conditions. The first column (1) of Delay/LOS values in *Table 7-1* presents a summary of existing AM, PM and Saturday Midday peak hour traffic conditions (which were also presented in *Table 6-1*). The second column (2) presents forecast Year 2022 Without ELSP Project Phase I traffic conditions and the third column (3) identifies forecast Year 2022 With ELSP Project Phase I traffic conditions. The fourth column (4) indicates whether the traffic associated with the ELSP Project Phase I will have a significant impact based on the significant impact criteria mentioned in this report. The fifth column (5) presents the resultant level of service with the inclusion of recommended improvements, where needed, to achieve an acceptable level of service.

Planned improvements, which are discussed in more detail in *Section 9.0* of this report, have been assumed for the “Year 2022 Without and With ELSP Project Phase I” scenarios for the intersections listed below:

- 1. Railroad Canyon Road at Summerhill Road/Grape Street
- 2. Railroad Canyon Road at I-15 NB Ramps
- 3. Diamond Drive at I-15 SB Ramps
- 5. Lucerne Street at Lakeshore Drive
- 11. Mission Trail at Olive Street
- 12. Mission Trail at Victorian Lane
- 15. Corydon Road at Cereal Street
- 16. Mission Trail at Bundy Canyon Road
- 24. Grape Street at I-15 Northbound Ramps
- 25. Diamond Drive at Olive Street
- 26. “A” Street at Olive Street
- 27. “A” Street at Victorian Lane
- 28. “A” Street at Cereal Street

7.1.1 Year 2022 Without East Lake Specific Plan Project Phase I Traffic Conditions

Review of column (2) of *Table 7-1* indicates that for the Year 2022 Without ELSP Project Phase I traffic conditions, nine (9) key study intersections are forecast to operate at an unacceptable level of service during the AM, PM and/or Saturday Midday peak hour when compared to the LOS standards defined in this report. The remaining key study intersections are forecast to operate at acceptable levels of service during the AM, PM and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|---|------------------------------|------------|------------------------------|------------|----------------------------------|------------|
| | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | 64.3 | E | 165.7 | F | 341.4 | F |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | -- | -- | -- | -- | 111.2 | F |
| 7. Diamond Drive at Campbell Street | -- | -- | -- | -- | 124.9 | F |
| 8. Mission Trail at Campbell Street | -- | -- | -- | -- | 47.6 | E |
| 9. Diamond Drive at Malaga Road | -- | -- | -- | -- | 272.0 | F |
| 17. Orange Street at Bundy Canyon Road | 290.7 | F | 192.9 | F | 290.1 | F |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | -- | -- | -- | -- | 64.6 | E |
| 22. Stoneman Street at Grand Avenue | 336.6 | F | 419.2 | F | -- | -- |
| 24. Grape Street at I-15 Northbound Ramps | -- | -- | -- | -- | 253.5 | F |

7.1.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

Review of column (3) of *Table 7-1* indicates that for the Year 2022 With ELSP Project Phase I traffic conditions, eleven (11) key study intersections are forecast to operate at unacceptable levels of service during the AM, PM and/or Saturday Midday peak hours when compared to the LOS standards defined in this report. The remaining key study intersections are forecast to operate at acceptable levels of service during the AM, PM and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|---|------------------------------|------------|------------------------------|------------|----------------------------------|------------|
| | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | 80.5 | F | 174.7 | F | 335.0 | F |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | -- | -- | -- | -- | 84.0 | F |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | -- | -- | 84.8 | F | 197.0 | F |
| 7. Diamond Drive at Campbell Street | -- | -- | -- | -- | 626.1 | F |
| 8. Mission Trail at Campbell Street | -- | -- | -- | -- | 76.5 | F |
| 9. Diamond Drive at Malaga Road | -- | -- | -- | -- | 322.6 | F |
| 15. Corydon Road at Cereal Street | 55.7 | E | -- | -- | -- | -- |
| 17. Orange Street at Bundy Canyon Road | 288.1 | F | 168.8 | F | 331.3 | F |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | 65.8 | E | -- | -- | 77.7 | E |

| | | | | | | |
|---|-------|----|-------|----|-------|----|
| 22. Stoneman Street at Grand Avenue | 442.0 | F | 664.7 | F | -- | -- |
| 24. Grape Street at I-15 Northbound Ramps | -- | -- | -- | -- | 257.1 | F |

Review of column (4) of *Table 7-1* indicates that eleven (11) key study intersections will have a significant impact under the Year 2022 With ELSP Project Phase I traffic conditions when compared to the LOS criteria defined in this report. However, as shown in column (5) of *Table 7-1*, the recommended improvements outlined in this report will offset the impact of the ELSP Project Phase I traffic and bring the significantly impacted intersections to pre-Project and/or acceptable conditions at nine (9) of the eleven (11) impacted locations. It should be noted that key study intersections #1, Railroad Canyon Road at Summerhill Lane/Grape Street, and #6, Diamond Drive at Lakeshore Drive/Mission Trail, were mitigated to a feasible extent but do not lower the level of service to acceptable conditions. It should also be noted that the mitigation for key study intersection #4, Diamond Drive at Casino Drive/Auto Center Drive, is infeasible due to the surrounding parcels preventing the additional needed right-of-way.

Appendix E contains the Delay/LOS calculation worksheets for the Year 2022 Traffic Conditions.

TABLE 7-1
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Year 2022 Without ELSP Project Phase I Traffic Conditions | | (3) Year 2022 With ELSP Project Phase I Traffic Conditions | | (4) Significant Impact | (5) Year 2022 With ELSP Project Phase I With Mitigation | |
|---|------------------------|-----------------|------------------------------------|-----|---|-----|---|-----|---------------------------|--|-----------------|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | | Delay (s/v) | LOS |
| | | | | | | | | | | Yes/No | |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | D | Weekday AM | 37.1 | D | 64.3 | E | 80.5 | F | Yes | 42.9 | D |
| | | Weekday PM | 46.4 | D | 165.7 | F | 174.7 | F | Yes | 59.2 | E |
| | | Saturday Midday | 39.8 | D | 341.4 | F | 335.0 | F | Yes | 43.9 | D |
| 2. Railroad Canyon Road at I-15 Northbound Ramps | D | Weekday AM | 21.3 | C | Intersection Does Not Exist Under Year 2022 Traffic Conditions Per City's Preferred Alternative Two | | | | No | -- | -- |
| | | Weekday PM | 19.8 | B | | | | | No | -- | -- |
| | | Saturday Midday | 24.1 | C | | | | | No | -- | -- |
| 3. Diamond Drive at I-15 Southbound Ramps | D | Weekday AM | 36.8 | D | 24.7 | C | 24.0 | C | No | -- | -- |
| | | Weekday PM | 27.0 | C | 24.2 | C | 23.5 | C | No | -- | -- |
| | | Saturday Midday | 28.2 | C | 29.1 | C | 35.7 | D | No | -- | -- |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | D | Weekday AM | 21.7 | C | 25.7 | C | 38.8 | D | No | 36.5 ²⁵ | D |
| | | Weekday PM | 20.6 | C | 26.4 | C | 51.5 | D | No | 34.6 | C |
| | | Saturday Midday | 21.4 | C | 37.4 | D | 84.0 | F | Yes | 46.8 | D |
| 5. Lucerne Street at Lakeshore Drive | D | Weekday AM | 12.3 | B | 11.4 | B | 13.5 | B | No | -- | -- |
| | | Weekday PM | 15.1 | C | 13.8 | B | 18.5 | C | No | -- | -- |
| | | Saturday Midday | 12.0 | B | 12.2 | B | 14.3 | B | No | -- | -- |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | E | Weekday AM | 36.5 | D | 41.1 | D | 48.7 | D | No | 43.7 | D |
| | | Weekday PM | 38.2 | D | 48.5 | D | 84.8 | F | Yes | 79.4 | E |
| | | Saturday Midday | 45.9 | D | 111.2 | F | 197.0 | F | Yes | 117.3 | F ²⁶ |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1 and 3-2* for the LOS definitions

²⁵ It should be noted that the mitigation is infeasible due to the surrounding parcels preventing the additional needed right-of-way and the mitigated LOS/Delay is shown only for informational purposes.

²⁶ Volumes have been rerouted due to the recommended improvement at the intersection of Diamond Drive at Campbell Street during the Saturday Midday peak hour.

TABLE 7-1 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) | | (2) | | (3) | | (4) Significant Impact | (5) | | |
|-------------------------------------|------------------------|-----------------|-----------------------------|-----|---|----------|--|----------|------------------------|---|-----------------|-----|
| | | | Existing Traffic Conditions | | Year 2022 Without ELSP Project Phase I Traffic Conditions | | Year 2022 With ELSP Project Phase I Traffic Conditions | | | Year 2022 With ELSP Project Phase I With Mitigation | | |
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | | Yes/No | Delay (s/v) | LOS |
| 7. Diamond Drive at Campbell Street | E | Weekday AM | 8.9 | A | 9.0 | A | 11.4 | B | No | -- | -- | |
| | | Weekday PM | 9.2 | A | 10.1 | B | 12.8 | B | No | -- | -- | |
| | | Saturday Midday | 10.1 | B | 124.9 | F | 626.1 | F | Yes | 18.3 | C ²⁷ | |
| 8. Mission Trail at Campbell Street | E | Weekday AM | 17.5 | C | 19.8 | C | 23.7 | C | No | 3.5 | A | |
| | | Weekday PM | 22.0 | C | 27.1 | D | 39.9 | E | No | 5.6 | A | |
| | | Saturday Midday | 28.6 | D | 47.6 | E | 76.5 | F | Yes | 6.7 | A ²⁸ | |
| 9. Diamond Drive at Malaga Road | E | Weekday AM | 9.9 | A | 12.9 | B | 38.2 | D | No | 31.0 | C | |
| | | Weekday PM | 13.2 | B | 20.7 | C | 22.7 | C | No | 19.7 | B | |
| | | Saturday Midday | 16.1 | B | 272.0 | F | 322.6 | F | Yes | 43.7 | D ²⁸ | |
| 10. Mission Trail at Malaga Road | E | Weekday AM | 9.2 | A | 9.2 | A | 10.0 | A | No | -- | -- | |
| | | Weekday PM | 14.1 | B | 15.9 | B | 16.7 | B | No | -- | -- | |
| | | Saturday Midday | 15.7 | B | 57.5 | E | 72.9 | E | No | 75.3 | E ²⁸ | |
| 11. Mission Trail at Olive Street | D | Weekday AM | 5.6 | A | 8.7 | A | 9.0 | A | No | -- | -- | |
| | | Weekday PM | 6.8 | A | 10.6 | B | 11.2 | B | No | -- | -- | |
| | | Saturday Midday | 7.2 | A | 10.7 | B | 11.8 | B | No | -- | -- | |
| 12. Mission Trail at Victorian Lane | D | Weekday AM | 25.3 | D | 2.5 | A | 2.8 | A | No | -- | -- | |
| | | Weekday PM | 27.9 | D | 2.6 | A | 2.9 | A | No | -- | -- | |
| | | Saturday Midday | 26.4 | D | 2.8 | A | 3.4 | A | No | -- | -- | |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1* and *3-2* for the LOS definitions

²⁷ The recommended improvement at this location includes the restriction of the southbound left and westbound left movement during the Saturday Midday peak hour. Due to the acceptable LOS during the AM and PM peak hour, no restriction will be required during the weekday AM and PM peak hour.

²⁸ Volumes have been rerouted due to the recommended improvement at the intersection of Diamond Drive at Campbell Street during the Saturday Midday peak hour.

TABLE 7-1 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) | | (2) | | (3) | | (4) | (5) | | |
|--|------------------------|-----------------|-----------------------------|----------|---|----------|--|----------|------------|---|-------------|-----|
| | | | Existing Traffic Conditions | | Year 2022 Without ELSP Project Phase I Traffic Conditions | | Year 2022 With ELSP Project Phase I Traffic Conditions | | | Year 2022 With ELSP Project Phase I With Mitigation | | |
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | | Yes/No | Delay (s/v) | LOS |
| 13. Mission Trail at Lemon Street | D | Weekday AM | 8.0 | A | 7.4 | A | 7.6 | A | No | -- | -- | |
| | | Weekday PM | 8.0 | A | 7.1 | A | 7.4 | A | No | -- | -- | |
| | | Saturday Midday | 7.7 | A | 6.3 | A | 6.9 | A | No | -- | -- | |
| 14. Mission Trail at Corydon Road | D | Weekday AM | 19.9 | B | 18.3 | B | 18.6 | B | No | -- | -- | |
| | | Weekday PM | 18.7 | B | 15.6 | B | 15.9 | B | No | -- | -- | |
| | | Saturday Midday | 18.4 | B | 15.8 | B | 16.6 | B | No | -- | -- | |
| 15. Corydon Road at Cereal Street | D | Weekday AM | 13.5 | B | 21.2 | C | 55.7 | E | Yes | 29.0 | C | |
| | | Weekday PM | 15.2 | C | 24.7 | C | 46.1 | D | No | 32.7 | C | |
| | | Saturday Midday | 13.9 | B | 29.6 | C | 48.4 | D | No | 29.9 | C | |
| 16. Mission Trail at Bundy Canyon Road | D | Weekday AM | 18.9 | B | 29.7 | C | 32.2 | C | No | -- | -- | |
| | | Weekday PM | 24.4 | C | 33.1 | C | 35.1 | D | No | -- | -- | |
| | | Saturday Midday | 20.5 | C | 38.9 | D | 41.7 | D | No | -- | -- | |
| 17. Orange Street at Bundy Canyon Road | D | Weekday AM | 294.4 | F | 290.7 | F | 288.1 | F | Yes | 53.8 | D | |
| | | Weekday PM | 112.5 | F | 192.9 | F | 168.8 | F | Yes | 33.0 | C | |
| | | Saturday Midday | 150.7 | F | 290.1 | F | 331.3 | F | Yes | 39.9 | D | |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | D | Weekday AM | 36.7 | D | 44.7 | D | 65.8 | E | Yes | 28.5 | C | |
| | | Weekday PM | 23.0 | C | 24.4 | C | 29.6 | C | No | 20.8 | C | |
| | | Saturday Midday | 19.8 | B | 64.6 | E | 77.7 | E | Yes | 20.1 | C | |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1* and *3-2* for the LOS definitions

TABLE 7-1 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) | | (2) | | (3) | | (4) | (5) | | |
|--|------------------------|-----------------|---|----------|---|----------|--|----------|------------|---|-------------|-----|
| | | | Existing Traffic Conditions | | Year 2022 Without ELSP Project Phase I Traffic Conditions | | Year 2022 With ELSP Project Phase I Traffic Conditions | | | Year 2022 With ELSP Project Phase I With Mitigation | | |
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | | Yes/No | Delay (s/v) | LOS |
| 19. I-15 Northbound Ramps at Bundy Canyon Road | D | Weekday AM | 23.8 | C | 25.7 | C | 27.9 | C | No | -- | -- | |
| | | Weekday PM | 24.4 | C | 26.4 | C | 29.5 | C | No | -- | -- | |
| | | Saturday Midday | 20.8 | C | 23.0 | C | 24.7 | C | No | -- | -- | |
| 20. Corydon Road at Palomar Street | D | Weekday AM | 16.4 | B | 19.8 | B | 21.5 | C | No | -- | -- | |
| | | Weekday PM | 13.5 | B | 20.3 | C | 22.0 | C | No | -- | -- | |
| | | Saturday Midday | 14.1 | B | 17.5 | B | 20.4 | C | No | -- | -- | |
| 21. Mission Trail at Palomar Street | D | Weekday AM | 13.7 | B | 15.4 | C | 16.8 | C | No | -- | -- | |
| | | Weekday PM | 12.6 | B | 13.5 | B | 15.2 | C | No | -- | -- | |
| | | Saturday Midday | 11.0 | B | 12.0 | B | 12.8 | B | No | -- | -- | |
| 22. Stoneman Street at Grand Avenue | D | Weekday AM | 41.7 | E | 336.6 | F | 442.0 | F | Yes | 13.3 | B | |
| | | Weekday PM | 38.3 | E | 419.2 | F | 664.7 | F | Yes | 13.2 | B | |
| | | Saturday Midday | 20.0 | C | 29.2 | D | 35.0 | D | No | 7.4 | A | |
| 23. Corydon Road at Grand Avenue | D | Weekday AM | 13.8 | B | 15.0 | B | 15.8 | B | No | -- | -- | |
| | | Weekday PM | 12.7 | B | 14.8 | B | 18.9 | B | No | -- | -- | |
| | | Saturday Midday | 11.6 | B | 13.8 | B | 14.6 | B | No | -- | -- | |
| 24. Grape Street at I-15 Northbound Ramps | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | | 21.7 | C | 22.8 | C | No | 24.9 | C | |
| | | Weekday PM | Intersection Does Not Exist Under Existing Traffic Conditions | | 29.1 | C | 29.3 | C | No | 25.4 | C | |
| | | Saturday Midday | Intersection Does Not Exist Under Existing Traffic Conditions | | 253.5 | F | 257.1 | F | Yes | 26.7 | C | |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1 and 3-2* for the LOS definitions

TABLE 7-1 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) | | (2) | | (3) | | (4) | (5) | |
|--|------------------------|-----------------|---|-----|---|------|--|-----|--------|---|-----|
| | | | Existing Traffic Conditions | | Year 2022 Without ELSP Project Phase I Traffic Conditions | | Year 2022 With ELSP Project Phase I Traffic Conditions | | | Year 2022 With ELSP Project Phase I With Mitigation | |
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | Yes/No | Delay (s/v) | LOS |
| 25. Diamond Drive at Olive Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 8.6 | A | 8.8 | A | No | -- | -- | |
| | | Weekday PM | | 8.7 | A | 9.0 | A | No | -- | -- | |
| | | Saturday Midday | | 8.6 | A | 9.0 | A | No | -- | -- | |
| 26. "A" Street at Olive Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 3.3 | A | 3.4 | A | No | -- | -- | |
| | | Weekday PM | | 3.3 | A | 3.4 | A | No | -- | -- | |
| | | Saturday Midday | | 3.3 | A | 3.4 | A | No | -- | -- | |
| 27. "A" Street at Victorian Lane | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 3.3 | A | 3.3 | A | No | -- | -- | |
| | | Weekday PM | | 3.3 | A | 3.4 | A | No | -- | -- | |
| | | Saturday Midday | | 3.3 | A | 3.3 | A | No | -- | -- | |
| 28. "A" Street at Cereal Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | 8.7 | A | 10.1 | B | No | -- | -- | |
| | | Weekday PM | | 8.8 | A | 11.8 | B | No | -- | -- | |
| | | Saturday Midday | | 8.7 | A | 10.3 | B | No | -- | -- | |
| 29. Lucerne Street at Sylvester Street | D | Weekday AM | Intersection Does Not Exist Under Existing and Year 2022 Traffic Conditions | | | | | | -- | -- | -- |
| | | Weekday PM | | | | | | | -- | -- | -- |
| | | Saturday Midday | | | | | | | -- | -- | -- |
| 30. Stoneman Street at Cereal Street | D | Weekday AM | Intersection Does Not Exist Under Existing and Year 2022 Traffic Conditions | | | | | | -- | -- | -- |
| | | Weekday PM | | | | | | | -- | -- | -- |
| | | Saturday Midday | | | | | | | -- | -- | -- |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1 and 3-2* for the LOS definitions

7.2 Year 2022 Conditions Roadway Segment Analysis

Table 7-2 summarizes the daily level of service results at the thirty-two (32) key study roadway segments during a “typical” Weekday and Saturday for the Year 2022 traffic conditions. The first column (1) of LOS E Capacity values in *Table 7-2* presents the daily roadway segment capacities from the *City of Lake Elsinore General Plan Update Draft Program EIR, dated August 2011*. The second column (2) lists the number of travel lanes and the third column (3) indicates the Existing daily traffic volumes, Volume to Capacity (V/C) ratio and Level of Service (LOS) (which were also presented in *Table 6-2*). The fourth column (4) forecasts Year 2022 Without ELSP Project Phase I traffic conditions. The fifth column (5) in *Table 7-2* forecasts the Year 2022 With ELSP Project Phase I traffic conditions. The sixth column (6) of *Table 7-2* presents the increase in the V/C ratio and indicates whether the roadway segment operates at an adverse level of service based on the LOS standards and the impact criteria defined in this report.

Planned improvements, which are discussed in more detail in *Section 9.0* of this report, have been assumed for the “Year 2022 Without and With ELSP Project Phase I” scenarios for the roadway segments listed below:

- 3. Lucerne Street, south of Lakeshore Drive
- 18. Cereal Street, west of Corydon Road
- 32. Bundy Canyon Road, between Corydon Road and Mission Trail
- 27. Sylvester Street, between Lucerne Street and Diamond Drive
- 28. Lucerne Street, between Sylvester Street and Cereal Street
- 29. Cereal Street, between Lucerne Street and Stoneman Street
- 30. Cereal Street, between Stoneman Street and Diamond Drive
- 31. Diamond Drive, between Olive Street and Cereal Street

7.2.1 Year 2022 Without East Lake Specific Plan Project Phase I Traffic Conditions

Review of column (4) of *Table 7-2* indicates that for the Year 2022 Without ELSP Project Phase I traffic conditions, four (4) key study roadway segments are forecast to operate at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway segments are forecast to operate at acceptable levels of service on daily basis. The roadway segments operating at adverse levels of service are:

| Key Roadway Segment | Weekday Daily | | | Saturday Daily | | |
|---|----------------------|------------------|------------|-----------------------|------------------|------------|
| | Volume | V/C Ratio | LOS | Volume | V/C Ratio | LOS |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | 34,739 | 1.019 | F | 41,285 | 1.211 | F |
| 20. Bundy Canyon Road, between Mission Trail and I-15 SB Ramps | 15,480 | 1.191 | F | 14,390 | 1.107 | F |
| 21. Corydon Road, <i>between Cereal Street and Palomar Street</i> | 20,308 | 1.128 | F | 18,803 | 1.045 | F |
| 26. Corydon Road, <i>between Palomar Street and Grand Avenue</i> | 16,459 | 0.914 | E | -- | -- | -- |

7.2.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

Review of column (5) of *Table 7-2* indicates that for the Year 2022 With ELSP Project Phase I traffic conditions, six (6) key study roadway segments are forecast to operate at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway segments are forecast to operate at acceptable levels of service on a daily basis. The roadway segments operating at adverse levels of service are:

| <u>Key Roadway Segment</u> | <u>Weekday Daily</u> | | | <u>Saturday Daily</u> | | |
|---|----------------------|------------------|------------|-----------------------|------------------|------------|
| | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | 35,311 | 1.036 | F | 41,902 | 1.229 | F |
| 15. Mission Trail, <i>between Victorian Lane and Lemon Street</i> | 23,456 | 0.906 | E | -- | -- | -- |
| 17. Corydon Road, <i>between Mission Trail and Cereal Street</i> | 17,177 | 0.954 | E | -- | -- | -- |
| 20. Bundy Canyon Road, <i>between Mission Trail and I-15 SB Ramps</i> | 19,789 | 1.522 | F | 19,035 | 1.464 | F |
| 21. Corydon Road, <i>between Cereal Street and Palomar Street</i> | 23,915 | 1.329 | F | 22,691 | 1.261 | F |
| 26. Corydon Road, <i>between Palomar Street and Grand Avenue</i> | 17,681 | 0.982 | E | 16,582 | 0.921 | E |

To determine if the ELSP Project Phase I creates a significant impact, these adverse roadway segments are further analyzed under peak hour conditions to determine if there are any peak hour deficiencies. As presented in *Table 7-3*, these study roadway segments are forecast to operate at LOS D or better during the AM, PM and Saturday Midday peak hours. As a result, the key study roadway segments are not significantly impacted by Year 2022 With ELSP Project Phase I traffic and therefore no improvements are required.

TABLE 7-2
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Year 2022 Type of Arterial | (1) LOS E Capacity ²⁹ (VPD) | (2) Lanes | (3) Existing Traffic Conditions | | | (4) Year 2022 Without ELSP Project Phase I Traffic Conditions | | | (5) Year 2022 With ELSP Project Phase I Traffic Conditions | | | (6) Adverse Condition | |
|--|---------------------|----------------------------|--|-----------|---------------------------------|----------------|--------|---|------------------------------|--------|--|------------------------------|--------|------------------------------|------------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | Weekday Saturday | Major | 34,100 | 4D | 20,281 24,102 | 0.595 0.707 | A C | 34,739 41,285 | 1.019 1.211 | F F | 35,311 41,902 | 1.036 1.229 | F F | 0.017 0.018 | Yes Yes |
| 2. Railroad Canyon Road, <i>between Summerhill Drive/Grape Street and Lakeshore Drive/Mission Trail</i> | Weekday Saturday | Urban Arterial | 62,850 | 7D | 26,367 26,682 | 0.420 0.425 | A A | 17,049 19,699 | 0.271 0.313 | A A | 22,993 26,106 | 0.366 0.415 | A A | 0.095 0.102 | No No |
| 3. Lucerne Street, <i>south of Lakeshore Drive</i> | Weekday Saturday | Major | 34,100 | 4D | 71 63 | 0.005 0.005 | A A | 71 63 | 0.002 0.002 | A A | 71 63 | 0.002 0.002 | A A | 0.000 0.000 | No No |
| 4. Casino Drive, <i>east of Diamond Drive</i> | Weekday Saturday | Major | 34,100 | 4D | 5,861 5,468 | 0.172 0.160 | A A | 7,289 6,800 | 0.214 0.199 | A A | 7,293 6,804 | 0.214 0.200 | A A | 0.000 0.001 | No No |
| 5. Diamond Drive, <i>between Lakeshore Drive/Mission Trail and Campbell Street</i> | Weekday Saturday | Major | 34,100 | 4D | 4,924 4,703 | 0.144 0.138 | A A | 9,129 10,998 | 0.268 0.323 | A A | 17,371 19,882 | 0.509 0.583 | A A | 0.241 0.260 | No No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

²⁹ Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 7-2 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Year 2022 Type of Arterial | (1) LOS E Capacity ³⁰ (VPD) | (2) Lanes | (3) Existing Traffic Conditions | | | (4) Year 2022 Without ELSP Project Phase I Traffic Conditions | | | (5) Year 2022 With ELSP Project Phase I Traffic Conditions | | | (6) Adverse Condition | |
|--|-------------|----------------------------|--|-----------|---------------------------------|-----------|-----|---|-----------|-----|--|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 6. Diamond Drive, <i>between Campbell Street and Malaga Road</i> | Weekday | Major | 34,100 | 4D | 3,671 | 0.108 | A | 4,826 | 0.142 | A | 13,951 | 0.409 | A | 0.267 | No |
| | Saturday | | | | 3,750 | 0.110 | A | 4,887 | 0.143 | A | 14,723 | 0.432 | A | 0.289 | No |
| 7. Mission Trail, <i>between Diamond Drive and Campbell Street</i> | Weekday | Major | 34,100 | 4D | 19,238 | 0.564 | A | 20,603 | 0.604 | B | 23,182 | 0.680 | B | 0.076 | No |
| | Saturday | | | | 16,742 | 0.491 | A | 17,976 | 0.527 | A | 20,756 | 0.609 | B | 0.082 | No |
| 8. Mission Trail, <i>between Campbell Street and Malaga Road</i> | Weekday | Major | 34,100 | 4D | 16,132 | 0.473 | A | 18,252 | 0.535 | A | 21,103 | 0.619 | B | 0.084 | No |
| | Saturday | | | | 16,713 | 0.490 | A | 18,889 | 0.554 | A | 21,962 | 0.644 | B | 0.090 | No |
| 9. Malaga Road, <i>between Diamond Drive and Mission Trail</i> | Weekday | Major | 34,100 | 4D | 1,216 | 0.036 | A | 2,210 | 0.065 | A | 2,831 | 0.083 | A | 0.018 | No |
| | Saturday | | | | 1,238 | 0.036 | A | 2,213 | 0.065 | A | 2,882 | 0.085 | A | 0.020 | No |
| 10. Malaga Road, <i>east of Mission Trail</i> | Weekday | Collector | 13,000 | 2U | 2,740 | 0.211 | A | 2,745 | 0.211 | A | 2,751 | 0.212 | A | 0.001 | No |
| | Saturday | | | | 2,934 | 0.226 | A | 2,940 | 0.226 | A | 2,946 | 0.227 | A | 0.001 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

³⁰ Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 7-2 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Year 2022 Type of Arterial | (1) LOS E Capacity ³¹ (VPD) | (2) Lanes | (3) Existing Traffic Conditions | | | (4) Year 2022 Without ELSP Project Phase I Traffic Conditions | | | (5) Year 2022 With ELSP Project Phase I Traffic Conditions | | | (6) Adverse Condition | |
|--|---------------------|----------------------------|--|-----------|---------------------------------|-----------|-----|---|-----------|-----|--|--------------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 11. Diamond Drive, <i>north of Summerly Place</i> | Weekday Saturday | Major | 34,100 | 4D | 703 | 0.021 | A | 1,039 | 0.030 | A | 1,778 | 0.052 | A | 0.022 | No |
| | | | | | 636 | 0.019 | A | 927 | 0.027 | A | 1,724 | 0.051 | A | 0.024 | No |
| 12. Mission Trail, <i>between Malaga Road and Olive Street</i> | Weekday Saturday | Major | 34,100 | 4D | 16,593 | 0.487 | A | 18,750 | 0.550 | A | 21,521 | 0.631 | B | 0.081 | No |
| | | | | | 16,042 | 0.470 | A | 18,063 | 0.530 | A | 21,050 | 0.617 | B | 0.087 | No |
| 13. Olive Street, <i>between Mission Trail and Grape Street</i> | Weekday Saturday | Collector | 13,000 | 2U | 2,393 | 0.184 | A | 3,766 | 0.290 | A | 3,993 | 0.307 | A | 0.017 | No |
| | | | | | 2,312 | 0.178 | A | 3,639 | 0.280 | A | 3,884 | 0.299 | A | 0.019 | No |
| 14. Mission Trail, <i>between Olive Street and Victorian Lane</i> | Weekday Saturday | Secondary | 25,900 | 4U | 17,898 | 0.691 | B | 21,028 | 0.812 | D | 23,260 | 0.898 | D | 0.086 | No |
| | | | | | 16,952 | 0.655 | B | 19,862 | 0.767 | C | 22,268 | 0.860 | D | 0.093 | No |
| 15. Mission Trail, <i>between Victorian Lane and Lemon Street</i> | Weekday Saturday | Secondary | 25,900 | 4U | 18,146 | 0.701 | C | 21,207 | 0.819 | D | 23,456 | 0.906 | E | 0.087 | Yes |
| | | | | | 17,176 | 0.663 | B | 20,020 | 0.773 | C | 22,444 | 0.867 | D | 0.094 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

³¹ Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 7-2 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Year 2022 Type of Arterial | (1) LOS E Capacity ³² (VPD) | (2) Lanes | (3) Existing Traffic Conditions | | | (4) Year 2022 Without ELSP Project Phase I Traffic Conditions | | | (5) Year 2022 With ELSP Project Phase I Traffic Conditions | | | (6) Adverse Condition | |
|--|------------------|----------------------------|--|-----------|---------------------------------|--------------|-----|---|--------------|-----|--|--------------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 16. Lemon Street, between Mission Trail and Grape Street | Weekday Saturday | Collector | 13,000 | 2U | 3,253 | 0.250 | A | 3,033 | 0.233 | A | 3,342 | 0.257 | A | 0.024 | No |
| | | | | | 3,007 | 0.231 | A | 2,803 | 0.216 | A | 3,136 | 0.241 | A | 0.025 | No |
| 17. Corydon Road, between Mission Trail and Cereal Street | Weekday Saturday | Divided Collector | 18,000 | 2D | 16,978 | 0.943 | E | 15,074 | 0.837 | D | 17,177 | 0.954 | E | 0.117 | Yes |
| | | | | | 15,639 | 0.869 | D | 13,872 | 0.771 | C | 16,139 | 0.897 | D | 0.126 | No |
| 18. Cereal Street, west of Corydon Road | Weekday Saturday | Major | 34,100 | 4D | 445 | 0.034 | A | 918 | 0.027 | A | 6,591 | 0.193 | A | 0.166 | No |
| | | | | | 711 | 0.055 | A | 1,466 | 0.043 | A | 7,581 | 0.222 | A | 0.179 | No |
| 19. Mission Trail, between Corydon Road and Bundy Canyon Road | Weekday Saturday | Major | 34,100 | 4D | 13,919 | 0.408 | A | 14,576 | 0.427 | A | 15,196 | 0.446 | A | 0.019 | No |
| | | | | | 12,283 | 0.360 | A | 12,848 | 0.377 | A | 13,516 | 0.396 | A | 0.019 | No |
| 20. Bundy Canyon Road, between Mission Trail and I-15 Southbound Ramps | Weekday Saturday | Collector | 13,000 | 2U | 9,781 | 0.752 | C | 15,480 | 1.191 | F | 19,789 | 1.522 | F | 0.331 | Yes |
| | | | | | 9,107 | 0.701 | C | 14,390 | 1.107 | F | 19,035 | 1.464 | F | 0.357 | Yes |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

³² Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 7-2 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Year 2022 Type of Arterial | (1) LOS E Capacity ³³ (VPD) | (2) Lanes | (3) Existing Traffic Conditions | | | (4) Year 2022 Without ELSP Project Phase I Traffic Conditions | | | (5) Year 2022 With ELSP Project Phase I Traffic Conditions | | | (6) Adverse Condition | |
|--|------------------|----------------------------|--|-----------|---------------------------------|-----------|-----|---|--------------|-----|--|--------------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 21. Corydon Road, <i>between Cereal Street and Palomar Street</i> | Weekday Saturday | Divided Collector | 18,000 | 2D | 15,630 | 0.868 | D | 20,308 | 1.128 | F | 23,915 | 1.329 | F | 0.201 | Yes |
| | | | | | 14,481 | 0.805 | D | 18,803 | 1.045 | F | 22,691 | 1.261 | F | 0.216 | Yes |
| 22. Mission Trail, <i>between Bundy Canyon Road and Palomar Street</i> | Weekday Saturday | Collector | 13,000 | 2U | 8,034 | 0.618 | B | 9,350 | 0.719 | C | 10,491 | 0.807 | D | 0.088 | No |
| | | | | | 6,887 | 0.530 | A | 8,006 | 0.616 | B | 9,236 | 0.710 | C | 0.094 | No |
| 23. Palomar Street, <i>between Corydon Road and Mission Trail</i> | Weekday Saturday | Collector | 13,000 | 2U | 3,221 | 0.248 | A | 3,843 | 0.296 | A | 4,337 | 0.334 | A | 0.038 | No |
| | | | | | 2,744 | 0.211 | A | 3,274 | 0.252 | A | 3,806 | 0.293 | A | 0.041 | No |
| 24. Stoneman Street, <i>north of Grand Avenue</i> | Weekday Saturday | Collector | 13,000 | 2U | 760 | 0.058 | A | 760 | 0.058 | A | 760 | 0.058 | A | 0.000 | No |
| | | | | | 724 | 0.056 | A | 724 | 0.056 | A | 724 | 0.056 | A | 0.000 | No |
| 25. Skylark Drive, <i>north of Grand Avenue</i> | Weekday Saturday | Collector | 13,000 | 2U | 220 | 0.017 | A | 2,063 | 0.159 | A | 2,063 | 0.159 | A | 0.000 | No |
| | | | | | 237 | 0.018 | A | 2,222 | 0.171 | A | 2,222 | 0.171 | A | 0.000 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

³³ Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 7-2 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Year 2022 Type of Arterial | (1) LOS E Capacity ³⁴ (VPD) | (2) Lanes | (3) Existing Traffic Conditions | | | (4) Year 2022 Without ELSP Project Phase I Traffic Conditions | | | (5) Year 2022 With ELSP Project Phase I Traffic Conditions | | | (6) Adverse Condition | |
|--|------------------|----------------------------|--|-----------|--|-----------|-----|---|--------------|-----|--|--------------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 26. Corydon Road, between Palomar Street and Grand Avenue | Weekday Saturday | Divided Collector | 18,000 | 2D | 11,849 | 0.658 | B | 16,459 | 0.914 | E | 17,681 | 0.982 | E | 0.068 | Yes |
| | | | | | 10,999 | 0.611 | B | 15,265 | 0.848 | D | 16,582 | 0.921 | E | 0.073 | Yes |
| 27. Sylvester Street, between Lucerne Street and Diamond Drive | Weekday Saturday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 710 | 0.021 | A | 9,894 | 0.290 | A | 0.269 | No |
| | | | | | 672 | 0.020 | A | 10,571 | 0.310 | A | 10,571 | 0.310 | A | 0.290 | No |
| 28. Lucerne Street, between Sylvester Street and Cereal Street | Weekday Saturday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 244 | 0.007 | A | 8,623 | 0.253 | A | 0.246 | No |
| | | | | | 231 | 0.007 | A | 9,263 | 0.272 | A | 9,263 | 0.272 | A | 0.265 | No |
| 29. Cereal Street, between Lucerne Street and Stoneman Street | Weekday Saturday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 244 | 0.007 | A | 5,602 | 0.164 | A | 0.157 | No |
| | | | | | 231 | 0.007 | A | 6,006 | 0.176 | A | 6,006 | 0.176 | A | 0.169 | No |
| 30. Cereal Street, between Stoneman Street and Diamond Drive | Weekday Saturday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 244 | 0.007 | A | 5,602 | 0.164 | A | 0.157 | No |
| | | | | | 231 | 0.007 | A | 6,006 | 0.176 | A | 6,006 | 0.176 | A | 0.169 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

³⁴ Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 7-2 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Year 2022 Type of Arterial | (1) LOS E Capacity ³⁵ (VPD) | (2) Lanes | (3) Existing Traffic Conditions | | | (4) Year 2022 Without ELSP Project Phase I Traffic Conditions | | | (5) Year 2022 With ELSP Project Phase I Traffic Conditions | | | (6) Adverse Condition | |
|---|------------------|----------------------------|--|-----------|--|-----------|-----|---|-----------|-----|--|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 31. Diamond Drive, between Olive Street and Cereal Street | Weekday Saturday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 812 | 0.024 | A | 1,597 | 0.047 | A | 0.023 | No |
| 32. Bundy Canyon Road, between Corydon Road and Mission Trail | Weekday Saturday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 769 | 0.023 | A | 1,615 | 0.047 | A | 0.024 | No |
| | | | | | | | | 6,702 | 0.197 | A | 11,699 | 0.343 | A | 0.146 | No |
| | | | | | | | | 6,348 | 0.186 | A | 11,734 | 0.344 | A | 0.158 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

³⁵ Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 7-3
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Type of Arterial | Approach | Time Period | Link Capacity (VPHPL) | Lanes | Total Link Capacity (VPH) | (4) Year 2022 With ELSP Project Phase I Traffic Conditions | | |
|--|------------------|------------|-----------------|-----------------------|-------|---------------------------|--|-----------|-----|
| | | | | | | | Peak Hour Volume | V/C Ratio | LOS |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | Major | Eastbound | Weekday AM | 1,600 | 2 | 3200 | 780 | 0.244 | A |
| | | | Weekday PM | 1,600 | 2 | 3200 | 769 | 0.240 | A |
| | | | Saturday Midday | 1,600 | 2 | 3200 | 1,689 | 0.528 | A |
| | | Westbound | Weekday AM | 1,600 | 2 | 3200 | 1,094 | 0.342 | A |
| | | | Weekday PM | 1,600 | 2 | 3200 | 1,447 | 0.452 | A |
| | | | Saturday Midday | 1,600 | 2 | 3200 | 1,536 | 0.480 | A |
| 15. Mission Trail, <i>between Victorian Lane and Lemon Street</i> | Secondary | Northbound | Weekday AM | 1,600 | 2 | 3200 | 897 | 0.280 | A |
| | | | Weekday PM | 1,600 | 2 | 3200 | 898 | 0.281 | A |
| | | | Saturday Midday | 1,600 | 2 | 3200 | 984 | 0.308 | A |
| | | Southbound | Weekday AM | 1,600 | 2 | 3200 | 697 | 0.218 | A |
| | | | Weekday PM | 1,600 | 2 | 3200 | 1,091 | 0.341 | A |
| | | | Saturday Midday | 1,600 | 2 | 3200 | 1,540 | 0.481 | A |

Notes:

- VPHPL = Vehicles Per Hour Per Lane
- VPH = Vehicles Per Hour
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions

TABLE 7-3 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Type of Arterial | Approach | Time Period | Link Capacity (VPHPL) | Lanes | Total Link Capacity (VPH) | (4) Year 2022 With ELSP Project Phase I Traffic Conditions | | |
|---|------------------|------------|-----------------|-----------------------|-------|---------------------------|--|-----------|-----|
| | | | | | | | Peak Hour Volume | V/C Ratio | LOS |
| 17. Corydon Road, <i>between</i> Mission Trail and Cereal Street | Divided Arterial | Northbound | Weekday AM | 1,600 | 1 | 1600 | 674 | 0.211 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 620 | 0.388 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 676 | 0.423 | A |
| | Southbound | | Weekday AM | 1,600 | 1 | 1600 | 504 | 0.315 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 790 | 0.494 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 565 | 0.353 | A |
| 20. Bundy Canyon Road, <i>between</i> Mission Trail and I-15 Southbound Ramps | Collector | Eastbound | Weekday AM | 1,600 | 1 | 1600 | 823 | 0.514 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 866 | 0.541 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 1,427 | 0.892 | D |
| | Westbound | | Weekday AM | 1,600 | 1 | 1600 | 583 | 0.364 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 851 | 0.532 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 732 | 0.458 | A |

Notes:

- VPHPL = Vehicles Per Hour Per Lane
- VPH = Vehicles Per Hour
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions

TABLE 7-3 (CONTINUED)
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Type of Arterial | Approach | Time Period | Link Capacity (VPHPL) | Lanes | Total Link Capacity (VPH) | (4) Year 2022 With ELSP Project Phase I Traffic Conditions | | |
|---|-------------------|------------|-----------------|-----------------------|-------|---------------------------|--|-----------|-----|
| | | | | | | | Peak Hour Volume | V/C Ratio | LOS |
| 21. Corydon Road, <i>between Cereal Street and Palomar Street</i> | Divided Collector | Northbound | Weekday AM | 1,600 | 1 | 1600 | 980 | 0.613 | B |
| | | | Weekday PM | 1,600 | 1 | 1600 | 883 | 0.552 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 908 | 0.568 | A |
| | | Southbound | Weekday AM | 1,600 | 1 | 1600 | 649 | 0.406 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 921 | 0.576 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 802 | 0.501 | A |
| 26. Corydon Road, <i>between Palomar Street and Grand Avenue</i> | Divided Collector | Northbound | Weekday AM | 1,600 | 1 | 1600 | 878 | 0.549 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 714 | 0.446 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 790 | 0.494 | A |
| | | Southbound | Weekday AM | 1,600 | 1 | 1600 | 562 | 0.351 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 660 | 0.413 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 657 | 0.411 | A |

Notes:

- VPHPL = Vehicles Per Hour Per Lane
- VPH = Vehicles Per Hour
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions

8.0 YEAR 2040 CONDITIONS TRAFFIC IMPACT ANALYSIS

The relative impacts of the added ELSP Project Buildout traffic volumes generated by proposed ELSP Project Buildout during the AM peak hour, PM peak hour, Saturday Midday peak hour and Daily conditions was evaluated based on analysis of future Year 2040 operating conditions at the thirty (30) key study intersections and thirty-two (32) key roadway segments, with Adopted Specific Plan and with the proposed ELSP Project Buildout. The previously discussed capacity analysis procedures were utilized to investigate the future Delay/V/C relationships and service level characteristics at each study intersection and roadway segment. The significance of the potential impacts of the ELSP Project Buildout at each key intersection and roadway segment was then evaluated using the traffic impact criteria mentioned in this report.

8.1 Year 2040 Conditions Intersection Capacity Analysis

Table 8-1 summarizes the AM, PM and Saturday Midday peak hour Level of Service results at the thirty (30) key study intersections for the Year 2040 traffic conditions. The first column (1) of Delay/LOS values in *Table 8-1* presents a summary of existing AM, PM and Saturday Midday peak hour traffic conditions. The second column (2) presents forecast Year 2040 With Adopted Specific Plan traffic conditions and the third column (3) identifies forecast Year 2040 With ELSP Project Buildout traffic conditions. The fourth column (4) indicates whether the traffic associated with the ELSP Project Buildout will have a significant impact based on the significant impact criteria mentioned in this report. The fifth column (5) presents the resultant level of service with the inclusion of recommended improvements, where needed, to achieve an acceptable level of service.

Planned improvements, which are discussed in more detail in *Section 9.0* of this report, have been assumed for the Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout scenarios for the intersections listed below:

- 1. Railroad Canyon Road at Summerhill Road/Grape Street
- 2. Railroad Canyon Road at I-15 NB Ramps
- 3. Diamond Drive at I-15 SB Ramps
- 5. Lucerne Street at Lakeshore Drive
- 6. Diamond Drive at Lakeshore Drive/Mission Trail
- 8. Mission Trail at Campbell Street
- 10. Mission Trail at Malaga Road
- 11. Mission Trail at Olive Street
- 12. Mission Trail at Victorian Lane
- 13. Mission Trail at Lemon Street
- 15. Corydon Road at Cereal Street
- 16. Mission Trail at Bundy Canyon Road
- 17. Orange Street at Bundy Canyon Road
- 18. I-15 SB Ramps at Bundy Canyon Road

- 19. I-15 NB Ramps at Bundy Canyon Road
- 20. Corydon Road at Palomar Street
- 21. Mission Trail at Palomar Street
- 22. Stoneman Street at Grand Avenue
- 23. Corydon Road at Grand Avenue
- 24. Grape Street at I-15 NB Ramps
- 25. Diamond Drive at Olive Street
- 26. "A" Street at Olive Street
- 27. "A" Street at Victorian Lane
- 28. "A" Street at Cereal Street
- 29. Lucerne Street at Sylvester Street
- 30. Stoneman Street at Cereal Street

8.1.1 Year 2040 With Adopted Specific Plan Traffic Conditions

Review of column (2) of *Table 8-1* indicates that for the Year 2040 With Adopted Specific Plan traffic conditions, fifteen (15) key study intersections are forecast to operate at an unacceptable level of service during the AM, PM and/or Saturday Midday peak hours when compared to the LOS standards defined in this report. The remaining key study intersections are forecast to operate at acceptable levels of service during the AM, PM and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|---|----------------------------|-------------------|----------------------------|-------------------|---|-------------------|
| | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> | <u>Delay (s/v)</u> | <u>LOS</u> |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | 178.9 | F | 280.6 | F | 387.5 | F |
| 3. Diamond Drive at I-15 Southbound Ramps | -- | -- | -- | -- | 98.1 | F |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | 164.6 | F | 254.9 | F | 273.5 | F |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | 265.9 | F | 344.1 | F | 499.0 | F |
| 7. Diamond Drive at Campbell Street | -- | -- | -- | -- | 5,294.2 | F |
| 8. Mission Trail at Campbell Street | -- | -- | 235.3 | F | 451.1 | F |
| 9. Diamond Drive at Malaga Road | -- | -- | -- | -- | 158.9 | F |
| 10. Mission Trail at Malaga Road | -- | -- | -- | -- | 91.4 | F |
| 15. Corydon Road at Cereal Street | -- | -- | 61.3 | E | -- | -- |
| 17. Orange Street at Bundy Canyon Road | 59.9 | E | 55.6 | E | 55.7 | E |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | 86.5 | F | -- | -- | 82.2 | F |
| 21. Mission Trail at Palomar Street | 87.0 | F | 110.0 | F | 58.5 | E |
| 22. Stoneman Street at Grand Avenue | 57.4 | E | -- | -- | -- | -- |
| 24. Grape Street at I-15 Northbound Ramps | 72.8 | E | 74.5 | E | 340.4 | F |
| 25. Diamond Drive at Olive Street | -- | -- | 48.0 | E | 41.9 | F |

8.1.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

Review of column (3) of *Table 8-1* indicates that for the Year 2040 With ELSP Project Buildout traffic conditions, eleven (11) key study intersections are forecast to operate at unacceptable levels of service during the AM, PM and/or Saturday Midday peak hours when compared to the LOS standards defined in this report. The remaining key study intersections are forecast to operate at acceptable levels of service during the AM, PM and Saturday Midday peak hours. The intersections operating at adverse levels of service are:

| <u>Key Intersection</u> | <u>AM Peak Hour</u> | | <u>PM Peak Hour</u> | | <u>Saturday Midday Peak Hour</u> | |
|---|------------------------------|------------|------------------------------|------------|----------------------------------|------------|
| | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> | <u>Delay</u> <u>(s/v)</u> | <u>LOS</u> |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | 162.0 | F | 271.8 | F | 383.1 | F |
| 3. Diamond Drive at I-15 Southbound Ramps | -- | -- | -- | -- | 87.2 | F |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | 124.8 | F | 209.0 | F | 213.5 | F |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | 237.7 | F | 308.6 | F | 440.0 | F |
| 7. Diamond Drive at Campbell Street | -- | -- | -- | -- | 3,158.4 | F |
| 8. Mission Trail at Campbell Street | -- | -- | 101.2 | F | 183.2 | F |
| 9. Diamond Drive at Malaga Road | -- | -- | -- | -- | 194.2 | F |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | 70.7 | E | -- | -- | 72.9 | E |
| 21. Mission Trail at Palomar Street | 76.6 | E | 108.1 | F | -- | -- |
| 22. Stoneman Street at Grand Avenue | 56.7 | E | -- | -- | -- | -- |
| 24. Grape Street at I-15 Northbound Ramps | 70.6 | E | 73.5 | E | 341.8 | F |

Review of column (4) of *Table 8-1* indicates that eleven (11) key study intersections will have a significant impact under the Year 2040 With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report. However, as shown in column (5) of *Table 8-1*, the recommended improvements outlined in this report will offset the impact of the ELSP Project Buildout traffic and bring the significantly impacted intersections to below Adopted Specific Plan and/or acceptable conditions at ten (10) of the eleven (11) impacted locations. It should be noted that mitigation for key study intersection #4, Diamond Drive at Casino Drive/Auto Center Drive, is infeasible due to the surrounding parcels preventing the additional needed right-of-way.

Appendix F contains the Delay/LOS calculation worksheets for the Year 2040 Traffic Conditions.

TABLE 8-1
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Year 2040 With Adopted Specific Plan Traffic Conditions | | (3) Year 2040 With ELSP Project Buildout Traffic Conditions | | (4) Significant Impact | (5) Year 2040 With ELSP Project Buildout With Mitigation | |
|---|------------------------|-----------------|------------------------------------|-----|---|-----|--|-----|---------------------------|---|-----------------|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | | Delay (s/v) | LOS |
| | | | | | | | | | | Yes/No | |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | D | Weekday AM | 37.1 | D | 178.9 | F | 162.0 | F | Yes | 109.1 | F |
| | | Weekday PM | 46.4 | D | 280.6 | F | 271.8 | F | Yes | 115.7 | F |
| | | Saturday Midday | 39.8 | D | 387.5 | F | 383.1 | F | Yes | 116.7 | F |
| 2. Railroad Canyon Road at I-15 Northbound Ramps | D | Weekday AM | 21.3 | C | Intersection Does Not Exist Under Year 2040 Traffic Conditions Per City's Preferred Alternative Two | | | | No | -- | -- |
| | | Weekday PM | 19.8 | B | | | | | No | -- | -- |
| | | Saturday Midday | 24.1 | C | | | | | No | -- | -- |
| 3. Diamond Drive at I-15 Southbound Ramps | D | Weekday AM | 36.8 | D | 30.2 | C | 25.6 | C | No | 24.4 | C |
| | | Weekday PM | 27.0 | C | 35.9 | D | 34.0 | C | No | 30.8 | C |
| | | Saturday Midday | 28.2 | C | 98.1 | F | 87.2 | F | Yes | 49.1 | D |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | D | Weekday AM | 21.7 | C | 164.6 | F | 124.8 | F | Yes | 28.1 ³⁶ | C |
| | | Weekday PM | 20.6 | C | 254.9 | F | 209.0 | F | Yes | 42.1 | D |
| | | Saturday Midday | 21.4 | C | 273.5 | F | 213.5 | F | Yes | 54.1 | D |
| 5. Lucerne Street at Lakeshore Drive | D | Weekday AM | 12.3 | B | 19.3 | B | 21.9 | C | No | -- | -- |
| | | Weekday PM | 15.1 | C | 25.2 | C | 44.7 | D | No | -- | -- |
| | | Saturday Midday | 12.0 | B | 22.8 | C | 52.2 | D | No | -- | -- |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | E | Weekday AM | 36.5 | D | 265.9 | F | 237.7 | F | Yes | 206.7 | F |
| | | Weekday PM | 38.2 | D | 344.1 | F | 308.6 | F | Yes | 271.8 | F |
| | | Saturday Midday | 45.9 | D | 499.0 | F | 440.0 | F | Yes | 372.4 | F ³⁷ |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1 and 3-2* for the LOS definitions

³⁶ It should be noted that the mitigation is infeasible due to the surrounding parcels preventing the additional needed right-of-way and the mitigated LOS/Delay is shown only for informational purposes.

³⁷ Volumes have been rerouted due to the recommended improvement at the intersection of Diamond Drive at Campbell Street during the Saturday Midday peak hour.

TABLE 8-1 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Year 2040 With Adopted Specific Plan Traffic Conditions | | (3) Year 2040 With ELSP Project Buildout Traffic Conditions | | (4) Significant Impact | (5) Year 2040 With ELSP Project Buildout With Mitigation | |
|-------------------------------------|------------------------|-----------------|------------------------------------|-----|--|----------|--|----------|---------------------------|---|-----------------|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | | Delay (s/v) | LOS |
| | | | | | | | | | | | |
| 7. Diamond Drive at Campbell Street | E | Weekday AM | 8.9 | A | 12.7 | B | 11.1 | B | No | -- | -- |
| | | Weekday PM | 9.2 | A | 21.5 | C | 16.8 | C | No | -- | -- |
| | | Saturday Midday | 10.1 | B | 5,294.2 | F | 3,158.4 | F | Yes | 27.8 | D ³⁸ |
| 8. Mission Trail at Campbell Street | E | Weekday AM | 17.5 | C | 48.4 | E | 36.2 | E | No | 2.9 | A |
| | | Weekday PM | 22.0 | C | 235.3 | F | 101.2 | F | Yes | 4.6 | A |
| | | Saturday Midday | 28.6 | D | 451.1 | F | 183.2 | F | Yes | 6.8 | A ³⁹ |
| 9. Diamond Drive at Malaga Road | E | Weekday AM | 9.9 | A | 9.8 | A | 13.5 | B | No | 13.4 | B |
| | | Weekday PM | 13.2 | B | 16.9 | B | 17.3 | B | No | 15.8 | B |
| | | Saturday Midday | 16.1 | B | 158.9 | F | 194.2 | F | Yes | 35.1 | D ³⁹ |
| 10. Mission Trail at Malaga Road | E | Weekday AM | 9.2 | A | 10.0 | B | 10.4 | B | No | -- | -- |
| | | Weekday PM | 14.1 | B | 22.3 | C | 18.3 | B | No | -- | -- |
| | | Saturday Midday | 15.7 | B | 91.4 | F | 79.4 | E | No | 79.5 | E ³⁹ |
| 11. Mission Trail at Olive Street | D | Weekday AM | 5.6 | A | 9.5 | A | 9.3 | A | No | -- | -- |
| | | Weekday PM | 6.8 | A | 12.9 | B | 12.2 | B | No | -- | -- |
| | | Saturday Midday | 7.2 | A | 13.1 | B | 12.3 | B | No | -- | -- |
| 12. Mission Trail at Victorian Lane | D | Weekday AM | 25.3 | D | 3.7 | A | 3.3 | A | No | -- | -- |
| | | Weekday PM | 27.9 | D | 4.4 | A | 3.9 | A | No | -- | -- |
| | | Saturday Midday | 26.4 | D | 4.9 | A | 4.0 | A | No | -- | -- |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1* and *3-2* for the LOS definitions

³⁸ The recommended improvement at this location includes the restriction of the southbound left and westbound left movement during the Saturday Midday peak hour. Due to the acceptable LOS during the AM and PM peak hour, no restrictions will be required during the weekday AM and PM peak hour.

³⁹ Volumes have been rerouted due to the recommended improvement at the intersection of Diamond Drive at Campbell Street during the Saturday Midday peak hour.

TABLE 8-1 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) | | (2) | | (3) | | (4) | (5) | | |
|--|------------------------|-----------------|-----------------------------|-----|---|-----|---|-----|------------|--|-----|--|
| | | | Existing Traffic Conditions | | Year 2040 With Adopted Specific Plan Traffic Conditions | | Year 2040 With ELSP Project Buildout Traffic Conditions | | | Year 2040 With ELSP Project Buildout With Mitigation | | |
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | | Delay (s/v) | LOS | |
| 13. Mission Trail at Lemon Street | D | Weekday AM | 8.0 | A | 12.5 | B | 11.7 | B | No | -- | -- | |
| | | Weekday PM | 8.0 | A | 12.3 | B | 11.6 | B | No | -- | -- | |
| | | Saturday Midday | 7.7 | A | 12.9 | B | 12.2 | B | No | -- | -- | |
| 14. Mission Trail at Corydon Road | D | Weekday AM | 19.9 | B | 16.9 | B | 16.5 | B | No | -- | -- | |
| | | Weekday PM | 18.7 | B | 15.2 | B | 14.9 | B | No | -- | -- | |
| | | Saturday Midday | 18.4 | B | 18.1 | B | 17.7 | B | No | -- | -- | |
| 15. Corydon Road at Cereal Street | D | Weekday AM | 13.5 | B | 30.1 | C | 25.5 | C | No | -- | -- | |
| | | Weekday PM | 15.2 | C | 61.3 | E | 43.1 | D | No | -- | -- | |
| | | Saturday Midday | 13.9 | B | 35.0 | D | 32.2 | C | No | -- | -- | |
| 16. Mission Trail at Bundy Canyon Road | D | Weekday AM | 18.9 | B | 40.2 | D | 37.5 | D | No | -- | -- | |
| | | Weekday PM | 24.4 | C | 51.5 | D | 47.9 | D | No | -- | -- | |
| | | Saturday Midday | 20.5 | C | 47.6 | D | 43.5 | D | No | -- | -- | |
| 17. Orange Street at Bundy Canyon Road | D | Weekday AM | 294.4 | F | 59.9 | E | 54.9 | D | No | -- | -- | |
| | | Weekday PM | 112.5 | F | 55.6 | E | 50.6 | D | No | -- | -- | |
| | | Saturday Midday | 150.7 | F | 55.7 | E | 52.5 | D | No | -- | -- | |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | D | Weekday AM | 36.7 | D | 86.5 | F | 70.7 | E | Yes | 27.1 | C | |
| | | Weekday PM | 23.0 | C | 48.1 | D | 43.7 | D | No | 21.8 | C | |
| | | Saturday Midday | 19.8 | B | 82.2 | F | 72.9 | E | Yes | 21.9 | C | |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1* and *3-2* for the LOS definitions

TABLE 8-1 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Year 2040 With Adopted Specific Plan Traffic Conditions | | (3) Year 2040 With ELSP Project Buildout Traffic Conditions | | (4) Significant Impact | (5) Year 2040 With ELSP Project Buildout With Mitigation | |
|--|------------------------|-----------------|---|----------|--|----------|--|----------|---------------------------|---|-----|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | | Delay (s/v) | LOS |
| | | | | | | | | | | | |
| 19. I-15 Northbound Ramps at Bundy Canyon Road | D | Weekday AM | 23.8 | C | 25.5 | C | 28.4 | C | No | -- | -- |
| | | Weekday PM | 24.4 | C | 41.7 | D | 33.4 | C | No | -- | -- |
| | | Saturday Midday | 20.8 | C | 27.4 | C | 25.6 | C | No | -- | -- |
| 20. Corydon Road at Palomar Street | D | Weekday AM | 16.4 | B | 30.0 | C | 26.9 | C | No | -- | -- |
| | | Weekday PM | 13.5 | B | 25.5 | C | 25.2 | C | No | -- | -- |
| | | Saturday Midday | 14.1 | B | 19.9 | B | 20.0 | C | No | -- | -- |
| 21. Mission Trail at Palomar Street | D | Weekday AM | 13.7 | B | 87.0 | F | 76.6 | E | Yes | 27.1 | C |
| | | Weekday PM | 12.6 | B | 110.0 | F | 108.1 | F | Yes | 30.8 | C |
| | | Saturday Midday | 11.0 | B | 58.5 | E | 35.7 | D | No | 24.5 | C |
| 22. Stoneman Street at Grand Avenue | D | Weekday AM | 41.7 | E | 57.4 | E | 56.7 | E | Yes | 52.2 | D |
| | | Weekday PM | 38.3 | E | 46.9 | D | 44.3 | D | No | 37.4 | D |
| | | Saturday Midday | 20.0 | C | 26.8 | C | 26.1 | C | No | 27.8 | C |
| 23. Corydon Road at Grand Avenue | D | Weekday AM | 13.8 | B | 23.6 | C | 23.3 | C | No | -- | -- |
| | | Weekday PM | 12.7 | B | 29.1 | C | 29.6 | C | No | -- | -- |
| | | Saturday Midday | 11.6 | B | 19.5 | B | 19.5 | B | No | -- | -- |
| 24. Grape Street at I-15 Northbound Ramps | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | | 72.8 | E | 70.6 | E | Yes | 25.8 | C |
| | | Weekday PM | Intersection Does Not Exist Under Existing Traffic Conditions | | 74.5 | E | 73.5 | E | Yes | 24.2 | C |
| | | Saturday Midday | Intersection Does Not Exist Under Existing Traffic Conditions | | 340.4 | F | 341.8 | F | Yes | 25.7 | C |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1 and 3-2* for the LOS definitions

TABLE 8-1 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR INTERSECTION CAPACITY ANALYSIS SUMMARY

| Key Intersection | Minimum Acceptable LOS | Time Period | (1) Existing Traffic Conditions | | (2) Year 2040 With Adopted Specific Plan Traffic Conditions | | (3) Year 2040 With ELSP Project Buildout Traffic Conditions | | (4) Significant Impact | (5) Year 2040 With ELSP Project Buildout With Mitigation | |
|--|------------------------|-----------------|---|-----|--|-----|--|-----|---------------------------|---|-----|
| | | | Delay (s/v) | LOS | Delay (s/v) | LOS | Delay (s/v) | LOS | | Delay (s/v) | LOS |
| 25. Diamond Drive at Olive Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | | 14.2 | B | 10.3 | B | No | -- | -- |
| | | Weekday PM | | | 48.0 | E | 11.6 | B | No | -- | -- |
| | | Saturday Midday | | | 41.9 | F | 11.0 | B | No | -- | -- |
| 26. "A" Street at Olive Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | | 5.4 | A | 3.6 | A | No | -- | -- |
| | | Weekday PM | | | 6.7 | A | 3.9 | A | No | -- | -- |
| | | Saturday Midday | | | 7.4 | A | 4.0 | A | No | -- | -- |
| 27. "A" Street at Victorian Lane | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | | 4.3 | A | 3.4 | A | No | -- | -- |
| | | Weekday PM | | | 5.1 | A | 3.5 | A | No | -- | -- |
| | | Saturday Midday | | | 5.2 | A | 3.6 | A | No | -- | -- |
| 28. "A" Street at Cereal Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | | 15.9 | C | 10.8 | B | No | -- | -- |
| | | Weekday PM | | | 32.7 | D | 13.8 | B | No | -- | -- |
| | | Saturday Midday | | | 17.3 | C | 11.9 | B | No | -- | -- |
| 29. Lucerne Street at Sylvester Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | | 15.8 | C | 17.9 | C | No | -- | -- |
| | | Weekday PM | | | 21.6 | C | 26.8 | D | No | -- | -- |
| | | Saturday Midday | | | 18.8 | C | 30.8 | D | No | -- | -- |
| 30. Stoneman Street at Cereal Street | D | Weekday AM | Intersection Does Not Exist Under Existing Traffic Conditions | | 25.5 | C | 23.9 | C | No | -- | -- |
| | | Weekday PM | | | 25.9 | C | 23.0 | C | No | -- | -- |
| | | Saturday Midday | | | 28.8 | C | 25.5 | C | No | -- | -- |

Notes:

- s/v = seconds per vehicle (delay); **Bold Delay/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report
- LOS = Level of Service, please refer to *Tables 3-1 and 3-2* for the LOS definitions

8.2 Year 2040 Conditions Roadway Segment Analysis

Table 8-2 summarizes the daily level of service results at the thirty-two (32) key study roadway segments during a “typical” Weekday and Saturday for the Year 2040 traffic conditions. The first column (1) of LOS E Capacity values in *Table 8-2* presents the daily roadway segment capacities from the *City of Lake Elsinore General Plan Update Draft Program EIR, dated August 2011*. The second column (2) lists the number of travel lanes and the third column (3) indicates the Existing daily traffic volumes, Volume to Capacity (V/C) ratio and Level of Service (LOS) (which were also presented in *Tables 7-2* and *8-2*). The fourth column (4) forecasts Year 2040 With Adopted Specific Plan traffic conditions. The fifth column (5) in *Table 8-2* forecasts the Year 2040 With ELSP Project Buildout traffic conditions. The sixth column (6) of *Table 8-2* presents the increase in the V/C ratio and indicates whether the roadway segment operates at an adverse level of service based on the LOS standards and the impact criteria defined in this report.

Planned improvements, which are discussed in more detail in *Section 9.0* of this report, have been assumed for the Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout scenarios for the roadway segments listed below:

- 3. Lucerne Street, south of Lakeshore Drive
- 7. Mission Trail, between Diamond Drive and Campbell Street
- 8. Mission Trail, between Campbell Street and Malaga Road
- 12. Mission Trail, between Malaga Road and Olive Street
- 13. Olive Street, between Mission Trail and Grape Street
- 14. Mission Trail, between Olive Street and Victorian Lane
- 15. Mission Trail, between Victorian Lane and Lemon Street
- 17. Corydon Road, between Mission Trail and Cereal Street
- 18. Cereal Street, west of Corydon Road
- 20. Bundy Canyon Road, between Mission Trail and I-15 SB Ramps
- 21. Corydon Road, between Cereal Street and Palomar Street
- 24. Stoneman Street, north of Grand Avenue
- 26. Corydon Road, between Palomar Street and Grand Avenue
- 27. Sylvester Street, between Lucerne Street and Diamond Drive
- 28. Lucerne Street, between Sylvester Street and Cereal Street
- 29. Cereal Street, between Lucerne Street and Stoneman Street
- 30. Cereal Street, between Stoneman Street and Diamond Drive
- 31. Diamond Drive, between Olive Street and Cereal Street
- 32. Bundy Canyon Road, between Corydon Road and Mission Trail

8.2.1 Year 2040 With Adopted Specific Plan Traffic Conditions

Review of column (4) of *Table 8-2* indicates that for the Year 2040 With Adopted Specific Plan traffic conditions, four (4) key study roadway segments are forecast to operate at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway segments are forecast to operate at acceptable levels of service on a daily basis. The roadway segments operating at adverse levels of service are:

| <u>Key Roadway Segment</u> | <u>Weekday Daily</u> | | | <u>Saturday Daily</u> | | |
|--|----------------------|------------------|------------|-----------------------|------------------|------------|
| | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | 44,238 | 1.297 | F | 52,557 | 1.541 | F |
| 21. Corydon Road, <i>between Cereal Street and Palomar Street</i> | 32,174 | 0.944 | E | 32,003 | 0.939 | E |
| 22. Mission Trail, <i>between Bundy Canyon Road and Palomar Street</i> | 16,208 | 1.247 | F | 14,631 | 1.125 | F |
| 23. Palomar Street, <i>between Corydon Road and Mission Trail</i> | 13,718 | 1.055 | F | 12,059 | 0.928 | E |

8.2.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

Review of column (5) of *Table 8-2* indicates that for the Year 2040 With ELSP Project Buildout traffic conditions, three (3) key study roadway segments are forecast to operate at unacceptable levels of service on a daily basis when compared to the LOS standards defined in this report. The remaining key study roadway segments are forecast to operate at acceptable levels of service on a daily basis. The roadway segments operating at adverse levels of service are:

| <u>Key Roadway Segment</u> | <u>Weekday Daily</u> | | | <u>Saturday Daily</u> | | |
|--|----------------------|------------------|------------|-----------------------|------------------|------------|
| | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> | <u>Volume</u> | <u>V/C Ratio</u> | <u>LOS</u> |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | 44,090 | 1.293 | F | 52,289 | 1.533 | F |
| 22. Mission Trail, <i>between Bundy Canyon Road and Palomar Street</i> | 15,466 | 1.190 | F | 13,554 | 1.043 | F |
| 23. Palomar Street, <i>between Corydon Road and Mission Trail</i> | 13,572 | 1.044 | F | 11,788 | 0.907 | E |

To determine if the ELSP Project Buildout creates a significant impact, these adverse roadway segments are further analyzed under peak hour conditions to determine if there are any peak hour deficiencies. As presented in *Table 8-3*, these study roadway segments are forecast to operate at LOS C or better during the AM, PM and Saturday Midday peak hours. As a result, the key study roadway segments are not significantly impacted by Year 2040 With ELSP Project Buildout traffic and therefore no improvements are required.

TABLE 8-2
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Yr. 2040 Type of Arterial | LOS E Capacity ⁴⁰ (VPD) | Lanes | (3) Existing Traffic Conditions | | | (4) Year 2040 With Adopted Specific Plan Traffic Conditions | | | (5) Year 2040 With ELSP Project Buildout Traffic Conditions | | | (6) Adverse Condition | |
|--|-------------|---------------------------|------------------------------------|-------|---------------------------------|-----------|-----|---|--------------|----------|---|--------------|----------|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | Weekday | Major | 34,100 | 4D | 20,281 | 0.595 | A | 44,238 | 1.297 | F | 44,090 | 1.293 | F | -0.004 | Yes |
| | Saturday | | | | 24,102 | 0.707 | C | 52,557 | 1.541 | F | 52,289 | 1.533 | F | -0.008 | Yes |
| 2. Railroad Canyon Road, <i>between Summerhill Drive/Grape Street and Lakeshore Drive/Mission Trail</i> | Weekday | Urban Arterial | 62,850 | 7D | 26,367 | 0.420 | A | 47,181 | 0.751 | C | 43,951 | 0.699 | B | -0.052 | No |
| | Saturday | | | | 26,682 | 0.425 | A | 52,096 | 0.829 | D | 47,416 | 0.754 | C | -0.075 | No |
| 3. Lucerne Street, <i>south of Lakeshore Drive</i> | Weekday | Major | 34,100 | 4D | 71 | 0.005 | A | 13,145 | 0.385 | A | 16,695 | 0.490 | A | 0.105 | No |
| | Saturday | | | | 63 | 0.005 | A | 13,658 | 0.401 | A | 16,943 | 0.497 | A | 0.096 | No |
| 4. Casino Drive, <i>east of Diamond Drive</i> | Weekday | Major | 34,100 | 4D | 5,861 | 0.172 | A | 12,291 | 0.360 | A | 12,352 | 0.362 | A | 0.002 | No |
| | Saturday | | | | 5,468 | 0.160 | A | 11,468 | 0.336 | A | 11,523 | 0.338 | A | 0.002 | No |
| 5. Diamond Drive, <i>between Lakeshore Drive/Mission Trail and Campbell Street</i> | Weekday | Major | 34,100 | 4D | 4,924 | 0.144 | A | 26,642 | 0.781 | C | 22,269 | 0.653 | B | -0.128 | No |
| | Saturday | | | | 4,703 | 0.138 | A | 29,203 | 0.856 | D | 23,759 | 0.697 | B | -0.159 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

⁴⁰ Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 8-2 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Yr. 2040 Type of Arterial | LOS E Capacity ⁴¹ (VPD) | Lanes | Existing Traffic Conditions | | | Year 2040 With Adopted Specific Plan Traffic Conditions | | | Year 2040 With ELSP Project Buildout Traffic Conditions | | | (6) Adverse Condition | |
|---|-------------|---------------------------|------------------------------------|-------|-----------------------------|-----------|-----|---|-----------|-----|---|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 6. Diamond Drive, between Campbell Street and Malaga Road | Weekday | Major | 34,100 | 4D | 3,671 | 0.108 | A | 16,884 | 0.495 | A | 11,556 | 0.339 | A | -0.156 | No |
| | Saturday | | | | 3,750 | 0.110 | A | 18,435 | 0.541 | A | 11,883 | 0.348 | A | -0.193 | No |
| 7. Mission Trail, between Diamond Drive and Campbell Street | Weekday | Urban Arterial | 53,900 | 6D | 19,238 | 0.564 | A | 37,889 | 0.703 | C | 33,497 | 0.621 | B | -0.082 | No |
| | Saturday | | | | 16,742 | 0.491 | A | 36,345 | 0.674 | B | 30,217 | 0.561 | A | -0.113 | No |
| 8. Mission Trail, between Campbell Street and Malaga Road | Weekday | Urban Arterial | 53,900 | 6D | 16,132 | 0.473 | A | 37,389 | 0.694 | B | 31,662 | 0.587 | A | -0.107 | No |
| | Saturday | | | | 16,713 | 0.490 | A | 40,311 | 0.748 | C | 32,960 | 0.612 | B | -0.136 | No |
| 9. Malaga Road, between Diamond Drive and Mission Trail | Weekday | Major | 34,100 | 4D | 1,216 | 0.036 | A | 4,264 | 0.125 | A | 4,024 | 0.118 | A | -0.007 | No |
| | Saturday | | | | 1,238 | 0.036 | A | 4,358 | 0.128 | A | 4,082 | 0.120 | A | -0.008 | No |
| 10. Malaga Road, east of Mission Trail | Weekday | Major | 34,100 | 4D | 2,740 | 0.211 | A | 2,776 | 0.081 | A | 2,754 | 0.081 | A | 0.000 | No |
| | Saturday | | | | 2,934 | 0.226 | A | 2,973 | 0.087 | A | 2,948 | 0.086 | A | -0.001 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

⁴¹ Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 8-2 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Yr. 2040 Type of Arterial | LOS E Capacity ⁴² (VPD) | Lanes | Existing Traffic Conditions | | | Year 2040 With Adopted Specific Plan Traffic Conditions | | | Year 2040 With ELSP Project Buildout Traffic Conditions | | | (6) Adverse Condition | |
|--|-------------|---------------------------|------------------------------------|-------|-----------------------------|-----------|-----|---|-----------|-----|---|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 11. Diamond Drive, <i>north of Summerly Place</i> | Weekday | Major | 34,100 | 4D | 703 | 0.021 | A | 11,934 | 0.350 | A | 6,413 | 0.188 | A | -0.162 | No |
| | Saturday | | | | 636 | 0.019 | A | 12,976 | 0.381 | A | 6,091 | 0.179 | A | -0.202 | No |
| 12. Mission Trail, <i>between Malaga Road and Olive Street</i> | Weekday | Urban Arterial | 53,900 | 6D | 16,593 | 0.487 | A | 39,372 | 0.730 | C | 33,313 | 0.618 | B | -0.112 | No |
| | Saturday | | | | 16,042 | 0.470 | A | 40,452 | 0.751 | C | 32,648 | 0.606 | B | -0.145 | No |
| 13. Olive Street, <i>between Mission Trail and Grape Street</i> | Weekday | Major | 34,100 | 4D | 2,393 | 0.184 | A | 5,824 | 0.171 | A | 5,673 | 0.166 | A | -0.005 | No |
| | Saturday | | | | 2,312 | 0.178 | A | 5,769 | 0.169 | A | 5,522 | 0.162 | A | -0.007 | No |
| 14. Mission Trail, <i>between Olive Street and Victorian Lane</i> | Weekday | Urban Arterial | 53,900 | 6D | 17,898 | 0.691 | B | 35,170 | 0.653 | B | 34,281 | 0.636 | B | -0.017 | No |
| | Saturday | | | | 16,952 | 0.655 | B | 34,584 | 0.642 | B | 32,917 | 0.611 | B | -0.031 | No |
| 15. Mission Trail, <i>between Victorian Lane and Lemon Street</i> | Weekday | Urban Arterial | 53,900 | 6D | 18,146 | 0.701 | C | 35,864 | 0.665 | B | 34,504 | 0.640 | B | -0.025 | No |
| | Saturday | | | | 17,176 | 0.663 | B | 35,343 | 0.656 | B | 33,121 | 0.614 | B | -0.042 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

⁴² Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 8-2 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Yr. 2040 Type of Arterial | LOS E Capacity ⁴³ (VPD) | Lanes | Existing Traffic Conditions | | | Year 2040 With Adopted Specific Plan Traffic Conditions | | | Year 2040 With ELSP Project Buildout Traffic Conditions | | | (6) Adverse Condition | |
|--|-------------|---------------------------|------------------------------------|-------|-----------------------------|--------------|----------|---|-----------|-----|---|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 16. Lemon Street, between Mission Trail and Grape Street | Weekday | Collector | 13,000 | 2U | 3,253 | 0.250 | A | 7,267 | 0.559 | A | 6,989 | 0.538 | A | -0.021 | No |
| | Saturday | | | | 3,007 | 0.231 | A | 6,945 | 0.534 | A | 6,529 | 0.502 | A | -0.032 | No |
| 17. Corydon Road, between Mission Trail and Cereal Street | Weekday | Major | 34,100 | 4D | 16,978 | 0.943 | E | 20,240 | 0.594 | A | 19,513 | 0.572 | A | -0.022 | No |
| | Saturday | | | | 15,639 | 0.869 | D | 19,760 | 0.579 | A | 18,482 | 0.542 | A | -0.037 | No |
| 18. Cereal Street, west of Corydon Road | Weekday | Major | 34,100 | 4D | 445 | 0.034 | A | 11,588 | 0.340 | A | 8,048 | 0.236 | A | -0.104 | No |
| | Saturday | | | | 711 | 0.055 | A | 14,785 | 0.434 | A | 10,187 | 0.299 | A | -0.135 | No |
| 19. Mission Trail, between Corydon Road and Bundy Canyon Road | Weekday | Major | 34,100 | 4D | 13,919 | 0.408 | A | 24,718 | 0.725 | C | 24,592 | 0.721 | C | -0.004 | No |
| | Saturday | | | | 12,283 | 0.360 | A | 22,336 | 0.655 | B | 21,891 | 0.642 | B | -0.013 | No |
| 20. Bundy Canyon Road, between Mission Trail and I-15 Southbound Ramps | Weekday | Urban Arterial | 53,900 | 6D | 9,781 | 0.752 | C | 33,669 | 0.625 | B | 23,734 | 0.440 | A | -0.185 | No |
| | Saturday | | | | 9,107 | 0.701 | C | 33,355 | 0.619 | B | 22,785 | 0.423 | A | -0.196 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

⁴³ Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 8-2 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Yr. 2040 Type of Arterial | LOS E Capacity ⁴⁴ (VPD) | Lanes | Existing Traffic Conditions | | | Year 2040 With Adopted Specific Plan Traffic Conditions | | | Year 2040 With ELSP Project Buildout Traffic Conditions | | | (6) Adverse Condition | |
|---|-------------|---------------------------|------------------------------------|-------|-----------------------------|-----------|-----|---|--------------|----------|---|--------------|----------|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| | | | | | | | | | | | | | | | |
| 21. Corydon Road, between Cereal Street and Palomar Street | Weekday | Major | 34,100 | 4D | 15,630 | 0.868 | D | 32,174 | 0.944 | E | 29,572 | 0.867 | D | -0.077 | No |
| | Saturday | | | | 14,481 | 0.805 | D | 32,003 | 0.939 | E | 28,185 | 0.827 | D | -0.112 | No |
| 22. Mission Trail, between Bundy Canyon Road and Palomar Street | Weekday | Collector | 13,000 | 2U | 8,034 | 0.618 | B | 16,208 | 1.247 | F | 15,466 | 1.190 | F | -0.057 | Yes |
| | Saturday | | | | 6,887 | 0.530 | A | 14,631 | 1.125 | F | 13,554 | 1.043 | F | -0.082 | Yes |
| 23. Palomar Street, between Corydon Road and Mission Trail | Weekday | Collector | 13,000 | 2U | 3,221 | 0.248 | A | 13,718 | 1.055 | F | 13,572 | 1.044 | F | -0.011 | Yes |
| | Saturday | | | | 2,744 | 0.211 | A | 12,059 | 0.928 | E | 11,788 | 0.907 | E | -0.021 | Yes |
| 24. Stoneman Street, north of Grand Avenue | Weekday | Collector | 13,000 | 2U | 760 | 0.058 | A | 7,233 | 0.556 | A | 6,808 | 0.524 | A | -0.032 | No |
| | Saturday | | | | 724 | 0.056 | A | 7,383 | 0.568 | A | 6,682 | 0.514 | A | -0.054 | No |
| 25. Skylark Drive, north of Grand Avenue | Weekday | Collector | 13,000 | 2U | 220 | 0.017 | A | 1,065 | 0.082 | A | 1,374 | 0.106 | A | 0.024 | No |
| | Saturday | | | | 237 | 0.018 | A | 1,146 | 0.088 | A | 1,479 | 0.114 | A | 0.026 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

⁴⁴ Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 8-2 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Yr. 2040 Type of Arterial | LOS E Capacity ⁴⁵ (VPD) | Lanes | Existing Traffic Conditions | | | Year 2040 With Adopted Specific Plan Traffic Conditions | | | Year 2040 With ELSP Project Buildout Traffic Conditions | | | (6) Adverse Condition | |
|--|-------------|---------------------------|------------------------------------|-------|--|-----------|-----|---|-----------|-----|---|-------|---|-----------------------|----|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | | | | | |
| | | | | | | | | | | | | | | | |
| 26. Corydon Road, between Palomar Street and Grand Avenue | Weekday | Major | 34,100 | 4D | 11,849 | 0.658 | B | 27,757 | 0.814 | D | 27,633 | 0.810 | D | -0.004 | No |
| | Saturday | | | | 10,999 | 0.611 | B | 26,059 | 0.764 | C | 25,775 | 0.756 | C | -0.008 | No |
| 27. Sylvester Street, between Lucerne Street and Diamond Drive | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 649 | 0.019 | A | 918 | 0.027 | A | 0.008 | No |
| | Saturday | | | | | | | 736 | 0.022 | A | 974 | 0.029 | A | 0.007 | No |
| 28. Lucerne Street, between Sylvester Street and Cereal Street | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 11,487 | 0.337 | A | 14,630 | 0.429 | A | 0.092 | No |
| | Saturday | | | | | | | 12,491 | 0.366 | A | 15,280 | 0.448 | A | 0.082 | No |
| 29. Cereal Street, between Lucerne Street and Stoneman Street | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 7,941 | 0.233 | A | 9,353 | 0.274 | A | 0.041 | No |
| | Saturday | | | | | | | 8,350 | 0.245 | A | 9,605 | 0.282 | A | 0.037 | No |
| 30. Cereal Street, between Stoneman Street and Diamond Drive | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 10,158 | 0.298 | A | 10,626 | 0.312 | A | 0.014 | No |
| | Saturday | | | | | | | 10,574 | 0.310 | A | 10,659 | 0.313 | A | 0.003 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

⁴⁵ Source: *City of Lake Elsinore General Plan Update Draft Program EIR (August 2011)*.

TABLE 8-2 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS DAILY ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Time Period | Yr. 2040 Type of Arterial | LOS E Capacity ⁴⁶ (VPD) | Lanes | Existing Traffic Conditions | | | Year 2040 With Adopted Specific Plan Traffic Conditions | | | Year 2040 With ELSP Project Buildout Traffic Conditions | | | (6) Adverse Condition | |
|---|-------------|---------------------------|------------------------------------|-------|--|-----------|-----|---|-----------|-----|---|-----------|-----|-----------------------|---------|
| | | | | | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | Daily Volume | V/C Ratio | LOS | V/C Inc. | Yes/ No |
| 31. Diamond Drive, between Olive Street and Cereal Street | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 7,005 | 0.205 | A | 5,248 | 0.154 | A | -0.051 | No |
| | Saturday | | | | | | | 7,437 | 0.218 | A | 5,089 | 0.149 | A | -0.069 | No |
| 32. Bundy Canyon Road, between Corydon Road and Mission Trail | Weekday | Major | 34,100 | 4D | Segment Does Not Exist Under Existing Traffic Conditions | | | 20,093 | 0.589 | A | 16,885 | 0.495 | A | -0.094 | No |
| | Saturday | | | | | | | 21,117 | 0.619 | B | 16,700 | 0.490 | A | -0.129 | No |

Notes:

- VPD = Vehicles Per Day
- D = Divided; U = Undivided
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions
- **Bold “V/C”/LOS values** indicate adverse service levels based on the LOS standards mentioned in this report

⁴⁶ Source: *City of Lake Elsinore General Plan Update Draft Program EIR* (August 2011).

TABLE 8-3
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Type of Arterial | Approach | Time Period | Link Capacity (VPHPL) | Lanes | Total Link Capacity (VPH) | (4) Year 2040 With ELSP Project Buildout Traffic Conditions | | |
|---|------------------|------------|-----------------|-----------------------|-------|---------------------------|---|-----------|-----|
| | | | | | | | Peak Hour Volume | V/C Ratio | LOS |
| 1. Grape Street, <i>east of Railroad Canyon Road</i> | Major | Eastbound | Weekday AM | 1,600 | 2 | 3200 | 1,159 | 0.362 | A |
| | | | Weekday PM | 1,600 | 2 | 3200 | 1,393 | 0.435 | A |
| | | | Saturday Midday | 1,600 | 2 | 3200 | 2,320 | 0.725 | C |
| | | Westbound | Weekday AM | 1,600 | 2 | 3200 | 1,377 | 0.430 | A |
| | | | Weekday PM | 1,600 | 2 | 3200 | 1,695 | 0.530 | A |
| | | | Saturday Midday | 1,600 | 2 | 3200 | 1,889 | 0.590 | A |
| 22. Mission Trail, <i>between Bundy Canyon Road and Palomar Street</i> | Collector | Northbound | Weekday AM | 1,600 | 1 | 1600 | 764 | 0.478 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 666 | 0.416 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 581 | 0.363 | A |
| | | Southbound | Weekday AM | 1,600 | 1 | 1600 | 632 | 0.395 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 803 | 0.502 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 798 | 0.499 | A |

Notes:

- VPHPL = Vehicles Per Hour Per Lane
- VPH = Vehicles Per Hour
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions

TABLE 8-3 (CONTINUED)
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR ROADWAY SEGMENT CAPACITY ANALYSIS SUMMARY

| Key Roadway Segment | Type of Arterial | Approach | Time Period | Link Capacity (VPHPL) | Lanes | Total Link Capacity (VPH) | (4) Year 2040 With ELSP Project Buildout Traffic Conditions | | |
|--|------------------|-----------|-----------------|-----------------------|-------|---------------------------|---|-----------|-----|
| | | | | | | | Peak Hour Volume | V/C Ratio | LOS |
| 23. Palomar Street, between Corydon Road and Mission Trail | Collector | Eastbound | Weekday AM | 1,600 | 1 | 1600 | 791 | 0.494 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 604 | 0.378 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 985 | 0.616 | B |
| | | Westbound | Weekday AM | 1,600 | 1 | 1600 | 634 | 0.396 | A |
| | | | Weekday PM | 1,600 | 1 | 1600 | 701 | 0.438 | A |
| | | | Saturday Midday | 1,600 | 1 | 1600 | 491 | 0.307 | A |

Notes:

- VPHPL = Vehicles Per Hour Per Lane
- VPH = Vehicles Per Hour
- V/C = Volume to Capacity Ratio
- LOS = Level of Service, please refer to *Table 3-3* for the LOS definitions

9.0 PLANNED AND RECOMMENDED IMPROVEMENTS

For those intersections and roadway segments where projected traffic volumes are expected to result in significant impacts, this report recommends improvements that change the intersection and/or roadway segments geometry to increase capacity. These capacity improvements involve roadway widening and/or re-striping to reconfigure (add lanes) roadways to specific approaches of a key intersection and/or roadway segments. The identified improvements are expected to:

- Address the impact of existing traffic, Project traffic and future non-project (ambient traffic growth and related projects) traffic, and
- Improve Levels of Service to an acceptable range and/or to pre-project conditions.

Figures 9-1, 9-2, and 9-3 present the planned and recommended improvements and intersection controls at the key study intersections for the Existing With ELSP Project Buildout, Year 2022 With ELSP Project Phase I, and Year 2040 With ELSP Project Buildout, respectively. These are discussed in more detail in the sections below.

9.1 Internal Network Planned Improvements

9.1.1 Project Phase I Planned Improvements

The planned improvements listed below are anticipated to be completed in conjunction with the Project Phase I development and have been assumed in the Year 2022 Without ELSP Project Phase I and Year 2022 With ELSP Project Phase I traffic conditions.

9.1.1.1 Intersections

The Project Phase I internal network planned improvements for intersections are as follows:

- Intersection 25. Diamond Drive at Olive Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no west leg. The northbound movement will consist of a through lane and a shared through-right-turn lane. The southbound movement will consist of a shared through-left-turn lane and through lane. The westbound movement will consist of a shared left-right-turn lane.
- Intersection 26. “A” Street at Olive Street: This intersection is proposed to be a roundabout three-legged intersection with no north leg. The roundabout will consist of one lane and each leg will have one entry lane and one exit lane. “A” Street and Olive Street are both proposed to be two lane collector roads.
- Intersection 27. “A” Street at Victorian Lane: This intersection is proposed to be a roundabout three-legged intersection with no west leg. The roundabout will consist of one lane and each leg will have one entry lane and one exit lane. “A” Street and Victorian Lane are both proposed to be two lane collector roads.
- Intersection 28. “A” Street at Cereal Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no south leg. The southbound movement will consist of a shared left-right-turn lane. The eastbound movement will

consist of a shared through-left-turn lane and through lane. The westbound movement will consist of a through lane and a shared through-right-turn lane.

9.1.1.2 Roadway Segments

The Project Phase I internal network planned improvements for roadway segments are as follows:

- Roadway Segment 27. Sylvester Street, between Lucerne Street and Diamond Drive: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
- Roadway Segment 28. Lucerne Street, between Sylvester Street and Cereal Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
- Roadway Segment 29. Cereal Street, between Lucerne Street and Stoneman Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
- Roadway Segment 30. Cereal Street between Stoneman Street and Diamond Drive: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
- Roadway Segment 31. Diamond Drive, between Olive Street and Cereal Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.

9.1.2 Project Buildout Planned Improvements

In addition to the planned improvements related to Project Phase I development, the planned improvements listed below are anticipated to be completed in conjunction with the Project Buildout development and have been assumed in the Existing With ELSP Project Buildout, Year 2040 With Adopted Specific Plan, Year 2040 With ELSP Project Buildout traffic conditions.

9.1.2.1 Intersections

The Project Buildout internal network planned improvements for intersections are as follows:

- Intersection 25. Diamond Drive at Olive Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no west leg. The northbound movement will consist of a through lane and a shared through-right-turn lane. The southbound movement will consist of a shared through-left-turn lane and through lane. The westbound movement will consist of a shared left-right-turn lane.
- Intersection 26. “A” Street at Olive Street: This intersection is proposed to be a roundabout three-legged intersection with no north leg. The roundabout will consist of one lane and each leg will have one entry lane and one exit lane. “A” Street and Olive Street are both proposed to be two lane collector roads.
- Intersection 27. “A” Street at Victorian Lane: This intersection is proposed to be a roundabout three-legged intersection with no west leg. The roundabout will consist of one lane and each leg will have one entry lane and one exit lane. “A” Street and Victorian Lane are both proposed to be two lane collector roads.
- Intersection 28. “A” Street at Cereal Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no south leg. The southbound

movement will consist of a shared left-right-turn lane. The eastbound movement will consist of a shared through-left-turn lane and through lane. The westbound movement will consist of a through lane and a shared through-right-turn lane.

- Intersection 29. Lucerne Street at Sylvester Street: This intersection is proposed to be a one-way stop-controlled three-legged intersection with no west leg. The northbound movement will consist of a through lane and a shared through-right-turn lane. The southbound movement will consist of a shared through-left-turn lane and through lane. The westbound movement will consist of an exclusive left-turn lane and an exclusive right-turn lane.
- Intersection 30. Stoneman Street at Cereal Street: This intersection is proposed to be a three phase signalized three-legged intersection with no north leg. The northbound movement will consist of an exclusive left-turn lane and an exclusive right-turn lane. The eastbound movement will consist of a through lane and a shared through-right-turn lane. The westbound movement will consist of an exclusive left-turn lane and two (2) through lanes.

9.1.2.2 Roadway Segments

The Project Buildout internal network planned improvements for roadway segments are as follows:

- Roadway Segment 27. Sylvester Street, between Lucerne Street and Diamond Drive: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
- Roadway Segment 28. Lucerne Street, between Sylvester Street and Cereal Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
- Roadway Segment 29. Cereal Street, between Lucerne Street and Stoneman Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
- Roadway Segment 30. Cereal Street between Stoneman Street and Diamond Drive: This roadway segment is proposed to be a major arterial with four (4) lanes divided.
- Roadway Segment 31. Diamond Drive, between Olive Street and Cereal Street: This roadway segment is proposed to be a major arterial with four (4) lanes divided.

9.2 External Network Planned Improvements

9.2.1 Existing With East Lake Specific Plan Project Buildout Planned Improvements

The planned improvements listed below are anticipated to be completed in conjunction with the Project Buildout and have been assumed in the Existing With ELSP Project Buildout traffic conditions.

9.2.1.1 Intersections

The Existing With ELSP Project Buildout external network planned improvements for intersections are as follows:

- Intersection 11. Mission Trail at Olive Street: Add a west leg and provide the eastbound approach with an exclusive eastbound left-turn lane, and a shared through-right-turn lane, and provide a lane for the westbound departure. Restripe the west leg to provide a shared through-right-turn lane. Restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane. Restripe the southbound approach to provide a shared through-right-turn lane. Modify the existing traffic signal to provide a five phase signal.

9.2.1.2 Roadway Segments

There are no Existing With ELSP Project Buildout external network planned improvements for roadway segments.

9.2.2 Year 2022 Planned Improvements

The planned improvements listed below are anticipated to be completed in Year 2022 and have been assumed in the Year 2022 Without ELSP Project Phase I and Year 2022 With ELSP Project Phase I traffic conditions.

9.2.2.1 Intersections

The Year 2022 external network planned improvements for intersections are as follows:

- Intersection 1. Railroad Canyon Road at Summerhill Road/Grape Street: Remove a northbound left-turn lane and the east leg crosswalk. Widen and/or restripe the westbound approach of Grape Street to provide an exclusive right-turn lane. Modify the existing traffic signal as necessary. These improvements are in conjunction with the Railroad Canyon Road Interchange Project.
- Intersection 2. Railroad Canyon Road at I-15 NB Ramps: This intersection will not exist upon completion of the Railroad Canyon Road Interchange Project.
- Intersection 3. Diamond Drive at I-15 SB Ramps: Widen and/or restripe the southbound approach to provide a second exclusive left-turn lane as well as a third exclusive through lane. Widen and/or restripe the southbound departure to include a third lane. Widen and/or restripe the eastbound departure to include two (2) additional on-ramp lanes. Modify the existing traffic signal as necessary. These improvements are in conjunction with the Railroad Canyon Road Interchange Project.
- Intersection 5. Lucerne Street at Lakeshore Drive: Widen and/or restripe Lucerne Street to provide an exclusive northbound left-turn lane.
- Intersection 11. Mission Trail at Olive Street: Add a west leg and provide the eastbound approach with an exclusive eastbound left-turn lane, and a shared through-right-turn lane, and provide a lane for the westbound departure. Restripe the west leg to provide a shared through-right-turn lane. Restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane. Restripe the southbound approach to provide a shared through-right-turn lane. Stripe crosswalks

on the north and east legs. Modify the existing traffic signal to provide a five phase signal with protective left-turn phasing on Mission Trail.

- Intersection 12. Mission Trail at Victorian Lane: Widen and/or restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive southbound left-turn lane. Stripe crosswalks on all four legs. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.
- Intersection 15. Corydon Road at Cereal Street: Add an east leg and provide the westbound approach with an exclusive left-turn lane, a through lane, a shared through-right-turn lane, and provide the eastbound departure with two (2) lanes. Widen and/or restripe the eastbound approach with an exclusive left-turn lane, a through lane, and a shared through-right-turn lane. Widen and/or restripe the westbound departure with a second lane. Restripe the northbound approach of Corydon Road to provide a shared through-right-turn lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane. Stripe crosswalks on all four legs. Install an eight phase traffic signal.
- Intersection 16. Mission Trail at Bundy Canyon Road: Widen and/or restripe the eastbound approach of Bundy Canyon Road to provide an exclusive left-turn lane, a through lane, and a shared through-right-turn lane. Widen and/or restripe the westbound departure with a second lane. Widen and/or restripe the westbound approach to provide two (2) through lanes. Modify the existing traffic signal to provide an eight phase signal.
- Intersection 24. Grape Street at I-15 NB Ramps: Add a west leg and provide the eastbound approach with two (2) exclusive left-turn lanes, an exclusive right-turn lane, and provide the westbound departure with three (3) on-ramp lanes. Widen and/or restripe the northbound approach on Grape Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive right-turn lane. Install a three phase traffic signal.

9.2.2.2 Roadway Segments

The Year 2022 external network planned improvements for roadway segments are as follows:

- Roadway Segment 3. Lucerne Street, south of Lakeshore Drive: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided.
- Roadway Segment 18. Cereal Street, west of Corydon Road: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided.
- Roadway Segment 32. Bundy Canyon Road, between Corydon Road and Mission Trail: Extend Bundy Canyon Road from Mission Trail to Corydon Road with four (4) lanes divided.

9.2.3 Year 2040 Planned Improvements

The planned improvements listed below are anticipated to be completed in Year 2040 and have been assumed in the Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout traffic conditions.

9.2.3.1 Intersections

The Year 2040 external network planned improvements for intersections are as follows:

- Intersection 1. Railroad Canyon Road at Summerhill Road/Grape Street: Remove a northbound left-turn lane and the east leg crosswalk. Widen and/or restripe the westbound approach of Grape Street to provide an exclusive right-turn lane. Modify the existing traffic signal as necessary. These improvements are in conjunction with the Railroad Canyon Road Interchange Project.
- Intersection 2. Railroad Canyon Road at I-15 NB Ramps: This intersection will not exist upon completion of the Railroad Canyon Road Interchange Project.
- Intersection 3. Diamond Drive at I-15 SB Ramps: Widen and/or restripe the southbound approach to provide a second exclusive left-turn lane as well as a third exclusive through lane. Widen and/or restripe the southbound departure to include a third lane. Widen and/or restripe the eastbound departure to include two (2) additional on-ramp lanes. Modify the existing traffic signal as necessary. These improvements are in conjunction with the Railroad Canyon Road Interchange Project.
- Intersection 5. Lucerne Street at Lakeshore Drive: Widen and/or restripe Lucerne Street to provide an exclusive northbound left-turn lane. Widen and/or restripe the eastbound approach on Lakeshore Drive to provide two (2) exclusive through lanes. Widen and/or restripe the westbound departure to provide two (2) additional lanes. Widen and/or restripe the westbound approach to provide two (2) exclusive through lanes. Widen and/or restripe the eastbound departure to provide two (2) additional lanes. Stripe crosswalks on all legs. Install three phase traffic signal.
- Intersection 6. Diamond Drive at Lakeshore Drive/Mission Trail: Widen and/or restripe the eastbound approach on Lakeshore Drive to provide one (1) additional through lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach on Mission Trail to provide one (1) additional through lane. Widen and/or restripe eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 8. Mission Trail at Campbell Street: Widen and/or restripe the northbound approach on Mission Trail to provide one (1) additional through lane. Widen and/or restripe the southbound departure to provide a third lane. Widen and/or restripe the southbound approach to provide one (1) additional through lane. Widen and/or restripe the northbound departure to provide a third lane.
- Intersection 10. Mission Trail at Malaga Road: Widen and/or restripe the northbound approach on Mission Trail to provide one (1) additional through lane. Widen and/or

restripe the southbound departure to provide a third lane. Widen and/or restripe the southbound approach to provide one (1) additional through lane. Widen and/or restripe the northbound departure to provide a third lane. Modify the existing traffic signal as necessary.

- Intersection 11. Mission Trail at Olive Street: Add a west leg and provide the eastbound approach with an exclusive eastbound left-turn lane, and a shared through-right-turn lane, and provide a lane for the westbound departure. Restripe the west leg to provide a shared through-right-turn lane. Widen and/or restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane and a second through lane. Widen and/or restripe the southbound departure to provide a third lane. Widen and/or restripe the southbound approach to provide a shared through-right-turn lane and a second through lane. Widen and/or restripe the northbound departure with a third lane. Stripe crosswalks on the north and east legs. Modify the existing traffic signal to provide a five phase signal with protective left-turn phasing on Mission Trail.
- Intersection 12. Mission Trail at Victorian Lane: Widen and/or restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane and a second through lane. Widen and/or restripe the southbound departure to provide a third lane. Widen and/or restripe the southbound approach to provide an exclusive southbound left-turn lane and a second through lane. Widen and/or restripe the northbound departure to provide a third lane. Stripe crosswalks on all four legs. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.
- Intersection 13. Mission Trail at Lemon Street: Widen and/or restripe the northbound approach of Mission Trail to provide a third through lane. Widen and/or restripe the southbound departure to provide a third lane. Widen and/or restripe the southbound approach to provide a third through lane. Widen and/or restripe the northbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 15. Corydon Road at Cereal Street: Add an east leg and provide the westbound approach with an exclusive left-turn lane, a through lane, and a shared through-right-turn lane, and provide the eastbound departure with two (2) lanes. Widen and/or restripe the eastbound approach with an exclusive left-turn lane, a through lane, and a shared through-right-turn lane. Widen and/or restripe the westbound departure with a second lane. Widen and/or restripe the northbound approach of Corydon Road to provide a through lane and a shared through-right-turn lane. Widen and/or restripe the southbound departure with a second lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane and a through lane. Widen and/or restripe the northbound departure with a second lane. Stripe crosswalks on all four legs. Install an eight phase traffic signal.
- Intersection 16. Mission Trail at Bundy Canyon Road: Widen and/or restripe the eastbound approach of Bundy Canyon Road to provide an exclusive left-turn lane, a

through lane, and a shared through-right-turn lane. Widen and/or restripe the westbound departure with a second lane. Widen and/or restripe the westbound approach to provide two (2) through lanes. Modify the existing traffic signal to provide an eight phase signal.

- Intersection 17. Orange Street at Bundy Canyon Road: Widen and/or restripe the northbound approach on Orange Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane and a shared through-right-turn lane. Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a second through lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify existing traffic signal to provide an eight phase signal.
- Intersection 18. I-15 SB Ramps at Bundy Canyon Road: Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a second through lane. Widen and/or restripe the westbound departure to provide a third lane. Please note that the addition of a third westbound departure lane would not result in a trap lane at the intersection of Orange Street at Bundy Canyon Road due to an additional westbound through lane included as a planned improvement at that location. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 19. I-15 NB Ramps at Bundy Canyon Road: Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a third through lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 20. Corydon Road at Palomar Street: Widen and/or restripe the northbound approach on Corydon Road to provide a second through lane. Widen and/or restripe the northbound departure to provide a second lane. Modify the existing traffic signal as necessary.
- Intersection 21. Mission Trail at Palomar Street: Stripe crosswalks on all legs. Install a three phase traffic signal.
- Intersection 22. Stoneman Street at Grand Avenue: Widen and/or restripe the eastbound approach on Grand Avenue to provide a through lane. Widen and/or restripe the eastbound departure to provide a second lane. Stripe crosswalks on all legs. Install a five phase traffic signal with protective left-turn phasing for Grand Avenue.

- Intersection 23. Corydon Road at Grand Avenue: Widen and/or restripe the eastbound approach on Grand Avenue to provide a through lane. Widen and/or restripe the westbound departure to provide a second lane. Widen and/or restripe the westbound approach to provide a through lane. Widen and/or restripe the eastbound departure to provide a second lane. Modify the existing traffic signal as necessary.
- Intersection 24. Grape Street at I-15 NB Ramps: Add a west leg and provide the eastbound approach with two (2) exclusive left-turn lanes, an exclusive right-turn lane, and provide the westbound departure with three (3) on-ramp lanes. Widen and/or restripe the northbound approach on Grape Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive right-turn lane. Install a three phase traffic signal.

9.2.3.2 Roadway Segments

The Year 2040 external network planned improvements for roadway segments are as follows:

- Roadway Segment 3. Lucerne Street, south of Lakeshore Drive: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided. Extend south to Sylvester Street.
- Roadway Segment 7. Mission Trail, between Diamond Drive and Campbell Street: Widen from a major arterial with four (4) lanes divided to an urban arterial with six (6) lanes divided.
- Roadway Segment 8. Mission Trail, between Campbell Street and Malaga Road: Widen from a major arterial with four (4) lanes divided to an urban arterial with six (6) lanes divided.
- Roadway Segment 12. Mission Trail, between Malaga Road and Olive Street: Widen from a major arterial with four (4) lanes divided to an urban arterial with six (6) lanes divided.
- Roadway Segment 13. Olive Street, between Mission Trail and Grape Street: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided.
- Roadway Segment 14. Mission Trail, between Olive Street and Victorian Lane: Widen from a secondary arterial with four (4) lanes undivided to an urban arterial with six (6) lanes divided.
- Roadway Segment 15. Mission Trail, between Victorian Lane and Lemon Street: Widen from a secondary arterial with four (4) lanes undivided to an urban arterial with six (6) lanes divided.
- Roadway Segment 17. Corydon Road, between Mission Trail and Cereal Street: Widen from a divided collector with two (2) lanes divided to a major arterial with four (4) lanes divided.

- Roadway Segment 18. Cereal Street, west of Corydon Road: Widen from a collector with two (2) lanes undivided to a major arterial with four (4) lanes divided.
- Roadway Segment 20. Bundy Canyon Road, between Mission Trail and I-15 SB Ramps: Widen from a collector with two (2) lanes undivided to an urban arterial with six (6) lanes divided.
- Roadway Segment 21. Corydon Road, between Cereal Street and Palomar Street: Widen from a divided collector with two (2) lanes divided to a major arterial with four (4) lanes divided.
- Roadway Segment 24. Stoneman Street, north of Grand Avenue: Extend north to Cereal Street.
- Roadway Segment 26. Corydon Road, between Palomar Street and Grand Avenue: Widen from a divided collector with two (2) lanes divided to a major arterial with four (4) lanes divided.
- Roadway Segment 32. Bundy Canyon Road, between Corydon Road and Mission Trail: Extend Bundy Canyon Road from Mission Trail to Corydon Road with four (4) lanes divided.

9.3 Recommended Improvements

9.3.1 Existing With East Lake Specific Plan Project Buildout Traffic Conditions

9.3.1.1 Intersections

The results of the Existing With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed Project Buildout will significantly impact six (6) key study intersections. The remaining key study intersections are forecast to operate at acceptable levels of service under the Existing With ELSP Project Buildout traffic conditions. The improvements listed below have been identified to address the traffic impacts at the intersections significantly impacted by the Existing With ELSP Project Buildout traffic:

- Intersection 5. Lucerne Street at Lakeshore Drive: Widen and/or restripe Lucerne Street to provide an exclusive northbound left-turn lane. Stripe crosswalks on all legs. Install three phase traffic signal.
- Intersection 6. Diamond Drive at Lakeshore Drive/Mission Trail: Modify the existing traffic signal to provide overlap phasing for the westbound right-turn movement. No additional physical improvements are feasible to achieve an acceptable level of service LOS D or better. Hence the Project's impact at this key intersection is considered unavoidable.
- Intersection 12. Mission Trail at Victorian Lane: Widen and/or restripe the northbound approach of Mission Trail to provide an exclusive northbound left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive southbound left-turn lane. Stripe crosswalks on all four legs. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.

- Intersection 17. Orange Street at Bundy Canyon Road: Widen and/or restripe the northbound approach on Orange Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane and a shared through-right-turn lane. Modify existing traffic signal to provide an eight phase signal.
- Intersection 18. I-15 SB Ramps at Bundy Canyon Road: Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a second through lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 22. Stoneman Street at Grand Avenue: Stripe crosswalks on all legs. Install a five phase traffic signal with protective left-turn phasing for Grand Avenue.

9.3.1.2 Roadway Segments

The results of the roadway segment analyses for Existing With ELSP Project Buildout traffic conditions indicate that the proposed Project is not forecast to have a significant impact at any of the thirty-one (31) key roadway segments (roadway segment 32 does not exist in Existing With ELSP Project Buildout traffic conditions). As there are no significant impacts, no traffic mitigation measures are required under this traffic scenario.

9.3.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

9.3.2.1 Intersections

The results of the Year 2022 With ELSP Project Phase I traffic conditions level of service analyses indicate that the proposed Project Phase I will significantly impact eleven (11) key study intersections. The remaining key study intersections are forecast to operate at acceptable levels of service under the Year 2022 With ELSP Project Phase I traffic conditions. The improvements listed below have been identified to address the traffic impacts at the intersections significantly impacted by the Year 2022 With ELSP Project Phase I traffic:

- Intersection 1. Railroad Canyon Road at Summerhill Road/Grape Street: Widen and/or restripe the eastbound approach of Summerhill Road to provide a second through lane and convert the shared through-right lane into an exclusive through lane. Widen and/or restripe the southbound approach to provide a second left-turn lane. Widen and/or restripe the northbound departure to provide a third lane. Widen and/or restripe the northbound movement to provide a third through lane and to convert the northbound right-turn lane into a free right-turn movement. Modify the existing traffic signal to be an eight phase signal and to provide overlap phasing for the westbound right-turn movement.
- Intersection 4. Diamond Drive at Auto Center Drive/Casino Drive: Widen the southbound approach of Diamond Drive to provide a second through lane. However, this mitigation is infeasible due to the surrounding parcels preventing the additional

needed right-of-way. Hence the Project's impact at this key intersection is considered unavoidable.

- Intersection 6. Diamond Drive at Lakeshore Drive/Mission Trail: Modify the existing traffic signal to provide overlap phasing for the westbound right-turn movement. No additional physical improvements are feasible to achieve an acceptable level of service LOS D or better. Hence the Project's impact at this key intersection is considered unavoidable.
- Intersection 7. Diamond Drive at Campbell Street: Restrict southbound left-turn movement and westbound left-turn movement. Please note that the recommended improvement is for Saturday Midday peak hour only.
- Intersection 8. Mission Trail at Campbell Street: Stripe crosswalks on the east and west leg. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.
- Intersection 9. Diamond Drive at Malaga Road: Restripe the southbound approach on Diamond Drive to provide a second exclusive left-turn lane. Widen and/or restripe the eastbound approach to provide a second exclusive left-turn lane. Modify the existing traffic signal as necessary.
- Intersection 15. Corydon Road at Cereal Street: Widen and/or restripe the northbound approach on Corydon Road to provide a through lane. Widen and/or restripe the northbound departure to provide a second lane. Modify the existing traffic signal as necessary.
- Intersection 17. Orange Street at Bundy Canyon Road: Widen and/or restripe the northbound approach on Orange Street to provide an exclusive left-turn lane. Widen and/or restripe the southbound approach to provide an exclusive left-turn lane and a shared through-right-turn lane. Modify existing traffic signal to provide an eight phase signal.
- Intersection 18. I-15 SB Ramps at Bundy Canyon Road: Widen and/or restripe the southbound approach to provide an exclusive right-turn lane. Widen and/or restripe the southbound departure to provide a second on-ramp lane. Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide a second through lane and an exclusive right-turn lane. Widen and/or restripe the westbound departure to provide a third lane. Widen and/or restripe the westbound approach to provide a second through lane. Widen and/or restripe the eastbound departure to provide a third lane. Modify the existing traffic signal as necessary.
- Intersection 22. Stoneman Street at Grand Avenue: Stripe crosswalks on all legs. Install a five phase traffic signal with protective left-turn phasing for Grand Avenue.
- Intersection 24. Grape Street at I-15 NB Ramps: Widen and/or restripe the southbound approach on Grape Street to convert the southbound right-turn lane into a free right-turn movement. Modify the existing traffic signal as necessary.

9.3.2.2 Roadway Segments

The results of the roadway segment analyses for Year 2022 With ELSP Project Phase I traffic conditions indicate that the proposed Project is not forecast to have a significant impact at any of the thirty-two (32) key roadway segments. As there are no significant impacts, no traffic mitigation measures are required under this traffic scenario.

9.3.3 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

9.3.3.1 Intersections

The results of the Year 2040 With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed Project Buildout will significantly impact eleven (11) key study intersections. The remaining key study intersections are forecast to operate at acceptable levels of service under the Year 2040 With ELSP Project Buildout traffic conditions. The improvements listed below have been identified to address the traffic impacts at the intersections significantly impacted by the Year 2040 With ELSP Project Buildout traffic:

- Intersection 1. Railroad Canyon Road at Summerhill Road/Grape Street: Widen and/or restripe the eastbound approach of Summerhill Road to provide a second through lane and convert the shared through-right lane into an exclusive through lane. Widen and/or restripe the southbound approach to provide a second left-turn lane. Widen and/or restripe the northbound departure to provide a third lane. Widen and/or restripe the northbound movement to provide a third through lane and to convert the northbound right-turn lane into a free right-turn movement. Modify the existing traffic signal to be an eight phase signal and to provide overlap phasing for the westbound right-turn movement.
- Intersection 3. Railroad Canyon Road at I-15 SB Ramps: Widen and/or restripe the northbound approach on Railroad Canyon Road to provide an exclusive right-turn lane. Widen and/or restripe the eastbound approach on the off-ramp to provide a second exclusive right-turn lane. Modify the existing traffic signal as necessary.
- Intersection 4. Diamond Drive at Auto Center Drive/Casino Drive: Widen the northbound approach of Diamond Drive to provide a second exclusive left-turn lane. Widen the southbound approach to provide an exclusive right-turn lane and third through lane. Widen the eastbound approach to provide a second exclusive left-turn lane and right-turn lane. Install a pedestrian refuge on the south leg. Modify the existing traffic signal to provide eight phasing with overlap phases for the southbound and eastbound right-turn. However, this mitigation is infeasible due to the surrounding parcels preventing the additional needed right-of-way. Hence the Project's impact at this key intersection is considered unavoidable.
- Intersection 6. Diamond Drive at Lakeshore Drive/Mission Trail: Modify the existing traffic signal to provide overlap phasing for the westbound right-turn movement. No additional physical improvements are feasible to achieve an acceptable level of service LOS D or better. Hence the Project's impact at this key intersection is considered unavoidable.

- Intersection 7. Diamond Drive at Campbell Street: Restrict southbound left-turn movement and westbound left-turn movement. Please note that the recommended improvement is for Saturday Midday peak hour only.
- Intersection 8. Mission Trail at Campbell Street: Stripe crosswalks on the east and west leg. Install a five phase traffic signal with protective left-turn phasing on Mission Trail.
- Intersection 9. Diamond Drive at Malaga Road: Restripe the southbound approach on Diamond Drive to provide a second exclusive left-turn lane. Widen and/or restripe the eastbound approach to provide a second exclusive left-turn lane. Modify the existing traffic signal as necessary. Please note that the second eastbound left-turn lane is only needed in the Year 2022 With ELSP Project Phase I traffic conditions.
- Intersection 18. I-15 SB Ramps at Bundy Canyon Road: Widen and/or restripe the southbound approach to provide an exclusive right-turn lane. Widen and/or restripe the eastbound approach on Bundy Canyon Road to provide an exclusive right-turn lane. Widen and/or restripe the southbound departure to provide a second on-ramp lane. Modify the existing traffic signal as necessary.
- Intersection 21. Mission Trail at Palomar Street: Widen and/or restripe the northbound approach on Mission Trail to provide a second exclusive left-turn lane. Widen and/or restripe the westbound departure to provide a second lane. Modify the traffic signal to provide overlap phasing for the eastbound right-turn movement.
- Intersection 22. Stoneman Street at Grand Avenue: Widen and/or restripe the northbound approach on Stoneman Street to provide an exclusive left-turn lane. Modify the existing traffic signal as necessary.
- Intersection 24. Grape Street at I-15 NB Ramps: Widen and/or restripe the southbound approach on Grape Street to convert the southbound right-turn lane into a free right-turn movement. Modify the existing traffic signal as necessary.

9.3.3.2 Roadway Segments

The results of the roadway segment analyses for Year 2040 With ELSP Project Buildout traffic conditions indicate that the proposed Project is not forecast to have a significant impact at any of the thirty-two (32) key roadway segments. As there are no significant impacts, no traffic mitigation measures are required under this traffic scenario.




FIGURE 9-1

EXISTING WITH ELS Project BUILDOUT
PLANNED AND RECOMMENDED IMPROVEMENTS
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE




FIGURE 9-2

YEAR 2022 WITH ELS Project Phase I
PLANNED AND RECOMMENDED IMPROVEMENTS
EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE




FIGURE 9-3

YEAR 2040 WITH ELS Project Buildout
 PLANNED AND RECOMMENDED IMPROVEMENTS
 EAST LAKE SPECIFIC PLAN EIR, LAKE ELSINORE

10.0 TRAFFIC SIGNAL WARRANT ANALYSIS

The level of service analyses at the key unsignalized impacted study intersections that are recommended to be signalized are supplemented with an assessment of the need for signalization of the intersections. This assessment is made on the basis of signal warrant criteria adopted by Caltrans. For this study, the need for signalization is assessed on the basis of the peak-hour traffic signal warrant. Warrant #3 described in the *California Manual on Uniform Traffic Control Devices (MUTCD)*. Warrant #3 has two parts: 1) Part A evaluates peak hour vehicle delay for traffic on the minor street approach with the highest delay and 2) Part B evaluates peak-hour traffic volumes on the major and minor streets. This method provides an indication of whether peak-hour traffic conditions or peak-hour traffic volume levels are, or would be, sufficient to justify installation of a traffic signal. Other traffic signal warrants are available, however, they cannot be checked under future conditions (Without Project/Build-out without and with Project) because they rely on data for which forecasts are not available (such as accidents, pedestrian volume, and four- or eight-hour vehicle volumes).

The decision to install a traffic signal should not be based purely on the warrants alone. Instead, the installation of a signal should be considered and further analysis performed when one or more of the warrants are satisfied. Additionally, engineering judgment is exercised on a case-by-case basis to evaluate the effect a traffic signal will have on certain types of accidents and traffic conditions at the subject intersection as well as at adjacent intersections.

10.1 Existing With East Lake Specific Plan Project Buildout Traffic Conditions

The results of the peak-hour traffic signal warrant analysis for the Existing With ELSP Project Buildout traffic conditions are summarized in column (1) of *Table 10-1*. The results indicate that the following key unsignalized impacted intersection has future traffic conditions that would exceed the volume thresholds of Warrant #3, Part A and Part B for the Weekday AM, Weekday PM and Saturday Midday peak hours:

- 5. Lucerne Street at Lakeshore Drive

The analysis and the recommended improvements show that the above-mentioned intersection in the Existing With ELSP Project Buildout traffic conditions is recommended to be signalized. With signalization of this intersection, which is warranted, this intersection is forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and Saturday Midday peak hours. Thus, it is concluded from *Table 10-1* that a traffic signal is justified at intersection #5, Lucerne Street at Lakeshore Drive.

The analysis and the recommended improvements show that intersections #12, Mission Trail at Victorian Lane, and #22, Stoneman Street at Grand Avenue, are recommended to be signalized. With signalization of these intersections, which is not warranted under any peak hours, these intersections are forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and Saturday Midday peak hours. Although these intersections do not meet signal

warrants, it is recommended these locations be signalized due to right-of-way restrictions and safety concerns.

The Existing With ELSP Project Buildout traffic conditions Traffic Signal Warrant Analysis worksheets are contained in *Appendix G*.

10.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

The results of the peak-hour traffic signal warrant analysis for the Year 2022 With ELSP Project Phase I traffic conditions are summarized in column (2) of *Table 10-1*. The results indicate that the following key unsignalized impacted intersection has future traffic conditions that would exceed the volume thresholds of Warrant #3, Part A and Part B for the Weekday AM and Weekday PM peak hours:

- 22. Stoneman Street at Grand Avenue

The analysis and the recommended improvements show that the above-mentioned intersection in the Year 2022 With ELSP Project Phase I traffic conditions is recommended to be signalized. With signalization of this intersection, which is warranted under the Weekday AM and PM peak hours, this intersection is forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and Saturday Midday peak hours. Thus, it is concluded from *Table 10-1* that a traffic signal is justified at intersection #22, Stoneman Street at Grand Avenue.

The analysis and the recommended improvements show that intersection #8, Mission Trail at Campbell Street, is recommended to be signalized. With signalization of this intersection, which is not warranted under any peak hours, these intersections are forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and Saturday Midday peak hours. Although this intersection does not meet signal warrants, it is recommended this location be signalized due to safety concerns.

The Year 2022 With ELSP Project Phase I traffic conditions Traffic Signal Warrant Analysis worksheets are contained in *Appendix G*.

10.3 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

The results of the peak-hour traffic signal warrant analysis for the Year 2040 With ELSP Project Buildout traffic conditions are summarized in column (3) of *Table 10-1*. The results indicate that the following key unsignalized impacted intersection has future traffic conditions that will not exceed the volume thresholds of Warrant #3, Part A and Part B for the Weekday AM, Weekday PM, or Saturday Midday peak hours:

- 8. Mission Trail at Campbell Street

The analysis and the recommended improvements show that the above-mentioned intersection in the Year 2040 With ELSP Project Buildout traffic conditions is recommended to be signalized. With signalization of this intersection, which is not warranted under any peak hours, this intersection is forecast to operate at an acceptable service level during the Weekday AM, Weekday PM and

Saturday Midday peak hours. Although this intersection does not meet signal warrants, the signalization of this intersection is consistent with the analysis performed in the currently Adopted Specific Plan and it is reasonable to assume that by Year 2040, along with the adjoining planned roadway widening along Mission Trail from 4 lanes to 6 lanes, a traffic signal will be installed at this location. Thus, it is concluded from *Table 10-1* that a traffic signal is justified at intersection #8, Mission Trail at Campbell Street.

The Year 2040 With ELSP Project Buildout traffic conditions Traffic Signal Warrant Analysis worksheets are contained in *Appendix G*.

TABLE 10-1
INTERSECTION TRAFFIC SIGNAL WARRANT ANALYSIS SUMMARY⁴⁷

| Key Intersection | Time Period | (1) Existing With ELSP Project Buildout Traffic Conditions | | (2) Year 2022 With ELSP Project Phase I Traffic Conditions | | (3) Year 2040 With ELSP Project Buildout Traffic Conditions | |
|--------------------------------------|-----------------|---|--------------------------------------|---|--------------------------------------|--|--------------------------------------|
| | | Part A of Warrant 3 Satisfied? | Part B of Warrant 3 Satisfied? | Part A of Warrant 3 Satisfied? | Part B of Warrant 3 Satisfied? | Part A of Warrant 3 Satisfied? | Part B of Warrant 3 Satisfied? |
| 5. Lucerne Street at Lakeshore Drive | Weekday AM | Yes | Yes | -- | -- | -- | -- |
| | Weekday PM | Yes | Yes | -- | -- | -- | -- |
| | Saturday Midday | Yes | Yes | -- | -- | -- | -- |
| 8. Mission Trail at Campbell Street | Weekday AM | -- | -- | No | No | No | No |
| | Weekday PM | -- | -- | No | No | No | No |
| | Saturday Midday | -- | -- | No | No | No | No |
| 12. Mission Trail at Victorian Lane | Weekday AM | No | No | -- | -- | -- | -- |
| | Weekday PM | No | No | -- | -- | -- | -- |
| | Saturday Midday | No | No | -- | -- | -- | -- |
| 22. Stoneman Street at Grand Avenue | Weekday AM | No | No | Yes | Yes | -- | -- |
| | Weekday PM | No | No | Yes | Yes | -- | -- |
| | Saturday Midday | No | No | No | No | -- | -- |

Notes:

- Signal Warrant checks based on Warrant 3, Part A - Peak-Hour Delay Warrant and Part B - Peak-Hour Volume Warrant contained in the *California MUTCD*.

⁴⁷ Appendix G contains the Traffic Signal Warrant Analysis worksheets for the key unsignalized impacted study intersections.

11.0 PROJECT FAIR SHARE ANALYSIS

The transportation impacts associated with the development of the proposed East Lake Specific Plan were determined based on the future conditions analysis with and without the proposed Project. The key study locations forecast to operate at adverse levels of service are discussed below. As such, the proposed Project's "fair share" of the recommended improvements has been calculated for the key study locations that are forecast to operate at adverse levels of service in the Existing With ELSP Project Buildout, Year 2022 With ELSP Project Phase I, and Year 2040 With ELSP Project Buildout traffic conditions.

11.1 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

11.1.1 *Intersections*

Table 11-1 presents the Weekday AM, Weekday PM, and Saturday Midday peak hours ELSP Project Phase I fair share percentages at the key study intersections that are forecast to operate at adverse levels of service in the Year 2022 With ELSP Project Phase I traffic conditions. As presented in **Table 11-1**, the first column (1) presents a total of all intersection peak hour movements for Existing conditions. The second column (2) presents traffic associated with Year 2022 Without ELSP Project Phase I conditions. The third column (3) presents Year 2022 With ELSP Project Phase I traffic. The fourth column (4) represents the ELSP Project Phase I fair share based on the following formula:

- Project Fair Share (4) = [Column (3) - Column (2)]/[Column (3) - Column (1)]*100

The ELSP Project Phase I fair share percentages (worse time period impacted) for the eleven (11) impacted intersections for the Existing With ELSP Project Phase I traffic conditions are shown below:

- | | |
|---|-----------------------|
| ▪ 1. Railroad Canyon Road at Summerhill Lane/Grape Street | 100.00% ⁴⁸ |
| ▪ 4. Diamond Drive at Casino Drive/Auto Center Drive | 32.01% ⁴⁹ |
| ▪ 6. Diamond Drive at Lakeshore Drive/Mission Trail | 100.00% ⁴⁸ |
| ▪ 7. Diamond Drive at Campbell Street | 27.41% |
| ▪ 8. Mission Trail at Campbell Street | 40.42% |
| ▪ 9. Diamond Drive at Malaga Road | 46.02% |
| ▪ 15. Croydon Road at Cereal Street | 61.60% |
| ▪ 17. Orange Street at Bundy Canyon Road | 48.01% |
| ▪ 18. I-15 SB Ramps at Bundy Canyon Road | 42.16% |
| ▪ 22. Stoneman Street at Grand Avenue | 18.62% |
| ▪ 24. Grape Street at I-15 Northbound Ramps | 5.54% |

⁴⁸ The mitigation at this intersection only mitigates up to pre-Project level. As such, the Project would be responsible for 100% of costs.

⁴⁹ The mitigation at this intersection is considered infeasible and is included for informational purposes only.

11.1.2 Roadway Segments

The results of the roadway segment analyses indicate that the proposed ELSP Project Phase I is not forecast to have a significant impact at any of the thirty-two (32) key roadway segments for the Existing With ELSP Project Buildout traffic conditions. As there are no significant impacts, no Project fair share calculation is needed.

11.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

11.2.1 Intersections

Table 11-2 presents the Weekday AM, Weekday PM, and Saturday Midday peak hours ELSP Project Buildout fair share percentages at the key study intersections that are forecast to operate at adverse levels of service in the Year 2040 With ELSP Project Buildout traffic conditions. As presented in *Table 11-2*, the first column (1) presents a total of all intersection peak hour movements for Existing conditions. The second column (2) presents traffic associated with Year 2040 Without ELSP Project Buildout conditions. The third column (3) presents Year 2040 With ELSP Project Buildout traffic. The fourth column (4) represents the ELSP Project Buildout fair share based on the following formula:

- Project Fair Share (4) = [Column (3) - Column (2)]/[Column (3) - Column (1)]*100

The ELSP Project Buildout fair share percentages (worse time period impacted) for the eleven (11) impacted intersections for the Existing With ELSP Project Buildout traffic conditions are shown below:

- 1. Railroad Canyon Road at Summerhill Lane/Grape Street 100.00%⁵⁰
- 3. Diamond Drive at I-15 Northbound Ramps 18.10%
- 4. Diamond Drive at Casino Drive/Auto Center Drive 21.54%⁵¹
- 6. Diamond Drive at Lakeshore Drive/Mission Trail 100.00%⁵⁰
- 7. Diamond Drive at Campbell Street 4.79%
- 8. Mission Trail at Campbell Street 34.65%
- 9. Diamond Drive at Malaga Road 13.99%
- 18. I-15 SB Ramps at Bundy Canyon Road 17.87%
- 21. Mission Trail at Palomar Street 12.72%
- 22. Stoneman Street at Grand Avenue 6.41%
- 24. Grape Street at I-15 Northbound Ramps 10.00%

11.2.2 Roadway Segments

The results of the roadway segment analyses indicate that the proposed ELSP Project Buildout is not forecast to have a significant impact at any of the thirty-two (32) key roadway segments for the Year

⁵⁰ The mitigation at this intersection only mitigates up to pre-Project level. As such, the Project would be responsible for 100% of costs.

⁵¹ The mitigation at this intersection is considered infeasible and is included for informational purposes only.

2040 With ELSP Project Buildout traffic conditions. As there are no significant impacts, no Project fair share calculation is needed.

TABLE 11-1
YEAR 2022 WITH ELSP PROJECT PHASE I TRAFFIC CONDITIONS INTERSECTION FAIR SHARE CONTRIBUTION

| Key Intersection | Impacted Time Period | Existing Traffic | (1) | (2) | (3) | (4) |
|---|----------------------|------------------|--|---|-----------------------|-----|
| | | | Year 2022 Without ELSP Project Phase I Traffic | Year 2022 With ELSP Project Phase I Traffic | | |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | AM | 4,470 | 4,985 | 5,480 | 100.00% ⁵² | |
| | PM | 4,689 | 5,367 | 5,893 | 100.00% ⁵² | |
| | Midday | 4,933 | 6,484 | 6,969 | 100.00% ⁵² | |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | Midday | 2,410 | 4,292 | 5,178 | 32.01% ⁵³ | |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | PM | 2,034 | 2,620 | 3,761 | 100.00% ⁵² | |
| | Midday | 2,372 | 4,351 | 5,457 | 100.00% ⁵² | |
| 7. Diamond Drive at Campbell Street | Midday | 403 | 2,265 | 2,968 | 27.41% | |
| | Midday | 1,534 | 1,876 | 2,108 | 40.42% | |
| 9. Diamond Drive at Malaga Road | Midday | 328 | 1,440 | 2,388 | 46.02% | |
| | AM | 1,122 | 1,516 | 2,148 | 61.60% | |
| 15. Croydon Road at Cereal Street | AM | 1,866 | 2,280 | 2,599 | 43.52% | |
| | PM | 1,845 | 2,302 | 2,724 | 48.01% | |
| | Midday | 1,417 | 2,588 | 2,888 | 20.39% | |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | AM | 2,348 | 2,765 | 3,069 | 42.16% | |
| | Midday | 1,744 | 2,904 | 3,190 | 19.78% | |
| 22. Stoneman Avenue at Grand Avenue | AM | 1,319 | 1,717 | 1,797 | 16.74% | |
| | PM | 1,492 | 1,986 | 2,099 | 18.62% | |
| 24. Grape Street at I-15 Northbound Ramps | Midday | 2,558 | 3,479 | 3,533 | 5.54% | |

Notes:

- Net Project Percent Increase (4) = [Column (3) – Column (2)] / [Column (3) – Column (1)]
- **Bold Project Fair Share Responsibility** is based on worse case

⁵² The mitigation at this intersection only mitigates up to pre-Project level. As such, the Project would be responsible for 100% of costs.

⁵³ The mitigation at this intersection is considered infeasible and is included for informational purposes only.

TABLE 11-2
YEAR 2040 WITH ELSP PROJECT BUILDOUT TRAFFIC CONDITIONS INTERSECTION FAIR SHARE CONTRIBUTION

| Key Intersection | Impacted Time Period | (1) | (2) | (3) | (4) |
|---|----------------------|------------------|---|--|-----------------------------------|
| | | Existing Traffic | Year 2040 Without ELSP Project Buildout Traffic | Year 2040 With ELSP Project Buildout Traffic | Project Fair Share Responsibility |
| 1. Railroad Canyon Road at Summerhill Lane/Grape Street | AM | 4,470 | 7,050 | 7,497 | 100.00%⁵⁴ |
| | PM | 4,689 | 7,955 | 8,568 | 100.00%⁵⁴ |
| | Midday | 4,933 | 9,169 | 9,813 | 100.00%⁵⁴ |
| 3. Diamond Drive at I-15 Southbound Ramps | Midday | 3,514 | 6,943 | 7,701 | 18.10% |
| 4. Diamond Drive at Casino Drive/Auto Center Drive | AM | 1,896 | 4,253 | 4,900 | 21.54%⁵⁵ |
| | PM | 2,102 | 5,432 | 6,291 | 20.51% ⁵³ |
| | Midday | 2,410 | 7,310 | 8,245 | 16.02% ⁵³ |
| 6. Diamond Drive at Lakeshore Drive/Mission Trail | AM | 1,591 | 3,797 | 4,556 | 100.00%⁵⁴ |
| | PM | 2,034 | 4,908 | 5,995 | 100.00%⁵⁴ |
| | Midday | 2,372 | 6,682 | 7,855 | 100.00%⁵⁴ |
| 7. Diamond Drive at Campbell Street | Midday | 403 | 3,722 | 3,889 | 4.79% |
| 8. Mission Trail at Campbell Street | PM | 1,200 | 2,125 | 2,575 | 32.73% |
| | Midday | 1,534 | 2,464 | 2,957 | 34.65% |
| 9. Diamond Drive at Malaga Road | Midday | 328 | 1,914 | 2,172 | 13.99% |
| 18. I-15 Southbound Ramps at Bundy Canyon Road | AM | 2,348 | 3,777 | 4,088 | 17.87% |
| | Midday | 1,744 | 3,746 | 4,064 | 13.71% |
| 21. Mission Trail at Palomar Street | AM | 991 | 2,491 | 2,639 | 8.98% |
| | PM | 873 | 2,444 | 2,673 | 12.72% |
| 22. Stoneman Avenue at Grand Avenue | AM | 1,319 | 3,041 | 3,159 | 6.41% |
| 24. Grape Street at I-15 Northbound Ramps | AM | 2,383 | 2,842 | 2,893 | 10.00% |
| | PM | 2,366 | 3,523 | 3,619 | 7.66% |
| | Midday | 2,558 | 4,565 | 4,663 | 4.66% |

Notes:

- Net Project Percent Increase (4) = [Column (3) – Column (2)] / [Column (3) – Column (1)]
- Bold Project Fair Share Responsibility** is based on worse case

⁵⁴ The mitigation at this intersection only mitigates up to pre-Project level. As such, the Project would be responsible for 100% of costs.

⁵⁵ The mitigation at this intersection is considered infeasible and is included for informational purposes only.

12.0 EXISTING CONDITIONS CALTRANS FACILITIES ANALYSIS

Caltrans requires the use of analysis methods provided in the Highway Capacity Manual (*HCM*) for the analysis of ramp intersections and basic freeway segments. Based on the *Caltrans Traffic Impact Study Guidelines, dated December 2002*, Caltrans endeavors to maintain a target LOS at the transition between LOS "C" and "D" on State highway facilities and *Caltrans District 8* has typically established that LOS D is the operating standard for all Caltrans facilities. However, Caltrans acknowledges that this may not always be feasible and recommends that the lead agency consult with Caltrans to determine the appropriate target LOS. If an existing State highway facility is operating at less than appropriate target LOS, the existing service level should be maintained.

Basic Freeway Segment Analysis for freeway mainlines was conducted for the following six (6) Caltrans freeway segments:

1. I-15 Northbound *from* Baxter Road to Bundy Canyon Road
2. I-15 Northbound *from* Bundy Canyon Road to Railroad Canyon Road
3. I-15 Northbound *from* Railroad Canyon Road to Main Street
4. I-15 Southbound *from* Main Street to Railroad Canyon Road
5. I-15 Southbound *from* Railroad Canyon Road to Bundy Canyon Road
6. I-15 Southbound *from* Bundy Canyon Road to Baxter Road

Additionally, Freeway Merge and Diverge Segment Analysis for ramp junctions was conducted for the following four (4) Caltrans freeway merge and diverge segments:

1. I-15 Northbound Off-Ramp *to* Railroad Canyon Road
2. I-15 Southbound On-Ramp *from* Railroad Canyon Road
3. I-15 Northbound Off-Ramp *to* Railroad Canyon Road
4. I-15 Southbound On-Ramp *from* Railroad Canyon Road

The City of Lake Elsinore and Caltrans is currently in the process of improving the Railroad Canyon Road and I-15 Interchange. Following the public review period of the Draft EIR/EIS, and considering public input, the Riverside County Transportation Commission (RCTC) and Caltrans have identified Alternative 2 as the preferred project alternative. Alternative 2 is split into two phases, both of which are anticipated to be completed by Year 2022 and thus is incorporated in the Year 2022 and Year 2040 analysis. Phase I includes reconstructing/widening Railroad Canyon Road under crossing from 4 lanes to 6 lanes from Summerhill Drive/Grape Street to Casino Road, replacing the existing northbound ramps off of Railroad Canyon Road with hook ramps off of Grape Street, and adding ramp acceleration/deceleration lanes for both the northbound and southbound ramps. Phase II includes the construction of a full interchange at Franklin Street and the I-15, adding auxiliary lanes from the Franklin Street Interchange to the Main Street Interchange as well as to the Railroad Canyon Road Interchange for both the northbound and southbound directions,

realign/widen the Main Street southbound on-ramp from 1 lane to 2 lanes, and construct a new frontage road on the west and east side of the I-15.

12.1 Existing Conditions Basic Freeway Segment Capacity Analysis

Table 12-1 summarizes the peak hour Level of Service results at the six (6) basic freeway segments for the Existing and Existing with ELSP Project Buildout traffic conditions. The first column (1) lists Existing traffic conditions. The second column (2) lists Existing With ELSP Project Buildout traffic conditions. The third column (3) shows whether the traffic associated with the Project (ELSP Project Buildout) will have a significant impact based on the LOS standards and the significance impact criteria defined in this report. The fourth column (4) presents the Level of Service with the implementation of improvements, if necessary.

12.1.1 Existing Traffic Conditions

Review of column (1) of *Table 12-1* indicates that all six (6) basic freeway segments are forecast to operate at acceptable LOS D or better during the AM and PM peak hours under the Existing traffic conditions based on the LOS standards defined in this report.

12.1.2 Existing With East Lake Specific Plan Project Buildout Traffic Conditions

Review of column (2) of *Table 12-1* indicates that all six (6) basic freeway segments are forecast to operate at acceptable levels of service during the AM and PM peak hours under the Existing With ELSP Project Buildout traffic conditions based on the LOS standards defined in this report.

Review of column (3) of *Table 12-1* indicates that none of the six (6) basic freeway segments will have a significant impact under the Existing With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report.

Please note that some basic freeway segments may operate at a slightly better level of service in the Existing With ELSP Project Buildout traffic conditions compared to the Existing traffic conditions due to the inclusion of the ELSP Buildout internal network. With the addition of the East Lake Specific Plan Buildout internal network, existing volumes are shifted along adjacent roadways and freeway segments due to the alternative paths of travel, as modeled utilizing LETAM. Existing volumes were shifted based on the differences between the “2007 Base Model” and the “2007 Base Model with the ELSP Buildout Network (No Project).” These shifts may lead to decreasing volumes at certain segments, thus yielding lower delays.

Appendix H contains the Basic Freeway Segments Analysis Calculation Worksheets for the Existing and Existing with ELSP Project Buildout Traffic Conditions.

TABLE 12-1
EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR BASIC FREEWAY SEGMENTS CAPACITY ANALYSIS SUMMARY⁵⁶

| Key Basic Freeway Segment | Time Period | (1) Existing Traffic Conditions | | | (2) Existing With ELSP Project Buildout Traffic Conditions | | | Significant Impact | (4) Existing With ELSP Project Buildout With Mitigation | | |
|--|-------------|---------------------------------------|-----------------------|-----|---|-----------------------|-----|-----------------------|--|-----------------------|-----|
| | | Peak Hour Volume | Density (pc/mi/ln) | LOS | Peak Hour Volume | Density (pc/mi/ln) | LOS | | Peak Hour Volume | Density (pc/mi/ln) | LOS |
| | | Yes/No | | | | | | | | | |
| 1. I-15 Northbound <i>from</i> Baxter Road <i>to</i> Bundy Canyon Road | AM | 2,983 | 16.3 | B | 2,997 | 16.3 | B | No | -- | -- | -- |
| | PM | 4,517 | 24.8 | C | 4,569 | 25.2 | C | No | -- | -- | -- |
| 2. I-15 Northbound <i>from</i> Bundy Canyon Rd <i>to</i> Railroad Canyon Rd | AM | 3,121 | 17.0 | B | 3,089 | 16.8 | B | No | -- | -- | -- |
| | PM | 3,984 | 21.7 | C | 3,910 | 21.3 | C | No | -- | -- | -- |
| 3. I-15 Northbound <i>from</i> Railroad Canyon Road <i>to</i> Main Street | AM | 4,092 | 22.3 | C | 4,115 | 22.4 | C | No | -- | -- | -- |
| | PM | 4,155 | 22.7 | C | 4,011 | 21.9 | C | No | -- | -- | -- |
| 4. I-15 Southbound <i>from</i> Main Street <i>to</i> Railroad Canyon Road | AM | 5,079 | 28.7 | D | 5,061 | 28.6 | D | No | -- | -- | -- |
| | PM | 5,164 | 29.3 | D | 5,190 | 29.5 | D | No | -- | -- | -- |
| 5. I-15 Southbound <i>from</i> Railroad Canyon Rd <i>to</i> Bundy Canyon Rd | AM | 5,028 | 28.3 | D | 5,004 | 28.1 | D | No | -- | -- | -- |
| | PM | 4,423 | 24.3 | C | 4,291 | 23.5 | C | No | -- | -- | -- |
| 6. I-15 Southbound <i>from</i> Bundy Canyon Road <i>to</i> Baxter Road | AM | 5,492 | 32.0 | D | 5,589 | 32.9 | D | No | -- | -- | -- |
| | PM | 4,279 | 23.4 | C | 4,181 | 22.8 | C | No | -- | -- | -- |

Notes:

- pc/mi/ln = Passenger cars per mile per lane (density)
- LOS = Level of Service, please refer to *Table 3-5* for the LOS definitions
- **Bold Volume/Density/LOS values** indicate adverse service levels based on the Caltrans LOS Criteria

⁵⁶ Appendix H contains the Density/LOS calculation worksheets for all study basic freeway segments.

12.2 Existing Conditions Freeway Merge And Diverge Segments Capacity Analysis

Table 12-2 summarizes the peak hour Level of Service results at the four (4) freeway merge and diverge segments for the Existing traffic conditions. The first column (1) of *Table 12-2* identifies the type of analysis, i.e., merge or diverge analysis. The second column (2) lists time period. The third column (3) lists Existing traffic conditions. The fourth column (4) lists Existing With ELSP Project Buildout traffic conditions. The fifth column (5) of *Table 12-2* shows whether the traffic associated with the ELSP Project Buildout will have a significant impact based on the LOS standards and the significance impact criteria defined in this report.

12.2.1 Existing Traffic Conditions

Review of column (3) of *Table 12-2* indicates that all four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service LOS D or better under the Existing traffic conditions based on the LOS standards defined in this report.

12.2.2 Existing With East Lake Specific Plan Project Buildout Traffic Conditions

Review of column (4) of *Table 12-2* indicates that all four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service LOS D or better under the Existing With ELSP Project Buildout traffic conditions based on the LOS standards defined in this report.

Review of column (5) of *Table 12-2* indicates that none of the four (4) freeway merge and diverge segments will have a significant impact under the Existing With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report.

Please note that some merge and diverge segments may operate at a slightly better level of service in the Existing With ELSP Project Buildout traffic conditions compared to the Existing traffic conditions due to the inclusion of the ELSP Buildout internal network. With the addition of the East Lake Specific Plan Buildout internal network, existing volumes are shifted along adjacent roadways and freeway segments due to the alternative paths of travel, as modeled utilizing LETAM. Existing volumes were shifted based on the differences between the “2007 Base Model” and the “2007 Base Model with the ELSP Buildout Network (No Project).” These shifts may lead to decreasing volumes at certain segments, thus yielding lower delays.

Appendix I contains the Freeway Merge and Diverge Segments Analysis Calculation Worksheets for the Existing and Existing with ELSP Project Buildout Traffic Conditions.

TABLE 12-2

EXISTING WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR FREEWAY MERGE AND DIVERGE SEGMENTS CAPACITY ANALYSIS SUMMARY⁵⁷

| Key Freeway Merge or Diverge Segment | Analysis Type | Time Period | (3) Existing Traffic Conditions | | | | (4) Existing With ELSP Project Buildout Traffic Conditions | | | | (5) Significant Impact |
|--|---------------------|-------------|---------------------------------------|-------------------------|-----------------------|-----|---|-------------------------|-----------------------|-----|------------------------------|
| | | | Freeway Pk Hr Volume | Ramp Pk Hr Volume | Density (pc/mi/ln) | LOS | Freeway Pk Hr Volume | Ramp Pk Hr Volume | Density (pc/mi/ln) | LOS | |
| 1. I-15 Northbound Off-Ramp <i>to</i> Railroad Canyon Road | Diverge Analysis | AM | 3,121 | 523 | 22.2 | C | 3,089 | 483 | 21.9 | C | No |
| | | PM | 3,984 | 833 | 27.2 | C | 3,910 | 854 | 26.9 | C | No |
| 2. I-15 Northbound On-Ramp <i>from</i> Railroad Canyon Road | Merge Analysis | AM | 2,598 | 1,494 | 26.5 | C | 2,606 | 1,509 | 26.6 | C | No |
| | | PM | 3,181 | 1,004 | 25.3 | C | 3,056 | 955 | 24.5 | C | No |
| 3. I-15 Southbound Off-Ramp <i>to</i> Railroad Canyon Road | Diverge Analysis | AM | 5,079 | 971 | 23.1 | C | 5,061 | 949 | 23.0 | C | No |
| | | PM | 5,164 | 1,300 | 24.2 | C | 5,190 | 1,325 | 24.4 | C | No |
| 4. I-15 Southbound On-Ramp <i>from</i> Railroad Canyon Road | Merge Analysis | AM | 4,108 | 920 | 29.5 | D | 4,112 | 892 | 29.3 | D | No |
| | | PM | 3,864 | 559 | 25.5 | C | 3,865 | 426 | 24.5 | C | No |

Notes:

- Pk Hr = Peak Hour
- pc/mi/ln = Passenger cars per mile per lane (density)
- LOS = Level of Service, please refer to *Table 3-6* for the LOS definitions
- **Bold Volume/Density/LOS values** indicate adverse service levels based on the Caltrans LOS Criteria

⁵⁷ Appendix I contains the Density/LOS calculation worksheets for all study freeway merge and diverge segments.

13.0 YEAR 2022 CONDITIONS CALTRANS FACILITIES ANALYSIS

Caltrans requires the use of analysis methods provided in the Highway Capacity Manual (*HCM*) for the analysis of ramp intersections and basic freeway segments. Based on the *Caltrans Traffic Impact Study Guidelines, dated December 2002*, Caltrans endeavors to maintain a target LOS at the transition between LOS "C" and "D" on State highway facilities and *Caltrans District 8* has typically established that LOS D is the operating standard for all Caltrans facilities. However, Caltrans acknowledges that this may not always be feasible and recommends that the lead agency consult with Caltrans to determine the appropriate target LOS. If an existing State highway facility is operating at less than appropriate target LOS, the existing service level should be maintained.

Basic Freeway Segment Analysis for freeway mainlines was conducted for the following six (6) Caltrans freeway segments:

1. I-15 Northbound *from* Baxter Road to Bundy Canyon Road
2. I-15 Northbound *from* Bundy Canyon Road to Railroad Canyon Road
3. I-15 Northbound *from* Railroad Canyon Road to Main Street
4. I-15 Southbound *from* Main Street to Railroad Canyon Road
5. I-15 Southbound *from* Railroad Canyon Road to Bundy Canyon Road
6. I-15 Southbound *from* Bundy Canyon Road to Baxter Road

Additionally, Freeway Merge and Diverge Segment Analysis for ramp junctions was conducted for the following four (4) Caltrans freeway merge and diverge segments:

1. I-15 Northbound Off-Ramp *to* Railroad Canyon Road
2. I-15 Southbound On-Ramp *from* Railroad Canyon Road
3. I-15 Northbound Off-Ramp *to* Railroad Canyon Road
4. I-15 Southbound On-Ramp *from* Railroad Canyon Road

The City of Lake Elsinore and Caltrans is currently in the process of improving the Railroad Canyon Road and I-15 Interchange. Following the public review period of the Draft EIR/EIS, and considering public input, the Riverside County Transportation Commission (RCTC) and Caltrans have identified Alternative 2 as the preferred project alternative. Alternative 2 is split into two phases, both of which are anticipated to be completed by Year 2022 and thus is incorporated in the Year 2022 and Year 2040 analysis. Phase I includes reconstructing/widening Railroad Canyon Road under crossing from 4 lanes to 6 lanes from Summerhill Drive/Grape Street to Casino Road, replacing the existing northbound ramps off of Railroad Canyon Road with hook ramps off of Grape Street, and adding ramp acceleration/deceleration lanes for both the northbound and southbound ramps. Phase II includes the construction of a full interchange at Franklin Street and the I-15, adding auxiliary lanes from the Franklin Street Interchange to the Main Street Interchange as well as to the Railroad Canyon Road Interchange for both the northbound and southbound directions,

realign/widen the Main Street southbound on-ramp from 1 lane to 2 lanes, and construct a new frontage road on the west and east side of the I-15.

13.1 Year 2022 Conditions Basic Freeway Segment Capacity Analysis

Table 13-1 summarizes the peak hour Level of Service results at the six (6) basic freeway segments for the Year 2022 traffic conditions. The first column (1) lists Existing traffic conditions. The second column (2) lists Year 2022 Without East Lake Specific Plan Phase I traffic conditions and the third column (3) lists Year 2022 With ELSP Project Phase I traffic conditions. The fourth column (4) shows whether the traffic associated with the East Lake Specific Plan Phase I will have a significant impact based on the LOS standards and the significance impact criteria defined in this report. The fifth column (5) presents the Level of Service with the implementation of improvements, if necessary.

It should be noted that the Basic Freeway Segment analysis includes the planned improvements from the Railroad Canyon Road and I-15 Interchange Project in the Year 2022 background traffic conditions.

13.1.1 Year 2022 Without East Lake Specific Plan Phase I Traffic Conditions

Review of column (2) of *Table 13-1* indicates that one (1) basic freeway segment is forecast to operate at an adverse level of service under the Year 2022 Without ELSP Project Phase I traffic conditions based on the LOS standards defined in this report. The remaining five (5) basic freeway segments are forecast to operate at an acceptable LOS D or better during the AM and PM peak hours under the Year 2022 Without ELSP Project Phase I traffic conditions. The location operating at an adverse level of service is listed below:

| <u>Key Basic Freeway Segment</u> | <u>AM Peak Hour</u> | | | <u>PM Peak Hour</u> | | |
|--|---------------------|---------------------------|------------|---------------------|---------------------------|------------|
| | <u>Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> | <u>Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> |
| 6. I-15 Southbound from Bundy Canyon Road to Baxter Road | 5,912 | 36.0 | E | -- | -- | -- |

13.1.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

Review of column (3) of *Table 13-1* indicates that one (1) basic freeway segment is forecast to operate at an adverse level of service under the Year 2022 With ELSP Project Phase I traffic conditions based on the LOS standards defined in this report. The remaining five (5) basic freeway segments are forecast to operate at an acceptable LOS D or better during the AM and PM peak hours under the Year 2022 With ELSP Project Phase I traffic conditions. The location operating at an adverse level of service is listed below:

| <u>Key Basic Freeway Segment</u> | <u>AM Peak Hour</u> | | | <u>PM Peak Hour</u> | | |
|--|---------------------|---------------------------|------------|---------------------|---------------------------|------------|
| | <u>Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> | <u>Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> |
| 6. I-15 Southbound from Bundy Canyon Road to Baxter Road | 6,120 | 38.3 | E | -- | -- | -- |

Review of column (4) of *Table 13-1* indicates that one (1) of the six (6) basic freeway segments will have a significant impact under the Year 2022 With ELSP Project Phase I traffic conditions when compared to the LOS criteria defined in this report. However, as shown in column (5) of *Table 13-1*, the implementation of recommended mitigation measures at the impacted basic freeway segments, mitigates the impacts of the proposed East Lake Specific Plan (Phase I). After implementation of the recommended mitigation measures, the impacted basic freeway segment is forecast to operate at an acceptable LOS based on the LOS standards outlined in this report.

Please note that all basic freeway segments yield higher delay values in the Year 2022 With ELSP Project Phase I traffic conditions compared to the Year 2022 Without ELSP Project Phase I traffic conditions. Both of these scenarios utilize the same internal and external roadway networks. The East Lake Specific Plan Phase I traffic volumes is added directly on top of Year 2022 Without ELSP Project Phase I traffic conditions, resulting in an increase in volumes at all freeway segments and subsequently yielding higher delays.

Appendix J contains the Basic Freeway Segments Analysis Calculation Worksheets for the Year 2022 Traffic Conditions.

TABLE 13-1
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR BASIC FREEWAY SEGMENTS CAPACITY ANALYSIS SUMMARY⁵⁸

| Key Basic Freeway Segment | Time Period | (1) Existing Traffic Conditions | | | (2) Year 2022 Without ELSP Project Phase I Traffic Conditions | | | (3) Year 2022 With ELSP Project Phase I Traffic Conditions | | | (4) Significant Impact | (5) Year 2022 With ELSP Project Phase I With Mitigation | | |
|--|-------------|---------------------------------------|-----------------------|-----|--|-----------------------|-----|---|-----------------------|-----|------------------------------|--|-----------------------|-----|
| | | Peak Hour Volume | Density (pc/mi/ln) | LOS | Peak Hour Volume | Density (pc/mi/ln) | LOS | Peak Hour Volume | Density (pc/mi/ln) | LOS | | Peak Hour Volume | Density (pc/mi/ln) | LOS |
| 1. I-15 Northbound <i>from</i> Baxter Road <i>to</i> Bundy Canyon Road | AM | 2,983 | 16.3 | B | 3,165 | 17.3 | B | 3,210 | 17.5 | B | No | -- | -- | -- |
| | PM | 4,517 | 24.8 | C | 4,828 | 26.9 | D | 5,0117 | 28.2 | D | No | -- | -- | -- |
| 2. I-15 Northbound <i>from</i> Bundy Canyon Rd <i>to</i> Railroad Canyon Rd | AM | 3,121 | 17.0 | B | 3,214 | 17.5 | B | 3,224 | 17.6 | B | No | -- | -- | -- |
| | PM | 3,984 | 21.7 | C | 4,301 | 23.5 | C | 4,331 | 23.7 | C | No | -- | -- | -- |
| 3. I-15 Northbound <i>from</i> Railroad Canyon Road <i>to</i> Franklin Street | AM | 4,092 | 22.3 | C | 3,400 | 13.9 | B | 3,419 | 14.0 | B | No | -- | -- | -- |
| | PM | 4,155 | 22.7 | C | 4,009 | 16.4 | B | 4,013 | 16.4 | B | No | -- | -- | -- |
| 4. I-15 Southbound <i>from</i> Franklin Street <i>to</i> Railroad Canyon Road | AM | 5,079 | 28.7 | D | 5,211 | 21.3 | C | 5,231 | 21.4 | C | No | -- | -- | -- |
| | PM | 5,164 | 29.3 | D | 4,704 | 19.2 | C | 4,751 | 19.4 | C | No | -- | -- | -- |
| 5. I-15 Southbound <i>from</i> Railroad Canyon Rd <i>to</i> Bundy Canyon Rd | AM | 5,028 | 28.3 | D | 5,329 | 30.7 | D | 5,359 | 30.9 | D | No | -- | -- | -- |
| | PM | 4,423 | 24.3 | C | 4,228 | 23.1 | C | 4,241 | 23.2 | C | No | -- | -- | -- |
| 6. I-15 Southbound <i>from</i> Bundy Canyon Road <i>to</i> Baxter Road | AM | 5,492 | 32.0 | D | 5,912 | 36.0 | E | 6,120 | 38.3 | E | Yes | 6,120 | 25.3 | C |
| | PM | 4,279 | 23.4 | C | 4,388 | 24.0 | C | 4,467 | 24.5 | C | No | 1,187 | 18.3 | C |

Notes:

- pc/mi/ln = Passenger cars per mile per lane (density)
- LOS = Level of Service, please refer to *Table 3-5* for the LOS definitions
- **Bold Volume/Density/LOS values** indicate adverse service levels based on the Caltrans LOS Criteria

⁵⁸ Appendices H and J contain the Density/LOS calculation worksheets for all study basic freeway segments.

13.2 Year 2022 Conditions Freeway Merge And Diverge Segments Capacity Analysis

Table 13-2 summarizes the peak hour Level of Service results at the four (4) freeway merge and diverge segments for the Year 2022 traffic conditions. The first column (1) of *Table 13-2* identifies the type of analysis, i.e., merge or diverge analysis. The second column (2) lists time period. The third column (3) lists Existing traffic conditions and the fourth column (4) lists Year 2022 Without ELSP Project Phase I traffic conditions. The fifth column (5) lists Year 2022 With ELSP Project Phase I traffic conditions. The sixth column (6) of *Table 13-2* shows whether the traffic associated with the East Lake Specific Plan (Phase I) will have a significant impact based on the LOS standards and the significance impact criteria defined in this report.

It should be noted that the Freeway Merge And Diverge Segment analysis includes the planned improvements from the Railroad Canyon Road and I-15 Interchange Project in the Year 2022 background traffic conditions.

13.2.1 Year 2022 Without East Lake Specific Plan Project Phase I Traffic Conditions

Review of column (4) of *Table 13-2* indicates that all four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service LOS C or better under the Year 2022 Without ELSP Project Phase I traffic conditions based on the LOS standards defined in this report.

13.2.2 Year 2022 With East lake Specific Plan Phase I Traffic Conditions

Review of column (5) of *Table 13-2* indicates that all four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service LOS C or better under the Year 2022 With ELSP Project Phase I traffic conditions based on the LOS standards defined in this report.

Review of column (6) of *Table 13-2* indicates that none of the four (4) freeway merge and diverge segments will have a significant impact under the Year 2022 With ELSP Project Phase I traffic conditions when compared to the LOS criteria defined in this report.

Please note that all merge and diverge segments yield higher delay values in the Year 2022 With ELSP Project Phase I traffic conditions compared to the Year 2022 Without ELSP Project Phase I traffic conditions. Both of these scenarios utilize the same internal and external roadway networks. The East Lake Specific Plan Phase I traffic volumes is added directly on top of Year 2022 Without ELSP Project Phase I traffic conditions, resulting in an increase in volumes at all merge and diverge segments and subsequently yielding higher delays.

Appendix K contains the Freeway Merge And Diverge Segments Analysis Calculation Worksheets for the Year 2022 Traffic Conditions.

TABLE 13-2
YEAR 2022 WITH ELSP PROJECT PHASE I CONDITIONS PEAK HOUR FREEWAY MERGE AND DIVERGE SEGMENTS CAPACITY ANALYSIS SUMMARY⁵⁹

| Key Freeway Merge or Diverge Segment | Analysis Type | Time Period | (3) Existing Traffic Conditions | | | | (4) Year 2022 Without ELSP Project Phase I Traffic Conditions | | | | (5) Year 2022 With ELSP Project Phase I Traffic Conditions | | | | (6) Significant Impact |
|---|------------------|-------------|---|-------------------------|-----------------------|-----|--|-------------------------|-----------------------|-----|---|-------------------------|-----------------------|-----|---------------------------|
| | | | Freeway Pk Hr Volume | Ramp Pk Hr Volume | Density (pc/mi/ln) | LOS | Freeway Pk Hr Volume | Ramp Pk Hr Volume | Density (pc/mi/ln) | LOS | Freeway Pk Hr Volume | Ramp Pk Hr Volume | Density (pc/mi/ln) | LOS | |
| | | | | | | | | | | | | | | | |
| 1. I-15 Northbound Off-Ramp <i>to</i> Grape Street | Diverge Analysis | AM | I-15 NB Ramps at Grape Street do not exist under existing conditions. Replaces existing Railroad Canyon Road ramps. | | | | 3,214 | 565 | 11.6 | B | 3,224 | 575 | 11.7 | B | No |
| | | PM | | | | | 4,301 | 1,035 | 18.0 | B | 4,331 | 1,065 | 18.2 | B | No |
| 2. I-15 Northbound On-Ramp <i>from</i> Grape Street | Merge Analysis | AM | I-15 NB Ramps at Grape Street do not exist under existing conditions. Replaces existing Railroad Canyon Road ramps. | | | | 2,649 | 751 | 10.7 | B | 2,649 | 770 | 10.9 | B | No |
| | | PM | | | | | 3,266 | 743 | 12.7 | B | 3,266 | 747 | 12.7 | B | No |
| 3. I-15 Southbound Off-Ramp <i>to</i> Railroad Canyon Road | Diverge Analysis | AM | 5,079 | 971 | 23.1 | C | 5,211 | 796 | 6.7 | A | 5,231 | 815 | 6.8 | A | No |
| | | PM | 5,164 | 1,300 | 24.2 | C | 4,704 | 1,126 | 6.5 | A | 4,751 | 1,173 | 6.9 | A | No |
| 4. I-15 Southbound On-Ramp <i>from</i> Railroad Canyon Road | Merge Analysis | AM | 4,108 | 920 | 29.5 | D | 4,415 | 914 | 25.9 | C | 4,416 | 943 | 26.1 | C | No |
| | | PM | 3,864 | 559 | 25.5 | C | 3,578 | 650 | 19.5 | B | 3,578 | 663 | 19.6 | B | No |

Notes:

- Pk Hr = Peak Hour
- pc/mi/ln = Passenger cars per mile per lane (density)
- LOS = Level of Service, please refer to *Table 3-6* for the LOS definitions
- **Bold Volume/Density/LOS values** indicate adverse service levels based on the Caltrans LOS Criteria

⁵⁹ Appendices I and K contain the Density/LOS calculation worksheets for all study freeway merge and diverge segments.

14.0 YEAR 2040 CONDITIONS CALTRANS FACILITIES ANALYSIS

Caltrans requires the use of analysis methods provided in the Highway Capacity Manual (*HCM*) for the analysis of ramp intersections and basic freeway segments. Based on the *Caltrans Traffic Impact Study Guidelines, dated December 2002*, Caltrans endeavors to maintain a target LOS at the transition between LOS "C" and "D" on State highway facilities and *Caltrans District 8* has typically established that LOS D is the operating standard for all Caltrans facilities. However, Caltrans acknowledges that this may not always be feasible and recommends that the lead agency consult with Caltrans to determine the appropriate target LOS. If an existing State highway facility is operating at less than appropriate target LOS, the existing service level should be maintained.

Basic Freeway Segment Analysis for freeway mainlines was conducted for the following six (6) Caltrans freeway segments:

1. I-15 Northbound *from* Baxter Road to Bundy Canyon Road
2. I-15 Northbound *from* Bundy Canyon Road to Railroad Canyon Road
3. I-15 Northbound *from* Railroad Canyon Road to Main Street
4. I-15 Southbound *from* Main Street to Railroad Canyon Road
5. I-15 Southbound *from* Railroad Canyon Road to Bundy Canyon Road
6. I-15 Southbound *from* Bundy Canyon Road to Baxter Road

Additionally, Freeway Merge and Diverge Segment Analysis for ramp junctions was conducted for the following four (4) Caltrans freeway merge and diverge segments:

1. I-15 Northbound Off-Ramp *to* Railroad Canyon Road
2. I-15 Southbound On-Ramp *from* Railroad Canyon Road
3. I-15 Northbound Off-Ramp *to* Railroad Canyon Road
4. I-15 Southbound On-Ramp *from* Railroad Canyon Road

The City of Lake Elsinore and Caltrans is currently in the process of improving the Railroad Canyon Road and I-15 Interchange. Following the public review period of the Draft EIR/EIS, and considering public input, the Riverside County Transportation Commission (RCTC) and Caltrans have identified Alternative 2 as the preferred project alternative. Alternative 2 is split into two phases, both of which are anticipated to be completed by Year 2022 and thus is incorporated in the Year 2022 and Year 2040 analysis. Phase I includes reconstructing/widening Railroad Canyon Road under crossing from 4 lanes to 6 lanes from Summerhill Drive/Grape Street to Casino Road, replacing the existing northbound ramps off of Railroad Canyon Road with hook ramps off of Grape Street, and adding ramp acceleration/deceleration lanes for both the northbound and southbound ramps. Phase II includes the construction of a full interchange at Franklin Street and the I-15, adding auxiliary lanes from the Franklin Street Interchange to the Main Street Interchange as well as to the Railroad Canyon Road Interchange for both the northbound and southbound directions,

realign/widen the Main Street southbound on-ramp from 1 lane to 2 lanes, and construct a new frontage road on the west and east side of the I-15.

14.1 Year 2040 Conditions Basic Freeway Segment Capacity Analysis

Table 14-1 summarizes the peak hour Level of Service results at the six (6) basic freeway segments for the Year 2040 traffic conditions. The first column (1) lists Existing traffic conditions. The second column (2) lists Year 2040 With Adopted Specific Plan traffic conditions and the third column (3) lists Year 2040 With East Lake Specific Plan Project Buildout traffic conditions. The fourth column (4) shows whether the traffic associated with the East Lake Specific Plan (Buildout) will have a significant impact based on the LOS standards and the significance impact criteria defined in this report. The fifth column (5) presents the Level of Service with the implementation of improvements, if necessary.

It should be noted that the Basic Freeway Segment analysis includes the planned improvements from the Railroad Canyon Road and I-15 Interchange Project in the Year 2040 background traffic conditions.

14.1.1 Year 2040 With Adopted Specific Plan Traffic Conditions

Review of column (2) of *Table 14-1* indicates that three (3) basic freeway segments are forecast to operate at adverse levels of service under the Year 2040 With Adopted Specific Plan traffic conditions based on the LOS standards defined in this report. The remaining three (3) basic freeway segments are forecast to operate at an acceptable LOS D or better during the AM and PM peak hours under the Year 2040 Adopted Specific Plan traffic conditions. The locations operating at adverse levels of service are listed below:

| <u>Key Basic Freeway Segment</u> | <u>AM Peak Hour</u> | | | <u>PM Peak Hour</u> | | |
|--|---------------------|---------------------------|------------|---------------------|---------------------------|------------|
| | <u>Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> | <u>Pk Hr Volume</u> | <u>Density (pc/mi/ln)</u> | <u>LOS</u> |
| 1. I-15 Northbound <i>from</i> Baxter Road <i>to</i> Bundy Canyon Road | -- | -- | -- | 6,104 | 38.1 | E |
| 5. I-15 Southbound <i>from</i> Railroad Canyon Rd <i>to</i> Bundy Canyon Rd | 6,752 | 46.9 | F | -- | -- | -- |
| 6. I-15 Southbound <i>from</i> Bundy Canyon Road <i>to</i> Baxter Road | 7,615 | 65.7 | F | -- | -- | -- |

14.1.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

Review of column (3) of *Table 14-1* indicates that four (4) basic freeway segments are forecast to operate at adverse levels of service under the Year 2040 With ELSP Project Buildout traffic conditions based on the LOS standards defined in this report. The remaining two (2) basic freeway segments are forecast to operate at an acceptable LOS D or better during the AM and PM peak hours under the Year 2040 With ELSP Project Buildout traffic conditions. The locations operating at adverse levels of service are listed below:

| Key Basic Freeway Segment | AM Peak Hour | | | PM Peak Hour | | |
|---|-------------------------|-------------------------------|------------|-------------------------|-------------------------------|------------|
| | Pk Hr Volume | Density (pc/mi/ln) | LOS | Pk Hr Volume | Density (pc/mi/ln) | LOS |
| 1. I-15 Northbound <i>from</i> Baxter Road <i>to</i> Bundy Canyon Road | -- | -- | -- | 7,232 | 55.9 | F |
| 2. I-15 Northbound <i>from</i> Bundy Canyon Rd <i>to</i> Railroad Canyon Rd | -- | -- | -- | 6,594 | 44.5 | E |
| 5. I-15 Southbound <i>from</i> Railroad Canyon Rd <i>to</i> Bundy Canyon Rd | 6,746 | 46.8 | F | -- | -- | -- |
| 6. I-15 Southbound <i>from</i> Bundy Canyon Road <i>to</i> Baxter Road | 7,528 | 63.2 | F | -- | -- | -- |

Review of column (4) of *Table 14-1* indicates that four (4) of the six (6) basic freeway segments will have a significant impact under the Year 2040 With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report. However, as shown in column (5) of *Table 14-1*, the implementation of recommended mitigation measures at the impacted basic freeway segments, mitigates the impacts of the proposed East Lake Specific Plan (Buildout). After implementation of the recommended mitigation measures, the impacted basic freeway segments are forecast to operate at an acceptable LOS based on the LOS standards outlined in this report.

Please note that some basic freeway segments may operate at a slightly better level of service in the Year 2040 With ELSP Project Buildout traffic conditions compared to the Year 2040 With Adopted Specific Plan traffic conditions. Both of these scenarios utilize the same internal and external roadway networks, however, the East Lake Specific Plan Buildout project description differs from the Adopted Specific Plan project description, thus resulting in different project volumes on the freeway segments. The segment volumes from the East Lake Specific Plan Buildout scenario can be greater or less than the segment volumes from the Adopted Specific Plan scenario, depending on the volumes and attractions/destinations defined by the project description and as modeled utilizing LETAM.

Appendix L contains the Basic Freeway Segments Analysis Calculation Worksheets for the Year 2040 Traffic Conditions.

TABLE 14-1
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR BASIC FREEWAY SEGMENTS CAPACITY ANALYSIS SUMMARY⁶⁰

| Key Basic Freeway Segment | Time Period | (1) Existing Traffic Conditions | | | (2) Year 2040 With Adopted Specific Plan Traffic Conditions | | | (3) Year 2040 With ELSP Project Buildout Traffic Conditions | | | (4) Significant Impact | (5) Year 2040 With ELSP Project Buildout With Mitigation | | |
|--|-------------|---------------------------------------|-----------------------|-----|--|-----------------------|----------|--|-----------------------|----------|------------------------------|---|-----------------------|-----|
| | | Peak Hour Volume | Density (pc/mi/ln) | LOS | Peak Hour Volume | Density (pc/mi/ln) | LOS | Peak Hour Volume | Density (pc/mi/ln) | LOS | | Peak Hour Volume | Density (pc/mi/ln) | LOS |
| | | | | | | | | | | | | | | |
| 1. I-15 Northbound <i>from</i> Baxter Road <i>to</i> Bundy Canyon Road | AM | 2,983 | 16.3 | B | 3,398 | 18.5 | C | 3,365 | 18.4 | C | No | 3,365 | 13.8 | B |
| | PM | 4,517 | 24.8 | C | 6,104 | 38.1 | E | 7,232 | 55.9 | F | Yes | 7,232 | 31.4 | D |
| 2. I-15 Northbound <i>from</i> Bundy Canyon Rd <i>to</i> Railroad Canyon Rd | AM | 3,121 | 17.0 | B | 3,323 | 18.1 | C | 3,327 | 18.1 | C | No | 3,327 | 13.6 | B |
| | PM | 3,984 | 21.7 | C | 5,425 | 31.5 | D | 6,594 | 44.5 | E | Yes | 6,594 | 27.7 | D |
| 3. I-15 Northbound <i>from</i> Railroad Canyon Road <i>to</i> Franklin Street | AM | 4,092 | 22.3 | C | 3,806 | 15.6 | B | 3,795 | 15.5 | B | No | -- | -- | -- |
| | PM | 4,155 | 22.7 | C | 5,294 | 21.6 | C | 6,479 | 27.1 | D | No | -- | -- | -- |
| 4. I-15 Southbound <i>from</i> Franklin Street <i>to</i> Railroad Canyon Road | AM | 5,079 | 28.7 | D | 6,436 | 26.9 | D | 6,432 | 26.9 | D | No | -- | -- | -- |
| | PM | 5,164 | 29.3 | D | 3,640 | 14.9 | B | 4,723 | 19.3 | C | No | -- | -- | -- |
| 5. I-15 Southbound <i>from</i> Railroad Canyon Rd <i>to</i> Bundy Canyon Rd | AM | 5,028 | 28.3 | D | 6,752 | 46.9 | F | 6,746 | 46.8 | F | Yes | 6,746 | 28.5 | D |
| | PM | 4,423 | 24.3 | C | 3,248 | 17.7 | B | 4,342 | 23.8 | C | No | 4,342 | 17.8 | B |
| 6. I-15 Southbound <i>from</i> Bundy Canyon Road <i>to</i> Baxter Road | AM | 5,492 | 32.0 | D | 7,615 | 65.7 | F | 7,528 | 63.2 | F | Yes | 7,528 | 33.4 | D |
| | PM | 4,279 | 23.4 | C | 3,922 | 21.4 | C | 4,977 | 27.9 | D | No | 4,977 | 20.4 | C |

Notes:

- pc/mi/ln = Passenger cars per mile per lane (density)
- LOS = Level of Service, please refer to *Table 3-5* for the LOS definitions
- **Bold Volume/Density/LOS values** indicate adverse service levels based on the Caltrans LOS Criteria

⁶⁰ Appendices H and L contain the Density/LOS calculation worksheets for all study basic freeway segments.

14.2 Year 2040 Conditions Freeway Merge And Diverge Segments Capacity Analysis

Table 14-2 summarizes the peak hour Level of Service results at the four (4) freeway merge and diverge segments for the Year 2040 traffic conditions. The first column (1) of *Table 14-2* identifies the type of analysis, i.e., merge or diverge analysis. The second column (2) lists time period. The third column (3) lists Existing traffic conditions and the fourth column (4) lists Year 2040 With Adopted Specific Plan traffic conditions. The fifth column (5) lists Year 2040 With East Lake Specific Plan Project Buildout traffic conditions. The sixth column (6) of *Table 14-2* shows whether the traffic associated with the East Lake Specific Plan (Buildout) will have a significant impact based on the LOS standards and the significance impact criteria defined in this report. The seventh column (7) presents the Level of Service with the implementation of improvements, if necessary.

It should be noted that the Freeway Merge And Diverge Segment analysis includes the planned improvements from the Railroad Canyon Road and I-15 Interchange Project in the Year 2040 background traffic conditions.

14.2.1 Year 2040 With Adopted Specific Plan Traffic Conditions

Review of column (4) of *Table 14-2* indicates that one (1) freeway merge segment is forecast to operate at an adverse level of service under the Year 2040 With Adopted Specific Plan traffic conditions based on the LOS standards defined in this report. The remaining three (3) freeway merge and diverge segments are forecast to operate at an acceptable LOS D or better during the AM and PM peak hours under the Year 2040 With Adopted Specific Plan traffic conditions. The location operating at an adverse level of service is listed below:

| Key Basic Freeway Segment | AM Peak Hour | | | | | | PM Peak Hour | | | | | |
|--|---------------------|---------------|---------------|---------------|-------------------|------------|---------------------|---------------|---------------|---------------|-------------------|------------|
| | Freeway | | Ramp | | Density | | Freeway | | Ramp | | Density | |
| | Pk Hr | Pk Hr | Pk Hr | Pk Hr | (pc/mi/in) | LOS | Pk Hr | Pk Hr | Pk Hr | Pk Hr | (pc/mi/in) | LOS |
| | Volume | Volume | Volume | Volume | (pc/mi/in) | LOS | Volume | Volume | Volume | Volume | (pc/mi/in) | LOS |
| 1. I-15 Southbound On-Ramp <i>from</i> Railroad Canyon Road | 5,507 | | 1,245 | | 34.1 | F | -- | -- | -- | -- | -- | -- |

14.2.2 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

Review of column (5) of *Table 14-2* indicates that one (1) freeway merge segment is forecast to operate at an adverse level of service under the Year 2040 With ELSP Project Buildout traffic conditions based on the LOS standards defined in this report. The remaining three (3) freeway merge and diverge segments are forecast to operate at an acceptable LOS C or better during the AM and PM peak hours under the Year 2040 With ELSP Project Buildout traffic conditions. The location operating at an adverse level of service is listed below:

| Key Basic Freeway Segment | AM Peak Hour | | | | | | PM Peak Hour | | | | | |
|--|---------------------|---------------|---------------|---------------|-------------------|------------|---------------------|---------------|---------------|---------------|-------------------|------------|
| | Freeway | | Ramp | | Density | | Freeway | | Ramp | | Density | |
| | Pk Hr | Pk Hr | Pk Hr | Pk Hr | (pc/mi/in) | LOS | Pk Hr | Pk Hr | Pk Hr | Pk Hr | (pc/mi/in) | LOS |
| | Volume | Volume | Volume | Volume | (pc/mi/in) | LOS | Volume | Volume | Volume | Volume | (pc/mi/in) | LOS |
| 1. I-15 Southbound On-Ramp <i>from</i> Railroad Canyon Road | 5,512 | | 1,234 | | 34.0 | F | -- | -- | -- | -- | -- | -- |

Review of column (6) of *Table 14-2* indicates that one (1) of the four (4) freeway merge and diverge segments will have a significant impact under the Year 2040 With ELSP Project Buildout traffic conditions when compared to the LOS criteria defined in this report. However, as shown in column (7) of *Table 14-2*, the implementation of recommended mitigation measures at the impacted freeway merge segment, mitigates the impacts of the proposed East Lake Specific Plan (Buildout). After implementation of the recommended mitigation measures, the impacted freeway merge segment is forecast to operate at an acceptable LOS based on the LOS standards outlined in this report.

Please note that some merge and diverge segments may operate at a slightly better level of service in the Year 2040 With ELSP Project Buildout traffic conditions compared to the Year 2040 With Adopted Specific Plan traffic conditions. Both of these scenarios utilize the same internal and external roadway networks, however, the East Lake Specific Plan Buildout project description differs from the Adopted Specific Plan project description, thus resulting in different project volumes on the freeway segments. The segment volumes from the East Lake Specific Plan Buildout scenario can be greater or less than the segment volumes from the Adopted Specific Plan scenario, depending on the volumes and attractions/destinations defined by the project description and as modeled utilizing LETAM.

Appendix M contains the Freeway Merge and Diverge Segments Analysis Calculation Worksheets for the Year 2040 Traffic Conditions.

TABLE 14-2
YEAR 2040 WITH ELSP PROJECT BUILDOUT CONDITIONS PEAK HOUR FREEWAY MERGE AND DIVERGE SEGMENTS CAPACITY ANALYSIS SUMMARY⁶¹

| Key Freeway Merge or Diverge Segment | Analysis Type | Time Period | Existing Traffic Conditions | | | | Year 2040 With Adopted Specific Plan Traffic Conditions | | | | Year 2040 With ELSP Project Buildout Traffic Conditions | | | | Significant Impact | Year 2040 With ELSP Project Buildout With Mitigation | | | |
|---|------------------|-------------|---|--------------|------------|---------|---|--------------|-------------|---------|---|--------------|-------------|---------|--------------------|--|--------------|------------|---------|
| | | | Freeway | | Ramp | Density | Freeway | | Ramp | Density | Freeway | | Ramp | Density | | Freeway | | Ramp | Density |
| | | | Pk Hr Volume | Pk Hr Volume | (pc/mi/ln) | LOS | Pk Hr Volume | Pk Hr Volume | (pc/mi/ln) | LOS | Pk Hr Volume | Pk Hr Volume | (pc/mi/ln) | LOS | | Pk Hr Volume | Pk Hr Volume | (pc/mi/ln) | LOS |
| 1. I-15 Northbound Off-Ramp <i>to</i> Grape Street | Diverge Analysis | AM | I-15 NB Ramps at Grape Street do not exist under existing conditions. Replaces existing Railroad Canyon Road ramps. | | | | 3,323 | 805 | 12.7 | B | 3,327 | 805 | 12.7 | B | No | -- | -- | -- | -- |
| | | PM | | | | | 5,425 | 1,272 | 23.4 | C | 6,594 | 1,260 | 27.8 | C | No | -- | -- | -- | -- |
| 2. I-15 Northbound On-Ramp <i>from</i> Grape Street | Merge Analysis | AM | I-15 NB Ramps at Grape Street do not exist under existing conditions. Replaces existing Railroad Canyon Road ramps. | | | | 2,518 | 1,288 | 14.5 | B | 2,522 | 1,273 | 14.4 | B | No | -- | -- | -- | -- |
| | | PM | | | | | 4,153 | 1,141 | 18.7 | B | 5,334 | 1,145 | 22.7 | C | No | -- | -- | -- | -- |
| 3. I-15 Southbound Off-Ramp <i>to</i> Railroad Canyon Road | Diverge Analysis | AM | 5,079 | 971 | 23.1 | C | 6,436 | 929 | 11.2 | B | 6,432 | 920 | 11.2 | B | No | -- | -- | -- | -- |
| | | PM | 5,164 | 1,300 | 24.2 | C | 3,640 | 1,254 | 4.8 | A | 4,723 | 1,227 | 7.2 | A | No | -- | -- | -- | -- |
| 4. I-15 Southbound On-Ramp <i>from</i> Railroad Canyon Road | Merge Analysis | AM | 4,108 | 920 | 29.5 | D | 5,507 | 1,245 | 34.1 | F | 5,512 | 1,234 | 34.0 | F | Yes | 5,512 | 1,234 | 24.0 | C |
| | | PM | 3,864 | 559 | 25.5 | C | 2,386 | 862 | 15.1 | B | 3,496 | 846 | 20.6 | C | No | 3,496 | 846 | 14.3 | B |

Notes:

- Pk Hr = Peak Hour
- pc/mi/ln = Passenger cars per mile per lane (density)
- LOS = Level of Service, please refer to *Table 3-6* for the LOS definitions
- **Bold Volume/Density/LOS values** indicate adverse service levels based on the Caltrans LOS Criteria

⁶¹ Appendices I and M contain the Density/LOS calculation worksheets for all study freeway merge and diverge segments.

15.0 CALTRANS FACILITIES PLANNED AND RECOMMENDED IMPROVEMENTS

For those basic freeway segments as well as freeway merge and diverge segments where projected traffic volumes are expected to result in significant impacts, this report recommends improvements that change the basic freeway segments and/or freeway merge and diverge segments' geometry to increase capacity. These capacity improvements involve freeway widening and/or re-striping to reconfigure (add lanes) the freeway. The identified improvements are expected to:

- Address the impact of existing traffic, Project traffic and future non-project (ambient traffic growth and related projects) traffic, and
- Improve Levels of Service to an acceptable range and/or to pre-project conditions.

15.1 Railroad Canyon Road Interchange Project Planned Improvements

15.1.1 Basic Freeway Segments

15.1.1.1 Year 2022 Without ELSP Project Phase I, Year 2022 With ELSP Project Phase I, Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout Traffic Conditions

The planned improvements listed below are anticipated to be completed in conjunction with the I-15 and Railroad Canyon Road Interchange Project and have been assumed in the Year 2022 Without ELSP Project Phase I, Year 2022 With ELSP Project Phase I, Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout traffic conditions:

- 3. I-15 Northbound from Railroad Canyon Road to Franklin Street: Add one (1) auxiliary lane connecting the Railroad Canyon Road On-Ramp to the Franklin Street Off-Ramp.
- 4. I-15 Southbound from Franklin Street to Railroad Canyon Road: Add one (1) auxiliary lane connecting the Franklin Street On-Ramp to the Railroad Canyon Road Off-Ramp.

15.1.2 Freeway Merge And Diverge Segments

15.1.2.1 Year 2022 Without ELSP Project Phase I, Year 2022 With ELSP Project Phase I, Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout Traffic Conditions

The planned improvements listed below are anticipated to be completed in conjunction with the I-15 and Railroad Canyon Road Interchange Project and have been assumed in the Year 2022 Without ELSP Project Phase I, Year 2022 With ELSP Project Phase I, Year 2040 With Adopted Specific Plan and Year 2040 With ELSP Project Buildout traffic conditions:

- 1. I-15 Northbound Off-Ramp to Grape Street: Replace the existing off-ramp onto Railroad Canyon Road with a one-lane hook ramp onto Grape Street. Extend the deceleration lane to approximately 1,530 feet.
- 2. I-15 Northbound On-Ramp from Grape Street: Replace the existing on-ramp from Railroad Canyon Road with a one-lane hook ramp from Grape Street. The acceleration lane will tie in with the future auxiliary lane connecting to the Franklin Street off-ramp, approximately 2,400 feet downstream.

- 3. I-15 Southbound Off-Ramp to Railroad Canyon Road: Add a second off-ramp lane with an approximately 170 foot long deceleration lane. Configure the existing off-ramp lane to the proposed auxiliary lane connecting to the Franklin Street on-ramp approximately 1,950 feet upstream.
- 4. I-15 Southbound On-Ramp from Railroad Canyon Road: Extend the acceleration lane to approximately 1,500 feet.

15.2 Recommended Improvements

15.2.1 Basic Freeway Segments

15.2.1.1 Existing With East Lake Specific Plan Project Buildout Traffic Conditions

The results of the Existing With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed East Lake Specific Plan (Buildout) will not have a significant impact at any of the six (6) basic freeway segments. All six (6) basic freeway segments are forecast to operate at acceptable levels of service under the Existing With ELSP Project Buildout traffic conditions.

15.2.1.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

The results of the Year 2022 With ELSP Project Phase I traffic conditions level of service analyses indicate that the proposed East Lake Specific Plan (Phase I) will significantly impact one (1) of the six (6) basic freeway segments. The remaining five (5) basic freeway segments are forecast to operate at acceptable levels of service under the Year 2022 With ELSP Project Phase I traffic conditions. It should be noted that the planned improvements from the Railroad Canyon Road Interchange Project have been included in the background traffic conditions for Year 2022. The improvements listed below have been identified to address the traffic impacts at the basic freeway segments significantly impacted by the Year 2022 With ELSP Project Phase I traffic:

- 6. I-15 Southbound from Bundy Canyon Road to Baxter Road: Add one (1) general purpose lane in the southbound direction.

15.2.1.3 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

The results of the Year 2040 With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed East Lake Specific Plan (Buildout) will significantly impact four (4) of the six (6) basic freeway segments. The remaining two (2) basic freeway segments are forecast to operate at acceptable levels of service under the Year 2040 With ELSP Project Buildout traffic conditions. It should be noted that the planned improvements from the Railroad Canyon Road Interchange Project have been included in the background traffic conditions for Year 2040. The improvements listed below have been identified to address the traffic impacts at the basic freeway segments significantly impacted by the Year 2040 With ELSP Project Buildout traffic:

- 1. I-15 Northbound from Baxter Road to Bundy Canyon Road: Add one (1) general purpose lane in the northbound direction.
- 2. I-15 Northbound from Bundy Canyon Road to Railroad Canyon Road: Add one (1) general purpose lane in the northbound direction.

- 5. I-15 Southbound from Railroad Canyon Road to Bundy Canyon Road: Add one (1) general purpose lane in the southbound direction.
- 6. I-15 Southbound from Bundy Canyon Road to Baxter Road: Add one (1) general purpose lane in the southbound direction.

15.2.2 Freeway Merge And Diverge Segments

15.2.2.1 Existing With East Lake Specific Plan Project Buildout Traffic Conditions

The results of the Existing With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed East Lake Specific Plan (Buildout) will not have a significant impact at any of the four (4) freeway merge and diverge segments. All four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service under the Existing With ELSP Project Buildout traffic conditions.

15.2.2.2 Year 2022 With East Lake Specific Plan Project Phase I Traffic Conditions

The results of the Year 2022 With ELSP Project Phase I traffic conditions level of service analyses indicate that the proposed Project (Phase I) will not have a significant impact at any of the four (4) freeway merge and diverge segments. All four (4) freeway merge and diverge segments are forecast to operate at acceptable levels of service under the Year 2022 With ELSP Project Phase I traffic conditions. It should be noted that the planned improvements from the Railroad Canyon Road Interchange Project have been included in the background traffic conditions for Year 2022.

15.2.2.3 Year 2040 With East Lake Specific Plan Project Buildout Traffic Conditions

The results of the Year 2040 With ELSP Project Buildout traffic conditions level of service analyses indicate that the proposed East Lake Specific Plan (Buildout) will significantly impact one (1) of the four (4) freeway merge and diverge segments. The remaining three (3) freeway merge and diverge segments are forecast to operate at acceptable levels of service under the Year 2040 With ELSP Project Buildout traffic conditions. It should be noted that the planned improvements from the Railroad Canyon Road Interchange Project have been included in the background traffic conditions for Year 2040. The improvements listed below have been identified to address the traffic impacts at the freeway merge segment significantly impacted by the Year 2040 With ELSP Project Buildout traffic:

- 4. I-15 Southbound On-Ramp from Railroad Canyon Road: The addition of the fourth southbound general purpose lane previously mentioned (Section 15.2.1.3) to mitigate basic freeway segment No. 5 (I-15 Southbound from Railroad Canyon Road to Bundy Canyon Road) under Year 2040 With ELSP Project Buildout traffic conditions will sufficiently offset the adverse level of service for this merge segment. No additional mitigation is needed.